

SAFETY DATA SHEET # 2200 REVISION #16 DATE REVISED: 08/30/2018

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade Name(s): (CELITE® = C) C206, C209, C209C, C230, C266, C292, C321, C392, C410, C441, C500, FC, SNOW FLOSS®, C266C, CELITE

FOR CONCRETE, SNOW FLOSS C, SIL-O-CEL®

USES: FUNCTIONAL FILLER OR FILTER AID IN A VARIETY OF APPLICATIONS.

Generic Name: NATURAL DIATOMACEOUS EARTH
CAS: 61790-53-2
Chemical Name: SILICA
EINECS: 310-127-6
Manufacturer: IMERYS
Formula: SiO₂

Address: 1732 NORTH FIRST STREET, SUITE 450 Telephone: (805) 737-1239

 City: SAN JOSE
 State: CA
 Zip: 95112
 Emergency: CHEMTREC – USA: (800) 424-9300

 International: +01 (703) 527-3887 (collect)

2. HAZARD IDENTIFICATION

2.1

PHYSICAL AND CHEMICAL HAZARDS: NO CLASSIFICATION.
HUMAN HEALTH: QUARTZ: STOT RE 1 – H372.
ENVIRONMENT: NO CLASSIFICATION.

2.2 Label Elements:

GHS PICTOGRAM



- SIGNAL WORD: DANGER
- HAZARD STATEMENT:

H372 CAUSES DAMAGE TO LUNGS THROUGH PROLONGED OR REPEATED EXPOSURE VIA INHALATION.

 PRECAUTIONARY STATEMENTS: P260 DO NOT BREATHE DUST.

P285 IN CASE OF INADEQUATE VENTILATION WEAR RESPIRATORY PROTECTION.

P501 DISPOSE OF CONTENTS/CONTAINERS IN ACCORDANCE WITH LOCAL REGULATIONS.

LONG TERM EXPOSURE TO CRYSTALLINE SILICA CAN CAUSE LUNG INJURY (SILICOSIS). IARC AND NTP HAVE DETERMINED THAT CRYSTALLINE SILICA INHALED FROM OCCUPATIONAL SOURCES CAN CAUSE CANCER IN HUMANS. RISK OF INJURY IS DEPENDENT ON THE DURATION AND LEVEL OF EXPOSURE.

3. COMPOSITION/INFORMATION ON INGREDIENTS			
INGREDIENT NAME:	CAS NUMBER:	%	PEL AND TLV (except as noted)
NATURAL DIATOMACEOUS EARTH (DE) - AMORPHOUS SILICA	61790-53-2	100	
THIS PRODUCT MAY CONTAIN UP TO 7% CRYSTALLINE SILICA: CRISTOBALITE	14464-46-1	< 3	.025mg/M₃RESPIRABLE CRISTOBALITE, ACGIH
QUARTZ	14808-60-7	< 4	.025mg/M₃ RESPIRABLE QUARTZ, ACGIH

4. FIRST AID MEASURES

Inhalation: REMOVE TO FRESH AIR. DRINK WATER TO CLEAR THROAT AND BLOW NOSE TO EVACUATE DUST.

Eyes: FLUSH EYES WITH LARGE QUANTITIES OF WATER. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN.

Skin Contact: NA Skin Absorption: NA Ingestion: NA

5. FIRE FIGHTING MEASURES

Flash Point (Method): NONFLAMMABLE NFPA Flammable/Combustible Liquid Classification: NA

Flammable Limits: LEL: NA UEL: NA Auto-Ignition Temperature: NA

Extinguishing Media: NA Unusual Fire or Explosion Hazards: NONE Special Fire-Fighting Procedure: NONE

6. ACCIDENTAL RELEASE MEASURES

Procedure for Spill/ Leak: VACUUM CLEAN DUST WITH EQUIPMENT FITTED WITH HEPA FILTER. USE A DUST SUPPRESSANT SUCH AS WATER IF SWEEPING IS NECESSARY.

7. HANDLING AND STORAGE

MINIMIZE DUST GENERATION AND ACCUMULATION. AVOID BREATHING DUST. AVOID CONTACT WITH EYES. SEAL BROKEN BAGS IMMEDIATELY. CONTINUE TO FOLLOW ALL SDS/ LABEL WARNING WHEN HANDLING EMPTY CONTAINERS.

Rev: 16 / Page 1 of 2

MSDS: 2200

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Goggles: GOGGLES OR SAFETY GLASSES WITH SIDESHIELDS ARE RECOMMENDED.

Gloves: NOT NORMALLY REQUIRED.

Respirator: <10X PEL, USE AN N95 QUARTER OR HALF MASK RESPIRATOR; <50X PEL, USE A FULL FACE RESPIRATOR EQUIPPED WITH N95 FILTERS; <200X PEL, USE A POWERED AIR PURIFYING RESPIRATOR (POSITIVE PRESSURE) WITH N95 FILTERS; >200X

PEL, USE A FULL FACE, TYPE C SUPPLIED AIR RESPIRATOR (CONTINUOUS FLOW MODE).

Ventilation: USE SUFFICIENT NATURAL OR MECHANICAL VENTILATION TO KEEP DUST LEVEL BELOW PEL.

Other: Special Considerations for Repair/Maintenance of Contaminated Equipment: INSURE PROPER RESPIRATORY PROTECTION.

ACGIH TLV: .025mg/M3 RESPIRABLE QUARTZ OR CRISTOBALITE

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor: FINE GRAY POWDER, NO ODOR.

Boiling Point: Evaporation Rate (Specific Gravity (water = 1): NA =1): NA 2.3 Vapor Pressure: **Melting Point:** % Volatile by Volume: NA ND NIL Water Solubility (%): Vapor Density (Air=1): 5-10 NA NA pH:

10. STABILITY AND REACTIVITY

MATERIAL IS STABLE. HAZARDOUS POLYMERIZATION CANNOT OCCUR

Chemical Incompatibilities: HYDROFLUORIC ACID Conditions to Avoid: NONE IN DESIGNED USE.

11. TOXICOLOGY INFORMATION

Summary: THIS PRODUCT CONTAINS CRYSTALLINE SILICA (CS), WHICH IS CONSIDERED A HAZARD BY INHALATION. IARC HAS CLASSIFIED CS AS CARCINOGENIC FOR HUMANS (GROUP 1). CS IS LISTED BY NTP AS A KNOWN HUMAN CARCINOGEN. CS IS ALSO A KNOWN CAUSE OF SILICOSIS, A NONCANCEROUS LUNG DISEASE.

12. ECOLOGICAL INFORMATION

GENERALLY CONSIDERED CHEMICALLY INERT IN THE ENVIRONMENT. USED MATERIAL WHICH HAS BECOME CONTAMINATED MAY HAVE SIGNIFICANTLY DIFFERENT CHARACTERISTICS BASED ON THE CONTAMINANT AND SHOULD BE EVALUATED ACCORDINGLY

13. DISPOSAL CONSIDERATIONS

WASTE IS NOT HAZARDOUS AS DEFINED BY RCRA (40 CFR 261). OTHER STATE AND LOCAL REGULATIONS MAY VARY, CONSULT LOCAL AGENCIES AS NEEDED. USED MATERIAL WHICH HAS BECOME CONTAMINATED MAY HAVE SIGNIFICANTLY DIFFERENT CHARACTERISTICS BASED ON THE CONTAMINANTS AND SHOULD BE EVALUATED ACCORDINGLY.

14. TRANSPORTATION INFORMATION

D.O.T. Proper Shipping Name: EARTH, DIATOMACEOUS, CRUDE OR GROUND Hazard Classification: Not Classified

Reportable Quantities: NA UN (United Nations), NA (North America) Number: NA

15. REGULATORY INFORMATION

OSHA Hazard Communications Standard, 29 CFR 1910.1200: MATERIAL IS CONSIDERED HAZARDOUS, SEE SECTION 3.

RCRA: THIS MATERIAL IS NOT DEFINED AS HAZARDOUS WASTE PER 40 CFR 261.

TSCA: THIS MATERIAL IS LISTED IN THE TSCA INVENTORY, AND IS NOT OTHERWISE REGULATED BY TSCA SEC. 4, 5, 6, 7 OR 12.

CERCLA: MATERIAL IS NOT REPORTABLE UNDER CERCLA, LOCAL REQUIREMENTS MAY VARY.


SARA: 311/312 HAZARD CATEGORIES -IMMEDIATE AND DELAYED HEALTH, 313 REPORTABLE INGREDIENTS - NONE.


Canada: THIS PRODUCT IS LISTED ON THE DSL.

⚠California Proposition 65: WARNING THIS PRODUCT CAN EXPOSE YOU TO CHEMICALS INCLUDING CRYSTALLINE SILICA, WHICH IS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER. FOR MORE INFORMATION GO TO www.P65Warnings.com.

EU (REGULATION (EC) N° ° 1272/2008): THIS MATERIAL IS LABELED AND SUPPORTED ACCORDINGLY WITH GHS STANDARDS. European Inventory of Existing Chemicals (EINECS): ALL OF THE COMPONENTS OF THIS PRODUCT ARE INCLUDED ON EINECS.

16. OTHER INFORMATION











Rev: 16 / Page 2 of 2

Revisions Made Since Last Version: Compliance with 29 CFR 1910.1200 (OSHA) Hazard Communication Standard. Revised California Proposition 65 language in Section #15.

As of the date of preparation of this document, the foregoing information is believed to be accurate and is provided in good faith to comply with applicable federal and state law(s). However, no warranty or representation with respect to such information is intended or given. Always assume that unless this document is viewed on the Imerys Filtration website (www.imerys-filtration.com), this document may not be fully current and upto-date. End of SDS.