Material Safety Data Sheet

0816OI, 0826OI Series RD PRO 100% Silicone Sealant – RTV – Acetoxy Cure

MSDS No. 0080A, Rev. 7

Emergency Phone No. 800-535-5053 - INFOTRAC

ECTION 1 – P	RODUCT NAME & 1	MANUFACTURER 1	INFORM	ATION			
RD PRO 100% Silicone Sealant – Industrial Grade – RTV – Acetoxy Cure							
Red Devil, Inc. 918-825-5744							
4175 Webb Street							
Pryor, Oklahoma 74361							
- COMPOSITI	ON / HAZARDOUS 1	INGREDIENTS	%	TLV	PEL	UNITS	
17689-77-9)			< 6%	NE	NE		
** (4253-34-3)			< 6%	10	10	ppm	
(13463-67-7) (In white	& colors only)		< 5%	10	15	mg/m3	
(7631-86-9)			< 13	20	20	mg/m3	
Hydroxy-terminated Dimethyl Siloxane (70131-67-8)			> 50	10	10	ppm	
63148-62-9)			< 10	10	10	ppm	
Non-hazardous ingredients*				NA	NA		
*Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). **Observe limits for acetic acid formed during curing on exposure to water or humid air. ***Inhalation of particulates unlikely due to product's physical state. Calculated VOC: < 3%/wt (<30 g/L). CARB Compliance: Yes. Prop 65 Ingredients: None.							
S	ECTION 3 – HAZAR	DS IDENTIFICATION	ON				
Skin Contact	Skin Absorption	Eye Contact	⊠ Inhala	tion	⊠ Inge	estion	
Clear/opaque or colored paste. Harmful if swallowed or absorbed through skin. May cause eye & skin irritation. May cause nose, throat & respiratory tract irritation.							
known.							
	SECTION 4 – FIRS	T AID MEASURES					
SKIN CONTACT Wash w/ soap & water for @ least 15 minutes. Get medical attention if symptoms persist. Remove & wash contaminated clothing.							
E CONTACT Immediately flush w/ large quantities of water for @ least 15 minutes until irritation subsides. Get medical attention.							
No first aid should be needed under normal use. Remove to fresh air if needed.							
Not intended for ingestion. No first aid should be needed. Get medical attention if irritation persists. Treat according to person's condition & specifics of exposure.							
	RD PRO 100% Sili Red Devil, Inc. 4175 Webb Street Pryor, Oklahoma 7- COMPOSITI 17689-77-9) ** (4253-34-3) (13463-67-7) (In white (7631-86-9) imethyl Siloxane (7013) 63148-62-9) ents* re not considered hazare limits for acetic acid foulates unlikely due to pr /wt (<30 g/L). CARB C SI Skin Contact Copaque or colored paste rritation. c: (Eye) – Direct contact ges. (Oral) – No signific known. Wash w/ soap & Immediately flus No first aid shou Not intended for	RD PRO 100% Silicone Sealant – Industrial Grade – 1 Red Devil, Inc. 918-825-5744 4175 Webb Street Pryor, Oklahoma 74361 - COMPOSITION / HAZARDOUS 1 17689-77-9) ** (4253-34-3) (13463-67-7) (In white & colors only) (7631-86-9) imethyl Siloxane (70131-67-8) 63148-62-9) ents* re not considered hazardous under the OSHA Hazard Come limits for acetic acid formed during curing on exposure to ulates unlikely due to product's physical state. //wt (<30 g/L). CARB Compliance: Yes. Prop 65 Ingredier SECTION 3 – HAZAR Skin Contact SECTION 3 – Washed or absorbed ritation. (Eye) – Direct contact may cause moderate irritation. (Sk ges. (Oral) – No significant effects expected from a single sknown. SECTION 4 – FIRS Wash w/ soap & water for @ least 15 minutes. Get Immediately flush w/ large quantities of water for @ No first aid should be needed under normal use. Re Not intended for ingestion. No first aid should be needed under normal use. Re	RD PRO 100% Silicone Sealant – Industrial Grade – RTV – Acetoxy Cure Red Devil, Inc. 918-825-5744 4175 Webb Street Pryor, Oklahoma 74361 - COMPOSITION / HAZARDOUS INGREDIENTS 17689-77-9) ** (4253-34-3) (13463-67-7) (In white & colors only) (7631-86-9) methyl Siloxane (70131-67-8) 63148-62-9) ents* re not considered hazardous under the OSHA Hazard Communication Standard (29 CFR elimits for acetic acid formed during curing on exposure to water or humid air. ulates unlikely due to product's physical state. //vt (<30 g/L). CARB Compliance: Yes. Prop 65 Ingredients: None. SECTION 3 — HAZARDS IDENTIFICATION SECURITY (GP) Skin Contact Skin Absorption Eye Contact Copaque or colored paste. Harmful if swallowed or absorbed through skin. May cause eye & ritation. (Eye) — Direct contact may cause moderate irritation. (Skin) — May cause moderate irritation. (Eye) — Direct contact may cause moderate irritation. (Skin) — May cause moderate irritation. SECTION 4 — FIRST AID MEASURES Wash w/ soap & water for @ least 15 minutes. Get medical attention if symptoms per Immediately flush w/ large quantities of water for @ least 15 minutes until irritation is No first aid should be needed under normal use. Remove to fresh air if needed. Not intended for ingestion. No first aid should be needed. Get medical attention if irritation is first aid should be needed. Get medical attention if irritation is first aid should be needed. Get medical attention if irritation is not intended for ingestion. No first aid should be needed. Get medical attention if irritation is first aid should be needed. Get medical attention if irritation is first aid should be needed. Get medical attention if irritation is first aid should be needed. Get medical attention if irritation is first aid should be needed. Get medical attention if irritation is first aid should be needed. Get medical attention if irritation is first aid should be needed. Get medical attention if irritation.	Red Devil, Inc. 918-825-5744 4175 Webb Street Pryor, Oklahoma 74361 - COMPOSITION / HAZARDOUS INGREDIENTS ** ** ** ** ** ** ** ** **	Red Devil, Inc. 918-825-5744 4175 Webb Street Pryor, Oklahoma 74361 - COMPOSITION / HAZARDOUS INGREDIENTS	Red Devil, Inc. 918-825-5744 4175 Webb Street Pryor, Oklahoma 74361 - COMPOSITION / HAZARDOUS INGREDIENTS	

SECTION 5 – FIRE FIGHTING MEASURES							
FLAMMABLE Yes No							
EXTINGUISHING Carbon Dioxide, Dry Chemical, Foam, Water Spray							
MEDIA FLASHPOINT (°F) & > 212F (Closed Cup) METHOD	UPPER EXPLOSIVE LIMIT NE (% BY VOLUME)						
LOWER EXPLOSIVE LIMIT (% BY VOLUME)	AUTOIGNITION NE TEMPERTURE (°F)						
UNUSUAL FIRE & EXPLOSION None	TEMPERIURE (P)						
HAZARDS SPECIAL Wear self-contained breathing apparatus pressure demand (NIOSH approved or equivalent) & full protective gear. Use water spray to FIREFIGHTING cool exposed surfaces. Thermal breakdown of this product during fire or high heat conditions may evolve the following hazardous decomposition products: Silicon dioxide. Carbon oxides & traces of incompletely burned carbon compounds. Formaldehyde.							
SECTION 6 - ACCIDEN	ΓAL RELEASE MEASURES						
PROCEDURES Wear proper protective equipment (Section 8). Use absorb	ent material or scrape up dried material & place in approved container.						
SECTION 7 – HAN	NDLING & STORAGE						
	rnally. Do not breathe vapors. Use w/ adequate ventilation. Product evolves d air. Provide ventilation during use to control acetic acid within exposure void eye contact. Avoid skin contact.						
STORAGE REQUIREMENTS -	isture. Avoid extreme heat or cold. Store away from oxidizing materials. When ence of air, product may form formaldehyde vapors.						
SECTION 8 – EXPOSURE CON	TROL / PERSONAL PROTECTION						
RESPIRATORY No respiratory protection should be needed. As Engineering Controls, Local & General Ventilation is recommended. Provide adequate ventilation to control exposures within guidelines of OSHA PEL: TWA 10 ppm & ACGIG TLV: TWA 10 ppm, STEL 15 ppm. Use respiratory protection if adequate local exhaust ventilation unavailable. OSHA respirator regulations 29 CFR 1910.134 should be followed, using NIOSH/MSHA approved respirators. Spills: Full face respirator.							
EYEWEAR Goggles or safety glasses w/ side shields. Avoid eye contact.							
CLOTHING / SLOVES Nitrile rubber or butyl rubber gloves. Avoid skin contact.							
HYGENIC PRACTICES Remove & wash contaminated clothing before re-use. Wash hands before breaks & @ end of workday.							
SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES							
PHYSICAL STATE Viscous paste	ODOR & Clear or colored paste w/ acetic acid odor APPEARANCE						
SPECIFIC GRAVITY Approximately 1.0 to 1.1	VAPOR DENSITY NE (AIR=1)						
EVAPORATION RATE NE	BOILING RANGE (°F) NE						
pH NE	SOLUBILITY IN NE WATER						
VAPOR PRESSURE (MM NE Hg)	%/WT VOLATILE NE (TNV)						
SECTION 10 – STABILITY AND REACTIVITY							
STABILITY Xes No Stable under normal conditions.							
INCOMPATABILITY Yes No Materials to Avoid: Water, moisture or humid air can cause hazardous vapors to form (Sec. 8). Oxidizing material can cause a reaction.							
CONDITIONS None. TO AVOID							
HAZARDOUS POLYMERIZATION/HAZARDOUS PECAMPOSITION PRODUCTS Hazardous polymerization will not occur under normal conditions. Normal decomposition products, ie: COx, NOx.							

SECTION 11 - TOXICOLOGICAL INFORMATION / CARCINOGENICITY				
ACGIH	No known applicable information. This product does not contain carcinogens (@0.1% or greater) as defined by IARC, NTP or OSHA.			
OSHA	No known applicable information. See above.			
IARC	No known applicable information. See above.			
NTP	No known applicable information. See above.			
DATA WITH POSSIBLE RELEVANCE TO HUMANS	No known applicable information. See above.			

SECTION 12 – ECOLOGICAL INFORMATION

AQUATIC TOXICITY Complete information is not yet available.

Ecotoxicity Classification Criteria:

Hazard Parameters (LC50 or EC50) High Medium Low Acute Aquatic Toxicity mg/L <=1 >1 & <=100 >100 Acute Terrestrial Toxicity <=100 >100 & <=2000 >2000 (Table adapted from "Environmental Toxicology & Risk Assessment", ASTM STP 1179, p. 34, 1993)

(Table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the section concerning the overall ecological safety of this material.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

Dispose of material in accordance w/ Federal, State & Local regulations.

EPA WASTE CODE IF DISCARDED (40CFR Sec.261)

None. RCRA Hazard Class (40 CFR 261): Not classified as a hazardous waste. State or local laws may impose additional regulatory requirements regarding disposal.

SECTION 14 - TRANSPORT INFORMATION

SPECIAL SHIPPING INFORMATION

<u>DOT Road Shipment Information (49 CFR 172.101):</u> Not subject to DOT. <u>Ocean Shipment (IMDG)</u>: Not subject to IMDG code. <u>Air Shipment (IATA)</u>: Not subject to IATA regulations.

SECTION 15 – REGULATORY INFORMATION						
CERCLA – SARA HAZARD CATEGORY	Section 304 CERCLA: None. Section 302 (Extremely Hazardous Substances): None. Section 312 (Hazard Class): Acute: Yes. Chronic: No. Fire: No. Pressure: No. Reactive: No.	U.S. STATE REGS	See Section 16.			
SARA 313	None present or none present in regulated quantities.	TSCA	All ingredients either on TSCA Inventory or exempt.			

SECTION 16 – OTHER INFORMATION / SPECIAL PRECAUTIONS / LEGEND

Prop 65 Ingredients: (Known to State of California to cause cancer) None. NJ Right-to-Know: (Top 5 Ingredients): Hydroxy-terminated Dimethyl Siloxane (70131-67-8), Silica, amorphous (7631-86-9), Methyltriacetoxysilane (4253-34-3), Ethyltriacetoxysilane (17689-77-9), Polydimethylsiloxane (63148-62-9). Pennsylvania Right-to-Know (Non-Haz @ >3%): Dimethyl siloxane, hydroxy-terminated (70131-67-8). Ingredients Known to State of California to cause birth defects or reproductive harm: None. NFPA Profile: Health: 2, Flammability: 1, Reactivity: 0. HMIS Profile: Health: 1, Flammability: 0, Reactivity: 0, PPE: B. INTERNATIONAL EMERGENCY NUMBER: 352-323-3500 - INFOTRAC

<u>LEGEND</u>: NA – Not Applicable, NE – Not Established, UN – Unavailable, VOC – Volatile Organic Compound, PEL – Permissible Exposure Limit, TLV – Threshold Limit Value, STEL – Short Term Exposure Limit, MSDS – Material Safety Data Sheet, ACGIH – American Conference of Governmental Industrial Hygienists, SARA – Superfund Amendments & Reauthorization Act of 1986, OSHA – Occupational Safety & Health Administration, HMIS – Hazardous Materials Identification System, NTP – National Toxicology Program, CEIL – Ceiling Exposure Limit, CASRN (CAS Number) – Chemical Abstracts Service Registry Number, TSCA – Toxic Substances Control Act, NFPA – National Fire Protection Association.

Reviewed By: Larry G. Brandon VP Technology & General Manager January 27, 2014

NAME TITLE DATE

The information contained herein has been developed based upon currently available scientific data. New information may be developed from time to time which may render the conclusions of this report obsolete. Therefore, no warranty is extended as to the applicability of this information to the user's intended purpose or for the consequences of its use or misuse.