

SAFETY DATA SHEET

Issuing Date 28-Feb-2018

Revision Date 14-Feb-2019

Revision Number 2



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION

Product identifier

Product Name FOOD GRADE SILICONE AEROSOL

Other means of identification

Product Code(s) 50641

(M)SDS Number WPS-JLI-128

Synonyms JET-LUBE® FOOD GRADE SILICONE AEROSOL

Recommended use of the chemical and restrictions on use

Recommended Use Lubricants, Greases and Release Products

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Identification Jet Lube , LLC.

Address Jet Lube LLC

930 Whitmore Drive

Rockwall, Texas USA 75087

Telephone US Office: Phone:+1-972-771-1000 Fax:+1-972-722-2108

E-mail Sales@jetlube.com

Emergency telephone number

Company Emergency Phone

Number

1-800-699-6318

Emergency Telephone Number CHEMTREC: +1-703-527-3887 (INTERNATIONAL)

1-800-424-9300 (NORTH AMERICA)

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation Category 3



Aspiration toxicity	Category 1
Flammable Aerosols	Category 1
Gases Under Pressure	Compressed Gas

.

Appearance Clear

Physical state Liquid Aerosol

Odor Petroleum Solvent

GHS Label elements, including precautionary statements

Danger

Hazard statements

Causes mild skin irritation
May be fatal if swallowed and enters airways
Extremely flammable aerosol
Contains gas under pressure; may explode if heated



Precautionary Statements - Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor

Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Protect from sunlight. Store in a well-ventilated place

Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable.

<u>Mixture</u>

Synonyms JET-LUBE® FOOD GRADE SILICONE AEROSOL



Chemical Name	CAS-No	Weight-%	Hazardous Material	Date HMIRA filed and
			Information Review Act	date exemption granted
			registry number (HMIRA	(if applicable)
			registry #)	
Naphtha, petroleum,	64742-49-0	55-60	-	-
hydrotreated light				
n-Hexane	110-54-3	<2	-	-

4. FIRST AID MEASURES

First aid measures

General advice Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get

medical advice/attention. Immediate medical attention is required.

Inhalation Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing

has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical advice/attention. Delayed

pulmonary edema may occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and

persists.

Skin contact In case of contact with liquefied gas, thaw frosted parts with lukewarm water.

Ingestion Aspiration hazard if swallowed - can enter lungs and cause damage. Do NOT induce

vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth

to an unconscious person. Get immediate medical advice/attention.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s)

involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use

personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Indication of any immediate medical attention and special treatment needed

Note to physiciansBecause of the danger of aspiration, emesis or gastric lavage should not be employed

unless the risk is justified by the presence of additional toxic substances.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray.

Unsuitable extinguishing media DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders



may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Ruptured cylinders may rocket.

Hazardous Combustion Products Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact Yes. **Sensitivity to Static Discharge** Yes.

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See

section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Contents under pressure. Empty containers pose a potential fire

and explosion hazard. Do not cut, puncture of weld containers.

Other Information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage

if safe to do so. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce

vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labeled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Use personal

protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapors or mists. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture of weld containers. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and

shoes.



Conditions for safe storage, including any incompatibilities

Storage ConditionsKeep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight.

Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits .

Chemical Name ACGIH TL		LV	OSHA PEL		NIOSH IDLH			
n-Hexane	STEL: 1000 ppm other		other than	TWA	TWA: 500 ppm		IDLH: 1100 ppm	
110-54-3 n-Hexane		ne	TWA: 1800 mg/m ³		Ceiling: 510 ppm 15 min			
		TWA: 50 ppm		(vacated) TWA: 50 ppm		Ceiling: 1800 mg/m ³ 15 min		
		S*		(vacated)	TWA: 180 mg/m ³		TWA: 50 ppm	
	(vacated) STEL: 1000 ppm				TWA: 180 mg/m ³			
				(vacated) S	ed) STEL: 3600 mg/m ³			
Chemical Name	Chemical Name Alberta		British C	British Columbia Ontario TWAEV		V	Quebec	
n-Hexane	Hexane TWA: 50 ppm		TWA: 50 ppm TWA: 20 ppm		TWA: 50 ppm		TWA: 50 ppm	
110-54-3	110-54-3 TWA: 176 mg/m ³		Sł	Skin STEL: 1000 ppm		m	TWA: 176 mg/m ³	
		Skin		Skin		STEL: 1000 pp		
							STEL: 3500 mg/m ³	
							Skin	

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992). See section 15 for national exposure control parameters.

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Impervious gloves. Wear suitable gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.

Antistatic boots.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required. When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or

smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

Wash hands before breaks and immediately after handling the product.



9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state Liquid; Aerosol

Appearance Clear

Odor Petroleum Solvent
Color No information available
Odor Threshold No data available

Property Values Remarks Method

pH

Melting / freezing point No data available None known Boiling point / boiling range $> 60 \, ^{\circ}\text{C} \, / \, 140 \, ^{\circ}\text{F}$ None known Flash Point < -18 °C / 0 °F None known **Evaporation Rate** No data available None known Flammability (solid, gas) No data available None known Flammability Limit in Air None known

Upper flammability limit

No data available

Lower flammability limit

No data available

Vapor pressure

No data available

Vapor pressureNo data availableNone knownVapor densityNo data availableNone known

Relative density 0.666
Water Solubility Insoluble

Solubility(ies) Completely soluble None known

Partition coefficient: n-octanol/water Not Applicable

Autoignition temperatureNo data availableNone knownDecomposition temperatureNo data availableNone knownKinematic viscosityNo data availableNone known

Dynamic viscosity ~1 (@ 40°C)
Explosive properties No information available
Oxidizing properties No information available

Other Information

Softening Point
Molecular Weight
VOC Content (%)
Liquid Density
Bulk Density
Particle Size
Particle Size
No information available

10. STABILITY AND REACTIVITY

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of Hazardous Reactions None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to avoid Heat, flames and sparks. Excessive heat.

Incompatible materialsNone known based on information supplied.

Hazardous Decomposition Products Carbon oxides.



11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. May cause irritation.

Skin contact Specific test data for the substance or mixture is not available. Repeated exposure may

cause skin dryness or cracking. (based on components).

Ingestion Specific test data for the substance or mixture is not available. Potential for aspiration if

swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema

and pneumonitis. May be fatal if swallowed and enters airways.

Information on toxicological effects

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Numerical measures of toxicity

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

 ATEmix (oral)
 25,000.00 mg/kg

 ATEmix (dermal)
 3,000.00 mg/kg

 ATEmix (inhalation-vapor)
 169.17 mg/L

Unknown acute toxicity Component Information

No information available

Chemical Name LD50 Oral		LD50 Dermal	Inhalation LC50	
Naphtha, petroleum, hydrotreated light			= 73680 ppm (Rat) 4 h	
n-Hexane = 25 g/kg (Rat)		= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationMay cause skin irritation.Serious eye damage/eye irritationNo information available.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity No information available.

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Aspiration hazard May be fatal if swallowed and enters airways.



Page 7/11

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish Toxicity to		Daphnia Magna (Water
			Microorganisms	Flea)
Naphtha, petroleum,			-	LC50 96 h: = 2.6 mg/L
hydrotreated light				(Chaetogammarus
				marinus)
n-Hexane		96h LC50: 2.1 - 2.98	-	24h EC50: > 1000 mg/L
		mg/L (Pimephales		
		promelas)		

Persistence and Degradability No information available.

Bioaccumulation There is no data for this product.

MobilityNo information available.Other adverse effectsNo information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused

products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

US EPA Waste Number D001

California Hazardous Waste Codes 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste		
n-Hexane	Toxic		
110-54-3	Ignitable		

14. TRANSPORT INFORMATION

DOT

UN-No. UN1950 Proper Shipping Name AEROSOLS

Hazard Class 2.1

Description UN1950, AEROSOLS, 2.1

Emergency Response Guide 126

Number

TDG

UN Number UN1950 Proper Shipping Name Aerosols



Hazard Class 2.1 Packing Group None

Description UN1950, Aerosols, 2.1

MEX

UN-No. UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1

Description UN1950, Aerosols, 2.1

ICAO

UN-No. UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1

Description UN1950, Aerosols, 2.1

IATA

UN Number UN1950

Proper Shipping Name Aerosols, flammable

Hazard Class2.1Packing GroupNoneERG Code10L

Description UN1950, Aerosols, flammable, 2.1

IMDG

UN Number UN1950
Proper Shipping Name Aerosols
Hazard Class 2

Subsidiary classSee SP63Packing GroupNoneEmS-No.F-D, S-U

Description UN1950, Aerosols, 2.1 (See SP63), (-18°C c.c.)

RID

UN-No. UN1950
Proper Shipping Name Aerosols
Hazard Class 2
Classification code 5F

Description UN1950, Aerosols, 2.1

ADR/RID-Labels 2.1

<u>ADR</u>

UN-No. UN1950
Proper Shipping Name Aerosols
Hazard Class 2
Classification code 5F
Tunnel restriction code (D)

Description UN1950, Aerosols, 2.1, (D)

ADR/RID-Labels 2.1

ADN

UN-No. UN1950
Proper Shipping Name Aerosols
Hazard Class 2
Classification code 5F

Special Provisions 190, 327, 344, 625 **Description** UN1950, Aerosols, 2.1

Hazard Labels 2.1 Limited Quantity 1 L

Ventilation VE01, VE04



15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

Ozone-depleting substances (ODS) Not applicable

Persistent Organic Pollutants Not applicable

Export Notification requirements Not applicable

International Inventories

TSCA Contact supplier for inventory compliance status.

DSL/NDSL Complies.
EINECS/ELINCS Complies.
ENCS Complies.
KECL Complies.
PICCS Complies.
AICS Complies.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS-No	Weight-%	SARA 313 - Threshold Values %
n-Hexane - 110-54-3	110-54-3	<2	1.0

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden release of pressure hazard	Yes
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
n-Hexane	5000 lb		RQ 5000 lb final RQ



_			
	110-54-3		RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

.

Chemical Name	New Jersey	Massachusett	Pennsylvania	Rhode Island	Illinois
		S			
n-Hexane 110-54-3	X	X	X	X	X

16. OTHER INFORMATION

NFPA Health hazards 1 Flammability 4 Instability 0 Physical and Chemical Properties -

HMIS Health hazards 1 Flammability 4 Physical hazards 0 Personal Protection X

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

Revision Date 28-Feb-2018 14-Feb-2019

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

