Material Safety Data Sheet U.S. Department of Labor May be used to comply with Occupational Safety and Health Administration OSHA's Hazard Communication Standard (Non-Mandatory Form) 29 CFR 1910.1200. Standard must be Form Approved consulted for specific requirements. OMB No. 1218-0072 Identity (As Used on Label and List) Note: Blank spaces are not permitted. If any item is not applicable, or **PROPANE** no information is available, the space must be marked to indicate that. **SECTION 1** Supplier's Name E mer gency Telephone Number LENOX-A 800 -628 -8810 Address Telephone Number for Information Number, Street, City, State and ZIP Code 800 - 628 - 8810 **Date Prepared** 301 Chestnut Street June 14, 2010 Signature of Preparer (Optional) East Longmeadow , MA 01028 SECTION II - Hazardous Ingredients / Identity Information **Hazardous Components** Other Limits Specific Chemical Identity, Common Name(s) **OSHA PEL** ACGIH TLV Recommended % (optional) **PROPANE CAS #74-98-6** 1000PPM 1000PPM NA 100 NFPA HAZARD RATINGS HMIS RATINGS Health -1 Health -1 Flammability -4 Flammability -4 Reactivity -0 Reactivity -0 Note: When propane fuel is burned efficiently, the normal by-products of combustion are CO 2 and H20. Inefficient burning may add CO to the by-products of combustion. SECTION III - Physical / Chemical Characteristics **Boiling Point** Specific Gravity (H₂0 - 1) -44° F Liquid @ 60° F .51 Melting Point Vapor Pressure (mm Hg) @ 100° F 197 psig N/A Vapor Density (AIR=1) Evaporation Rate Butyl Acetate -1) @ 1 ATM @ 60° F 1.56 N/A Solubility in Water **Not Soluble** Appearance and Odor Colorless - Rotten Egg Odor SECTION IV - Fire and Explosion Hazard Data Flash Point (Method Used) Flammable Limits LEL UEL -156° F Closed Cup 9.5 2.1 Extinguishing Media Stop flow of gas or oxygen **Special Fire Fighting Procedures** Use water to cool tanks Auto Ignition temp. 842° F Heavier than air (vapor density 1.5). Unusual Fire and Explosion Hazards May travel a considerable distance to a source of ignition and flashback. SECTION V - Reactivity Data Stabilit y → Unstable Conditions to Avoid Stable N/A X Incompatibility (Materials to Avoid) N/A Hazardous Decomposition or Byproducts None Hazardous May Occur Conditions to Avoid Polymerization → Will Not Occur X N/A

SECTION VI - Health H	azard Data				
Routes of Entry →	Inhalation? YES			in? ES	Ingestion? NO
Health Hazards (Acute and Chronic)					
Contact with liquid propane may cause frost burns					
Carcinogenicity →	NTP? N/A			onographs? I/ A	OSHA Regulated? N/A
Signs and Symptoms of Exposure High concentrations may cause headaches and drowsiness.					
Medical Conditions Generally Aggravated by Exposure N/A					
Emergency and First Aid Procedures					
Remove exposed person from contaminated area.					
Warning					
This fuel, and byproducts of combustion of this fuel, contain chemicals					
known to the State of California to cause cancer, birth defects, and					
other reproductive harm.					
SECTION VII - Precautions for Safe Handling and Use					
Steps to be Taken in Case Material is Released or Spilled					
Remove ignition sources and ventilate area.					
Waste Disposal Method Vent gas to atmosphere in flame free, spark free area outdoors.					
Precautions to be Taken in Handling and Storing					
Store at temperatures below 120° F in well ventilated, spark free, flame					
free area.					
Other Precautions None					
SECTION VIII - Control Measures					
Respiratory Protection (Specify Type) Not required with normal use.					
Ventilation →	Local Exhaust N/A	Mechan	ical (General) N/A	Special N/A	Other N/A
Protective Gloves Not required		Eye Protection Not required			
Other Protective Clothing or Equipment Not required					
Work / Hygienic Practices N/A					
SECTION IX - Shipping Information					
WHMIS Classification: A - Con		nable Gas	Class: 2.1		
DOT	Proper Shipping Name Petroleum Gas, Liquefied		Hazard Classification UN. No. Flammable Gas 1075		UN. No.