Xylene



Section 1 Product Description

Product Name: Xylene

Recommended Use: Science education applications **Synonyms:** Xylol, Dimethylbenzene

Distributor: Carolina Biological Supply Company

2700 York Road, Burlington, NC 27215

1-800-227-1150

Chemical Information: 800-227-1150 (8am-5pm (ET) M-F)

Chemtrec: 800-424-9300 (Transportation Spill Response 24 hours)

Section 2

Hazard Identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

WARNING









Flammable liquid and vapor. Causes skin irritation. Suspected of causing cancer. Very toxic to aquatic life.

GHS Classification:

Hazardous to the aquatic environment - Acute Category 1, Skin Corrosion/Irritation Category 2, Carcinogenicity Category 2, Flammable Liquid Category 3

Other Safety Precautions: IF exposed or concerned: Get medical advice/attention.

Section 3 Composition / Information on Ingredients CAS# % Chemical Name m-Xylene 108-38-3 42 Ethylbenzene 100-41-4 21 95-47-6 19 o-Xylene p-Xylene 106-42-3 18

Section 4 First Aid Measures

Emergency and First Aid Procedures

Inhalation: In case of accident by inhalation: remove casualty to fresh air and keep at rest.

Eyes: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. **Skin Contact:** IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

water/shower. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and

wash before reuse.

Ingestion: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Section 5 Firefighting Procedures

Extinguishing Media: Use dry chemical, CO2 or appropriate foam.

Fire Fighting Methods and Protection: Firefighters should wear full protective equipment and NIOSH approved self-contained

breathing apparatus.

Fire and/or Explosion Hazards: Vapors may travel back to ignition source. Closed Containers exposed to heat may

explode.

Hazardous Combustion Products: Carbon dioxide, Carbon monoxide

Xylene Page 1 of 5

Section 6

Spill or Leak Procedures

Steps to Take in Case Material Is Released or Spilled:

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill. Ventilate the contaminated area. Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Collect spillage.

Section 7

Handling and Storage

Handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/.../ equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Avoid release to the environment. Wear protective gloves/protective clothing/eye

protection/face protection. Use personal protective equipment as required.

Storage: Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Keep container tightly

closed in a cool, well-ventilated place.

Storage Code: Red - Flammables. Store in approved flammable containers. Store away from oxidizing materials.

Section 8

Protection Information

	<u>ACGIH</u>		OSHA PEL	
Chemical Name	<u>(TWA)</u>	(STEL)	<u>(TWA)</u>	(STEL)
m-Xylene	100 ppm TWA	150 ppm STEL	100 ppm TWA; 435 mg/m3 TWA	N/A
Ethylbenzene	20 ppm TWA	N/A	100 ppm TWA; 435	N/A
o-Xylene	100 ppm TWA	150 ppm STEL	mg/m3 TWA 100 ppm TWA; 435 mg/m3 TWA	N/A
p-Xylene	100 ppm TWA	150 ppm STEL	100 ppm TWA; 435 mg/m3 TWA	N/A

Control Parameters

Engineering Measures: Local exhaust ventilation or other engineering controls are normally required when

handling or using this product to avoid overexposure.

Personal Protective Equipment (PPE):

Respiratory Protection:

Respirator Type(s):

Eye Protection:

Lab coat, apron, eye wash, safety shower.

No respiratory protection required under normal conditions of use.

None required where adequate ventilation is provided. If airborne concentrations are above the applicable exposure limits, use NIOSH/MSHA approved respiratory protection. Wear chemical splash goggles when handling this product. Have an eye wash station

available.

Skin Protection: Avoid skin contact by wearing chemically resistant gloves, an apron and other protective

equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving

work. Nitrile

Gloves:

ioves:

Section 9

Physical Data

Formula: C6H4(CH3)2

Molecular Weight: 106.17 g/mol Appearance: Colorless Liquid Odor: Strong Aromatic

Odor Threshold: 6 mg/m3 pH: No data available Melting Point: -48 - -13 C

Vapor Pressure: 88 - 120 hPa at 25 °C Evaporation Rate (BuAc=1): 0.61 Vapor Density (Air=1): 3.6 Specific Gravity: 0.86

Solubility in Water: Slightly Soluble Log Pow (calculated): 2.77 - 3.15 Autoignition Temperature: 465 - 525 C

Xylene Page 2 of 5

Boiling Point: 138 - 141 C Flash Point: 29 C

Flammable Limits in Air: 1.0 - 7.0%

Decomposition Temperature: No data available

Viscosity: No data available Percent Volatile by Volume: >99%

Section 10 Reactivity Data

Not generally reactive under normal conditions. Reactivity:

Chemical Stability: Stable under normal conditions.

Conditions to Avoid: Temperatures above flash point in combination with sparks, open flames, or other

sources of ignition.

Incompatible Materials: Oxidizing materials

Hazardous Decomposition Products: Carbon dioxide, Carbon monoxide

Hazardous Polymerization: Will not occur

Section 11 Toxicity Data

Routes of Entry Inhalation, ingestion, eye or skin contact.

Symptoms (Acute): Central Nervous System Disorders, Respiratory Irritation

Delayed Effects: Central Nervous System Disorders

Dermititis

Acute Toxicity: Chemical Name m-Xylene	CAS Number 108-38-3	Oral LD50 Oral LD50 Rat 4988 mg/kg	Dermal LD50 Dermal LD50 Rabbit 14100 UL/KG	Inhalation LC50 INHALATION LC50 CAT 9500 ppm INHALATION LC50 Mouse 5267
Ethylbenzene	100-41-4	Oral LD50 Rat 3500 mg/kg	Dermal LD50 Rabbit > 5000 mg/kg	ppm INHALATION LC50 Rat 55000 MG/M3 INHALATION LC50 Mouse 35500 MG/M3 INHALATION LC50 Rabbit 4000
o-Xylene	95-47-6	Oral LD50 Rat 3567 mg/kg		ppm INHALATION LC50 CAT 9500 ppm INHALATION LC50 Mouse 4595

Oral LD50 Rat 106-42-3 p-Xylene 3910 mg/kg

INHALATION LC50 CAT 9500

ppm

ppm

Carcinogenicity:

Chemical Name	CAS Number	IARC	NTP	OSHA
m-Xylene	108-38-3	Not listed	Not listed	Not listed
Ethylbenzene	100-41-4	Listed	Not listed	Listed
o-Xylene	95-47-6	Not listed	Not listed	Not listed
p-Xylene	106-42-3	Not listed	Not listed	Not listed

Chronic Effects:

Mutagenicity: No evidence of a mutagenic effect.

Teratogenicity: No evidence of a teratogenic effect (birth defect).

Sensitization: No evidence of a sensitization effect.

Reproductive: No evidence of negative reproductive effects.

Target Organ Effects:

Acute: Central Nervous System, Liver, Respiratory system

Chronic: Respiratory system, Liver, Blood

Page 3 of 5 Xylene

Section 12 **Ecological Data**

Overview: This material is not expected to be harmful to the ecology.

Mobility: No data

Persistence: Evaporation into atmosphere, Biodegradation, Adsorbs to soil.

No data Bioaccumulation: Degradability: No data Other Adverse Effects: No data

Chemical Name CAS Number Eco Toxicity m-Xylene 108-38-3 72 HR EC50 PSEUDOKIRCHNERIELLA SUBCAPITATA 4.9 MG/L [STATIC] Ethylbenzene 100-41-4 96 HR LC50 POECILIA RETICULATA 9.6 MG/L [STATIC] 96 HR LC50 LEPOMIS MACROCHIRUS 32 MG/L [STATIC] 48 HR EC50 DAPHNIA MAGNA 1.8 - 2.4 MG/L 96 HR EC50 PSEUDOKIRCHNERIELLA SUBCAPITATA > 438 MG/L 72 HR EC50 PSEUDOKIRCHNERIELLA SUBCAPITATA 4.6 MG/L Aquatic LC50 (96h) Guppy 12 MG/L o-Xylene 95-47-6 Aquatic EC50 (48h) Daphnia 3.2 MG/L 72 HR EC50 PSEUDOKIRCHNERIELLA SUBCAPITATA 4.7 MG/L [STATIC] 192 HR EC50 PSEUDOKIRCHNERIELLA SUBCAPITATA 4.2 MG/L p-Xylene

106-42-3 Aguatic LC50 (96h) Rainbow Trout 2.6 MG/L

72 HR EC50 PSEUDOKIRCHNERIELLA SUBCAPITATA 3.2 MG/L

[STATIC] 3 HR EC50 CHLORELLA VULGARIS 105.1 MG/L

Section 13 **Disposal Information**

Disposal Methods: Dispose in accordance with all applicable Federal, State and Local regulations. Always

contact a permitted waste disposer (TSD) to assure compliance.

Waste Disposal Code(s): If discarded, this product is considered a RCRA ignitable waste, D001.

Section 14 Transport Information

Ground - DOT Proper Shipping Name: Air - IATA Proper Shipping Name:

UN1307 UN1307 **Xylenes Xylenes** Class 3 Class 3 P.G. III P.G. III

Section 15 Regulatory Information

TSCA Status: All components in this product are on the TSCA Inventory.

Chemical Name	CAS Number	§ 313 Name	§ 304 RQ	CERCLA RQ	§ 302 TPQ	CAA 112(2) TQ
m-Xylene	108-38-3	m-Xylene	No	1000lb(454kg) final RQ	No	No
Ethylbenzene	100-41-4	Ethylbenzene	1000 lb RQ	1000lb(454kg) final RQ	No	No
o-Xylene	95-47-6	o-Xylene	No	1000lb(454kg) final RQ	No	No
p-Xylene	106-42-3	p-Xylene	No	100lb(45.4kg) final RQ	No	No

Xylene Page 4 of 5

California Prop 65:



WARNING: Cancer - www.P65Warnings.ca.gov

Section 16	Additional
	Information

The information provided in this (Material) Safety Data Sheet represents a compilation of data drawn directly from various sources available to us. Carolina Biological Supply makes no representation or guarantee as to the suitability of this information to a particular application of the substance covered in the (Material) Safety Data Sheet.

GI	ossary	1
----	--------	---

Giossaiy			
ACGIH	American Conference of Governmental	NTP	National Toxicology Program
	Industrial Hygienists	OSHA	Occupational Safety and Health Administration
CAS	Chemical Abstract Service Number	PEL	Permissible Exposure Limit
CERCLA	Comprehensive Environmental Response,	ppm	Parts per million
	Compensation, and Liability Act	RCRA	Resource Conservation and Recovery Act
DOT	U.S. Department of Transportation	SARA	Superfund Amendments and Reauthorization Act
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
N/A	Not Available	TSCA	Toxic Substances Control Act
		IDLH	Immediately dangerous to life and health

Xylene Page 5 of 5