

SAFETY DATA SHEET

Version 6.8 Revision Date 06/28/2021 Print Date 10/24/2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : *n*-Butyllithium solution

Product Number : 186171 Brand : Aldrich

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.

3050 SPRUCE ST ST. LOUIS MO 63103 UNITED STATES

Telephone : +1 314 771-5765 Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225

Pyrophoric liquids (Category 1), H250

Chemicals which, in contact with water, emit flammable gases (Category 1), H260

Skin corrosion (Category 1B), H314

Serious eye damage (Category 1), H318

Reproductive toxicity (Category 2), H361

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

Aspiration hazard (Category 1), H304

Long-term (chronic) aquatic hazard (Category 2), H411

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements



Pictogram Signal word Danger Hazard statement(s) H225 Highly flammable liquid and vapor. Catches fire spontaneously if exposed to air. H250 In contact with water releases flammable gases which may H260 ignite spontaneously. H304 May be fatal if swallowed and enters airways. H314 Causes severe skin burns and eye damage. May cause drowsiness or dizziness. H336 Suspected of damaging fertility or the unborn child. H361 Toxic to aquatic life with long lasting effects. H411 Precautionary statement(s) P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. P222 Do not allow contact with air. P223 Do not allow contact with water. P231 + P232 Handle under inert gas. Protect from moisture. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. Wash skin thoroughly after handling. P264 P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face

protection.
IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
IF ON SKIN: Immerse in cool water/ wrap in wet bandages.
IF ON SKIN (or hair): Take off immediately all contaminated
clothing. Rinse skin with water/ shower.

IF INHALED: Remove person to fresh air and keep comfortable P304 + P340 + P310 for breathing. Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338 + IF IN EYES: Rinse cautiously with water for several minutes. P310 Remove contact lenses, if present and easy to do. Continue

rinsing. Immediately call a POISON CENTER/ doctor. IF exposed or concerned: Get medical advice/ attention.

P335 + P334 Brush off loose particles from skin. Immerse in cool water/ wrap

in wet bandages.

P363 Wash contaminated clothing before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant

foam to extinguish.

P391 Collect spillage.

P402 + P404 Store in a dry place. Store in a closed container.

Store in a well-ventilated place. Keep container tightly closed. P403 + P233

P403 + P235 Store in a well-ventilated place. Keep cool.

Aldrich - 186171

P308 + P313



P405 Store locked up.

P422 Store contents under inert gas.

P501 Dispose of contents/ container to an approved waste disposal

plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

Reacts violently with water.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Synonyms : Lithium-1-butanide

n-BuLi

n-BuLi n-Butyllithium solution Butyl lithium Lithium-1-butanide

Formula : C₄H₉Li Molecular weight : 64.06 g/mol

Component		Classification	Concentration
Hexanes, isomers			
CAS-No. EC-No. Index-No.	92112-69-1 295-570-2 601-037-00-0	Flam. Liq. 2; Skin Irrit. 2; Repr. 2; STOT SE 3; Asp. Tox. 1; Aquatic Chronic 2; H225, H315, H361, H336, H304, H411	>= 70 - < 90 %
Butyllithium			
CAS-No. EC-No.	109-72-8 203-698-7	Pyr. Liq. 1; 1; Skin Corr. 1B; Eye Dam. 1; H250, H260, H314, H318	>= 10 - < 20 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.



If swallowed

After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Pulmonary failure possible after aspiration of vomit. Call a physician immediately. Do not attempt to neutralise.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2) Dry powder

Unsuitable extinguishing media

Water Foam

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Lithium oxides

Mixture with combustible ingredients.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

May not get in touch with: Water

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Contain spillage, pick up with an electrically protected vacuum cleaner or by wet-brushing and transfer to a container for disposal according to local regulations (see section 13). Do not flush with water. Cover drains. Collect, bind, and pump off spills. Observe possible

material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols. Keep workplace dry. Do not allow product to come into contact with water.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Keep away from heat and sources of ignition. Never allow product to get in contact with water during storage.

Storage stability

Recommended storage temperature 2 - 8 °C

Handle under nitrogen, protect from moisture. Reacts violently with water. Storage class (TRGS 510): 4.2: Pyrophoric and self-heating hazardous materials

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters



Component	CAS-No.	Value	Control parameters	Basis	
Hexanes, isomers	92112-69-	TWA	500 ppm	USA. ACGIH Threshold Limit Values (TLV)	
		STEL	1,000 ppm	USA. ACGIH Threshold Limit Values (TLV)	
		TWA	500 ppm 1,800 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	
		STEL	1,000 ppm 3,600 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	
		TWA	100 ppm 350 mg/m3	USA. NIOSH Recommended Exposure Limits	
		С	510 ppm 1,800 mg/m3	USA. NIOSH Recommended Exposure Limits	
		PEL	500 ppm 1,800 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)	
		STEL	1,000 ppm 3,600 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)	

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm Break through time: 480 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.2 mm Break through time: 30 min

Material tested: Dermatril® P (KCL 743 / Aldrich Z677388, Size M)



data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a)	Appearance	Form: liquid
b)	Odor	No data available
c)	Odor Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	No data available
f)	Initial boiling point and boiling range	No data available
g)	Flash point	-26 °C (-15 °F) - closed cup
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapor pressure	No data available
l)	Vapor density	No data available
m)	Relative density	No data available
n)	Water solubility	No data available
o)	Partition coefficient: n-octanol/water	No data available
p)	Autoignition temperature	No data available



q) Decomposition No data available temperature

r) Viscosity No data availables) Explosive properties No data availablet) Oxidizing properties No data available

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air.

10.2 Chemical stability

Sensitive to air. sensitive to moisture

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Exposure to air.

Warming.

Moisture.

10.5 Incompatible materials

Strong oxidizing agents, Reacts violently with water., Chlorine, Fluorine, Perchlorates.

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Mixture

Acute toxicity

Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the esophagus and the stomach.

Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages:, damage of

respiratory tract

Dermal: No data available

Skin corrosion/irritation

Mixture causes burns.

Serious eye damage/eye irritation

Mixture causes serious eye damage. Risk of blindness!

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity



IARC: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

Reproductive toxicity

Suspected of damaging the unborn child.

Suspected of damaging fertility.

Specific target organ toxicity - single exposure

Mixture may cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

Aspiration hazard, Aspiration may cause pulmonary edema and pneumonitis.

11.2 Additional Information

Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., Inhalation may provoke the following symptoms:, spasm, inflammation and edema of the bronchi, spasm, inflammation and edema of the larynx, Aspiration or inhalation may cause chemical pneumonitis., pulmonary edema, Symptoms of exposure may include burning sensation, coughing, wheezing, laryngitis, shortness of breath, headache, nausea, and vomiting., Lung irritation, chest pain, Gastrointestinal disturbance, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated., Warning: contains n-hexane (CAS#110-54-3) a suspected neurotoxin., May cause nervous system disturbances. Other dangerous properties can not be excluded.

This substance should be handled with particular care.

Handle in accordance with good industrial hygiene and safety practice.

Liver - Irregularities - Based on Human Evidence

Components

Hexanes, isomers

Acute toxicity

Oral: No data available Inhalation: No data available Dermal: No data available

Skin corrosion/irritation

Causes skin irritation. Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available



Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

Suspected of damaging fertility.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table

3.1/3.2)

The value is given in analogy to the following substances: 2-Methylpentane

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

May be fatal if swallowed and enters airways.

Butyllithium

Acute toxicity

Oral: No data available Inhalation: No data available Dermal: No data available

Skin corrosion/irritation

Causes skin irritation. (ECHA)

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available



SECTION 12: Ecological information

12.1 Toxicity

Mixture

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No data available

Components

Hexanes, isomers

No data available

Butyllithium

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

DOT (US)

UN number: 3394 Class: 4.2 (4.3) Packing group: I

Proper shipping name: Organometallic substance, liquid, pyrophoric, water-reactive

(Butyllithium, Hexanes, isomers) Reportable Quantity (RQ): Poison Inhalation Hazard: No

IMDG

UN number: 3394 Class: 4.2 (4.3) Packing group: I EMS-No: F-G, S-M Proper shipping name: ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-

REACTIVE (Butyllithium, Hexanes, isomers)

Marine pollutant : yes

Aldrich - 186171

Millipore

IATA

UN number: 3394 Class: 4.2 (4.3)

Proper shipping name: Organometallic substance, liquid, pyrophoric, water-reactive

(Butyllithium, Hexanes, isomers)

IATA Passenger: Not permitted for transport IATA Cargo: Not permitted for transport

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard, Reactivity Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

No components are subject to the Massachusetts Right to Know Act.

Hexanes, isomers	CAS-No. 92112-69-1	Revision Date 1993-02-16
Butyllithium	109-72-8	2007-03-01
New Jersey Right To Know Components Hexanes, isomers	CAS-No. 92112-69-1	Revision Date 1993-02-16
Butyllithium	109-72-8	2007-03-01

SECTION 16: Other information

Relevant changes since previous version

5. Fire-fighting measures

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See



www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.8 Revision Date: 06/28/2021 Print Date: 10/24/2021

Millipore