**Revision Number:** 006.0

**Issue date:** 10/14/2020

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product name:** **Loctite PL Polyurethane Roof and Flashing Sealant**
**IDH number:** 1675273
**Product type/use:** Sealant
**Restriction of Use:** None identified
**Region:** United States
**Company address:**
Henkel Corporation
One Henkel Way
Rocky Hill, Connecticut 06067
**Contact information:**
Telephone: +1 (860) 571-5100
MEDICAL EMERGENCY Phone: Poison Control Center
1-877-671-4608 (toll free) or 1-303-592-1711
TRANSPORT EMERGENCY Phone: CHEMTREC
1-800-424-9300 (toll free) or 1-703-527-3887
Internet: www.henkelna.com

**This product contains a chemical which is subject to a proposed Environmental Protection Agency (EPA) Significant New Use Restriction (SNUR).**

## 2. HAZARDS IDENTIFICATION

| EMERGENCY OVERVIEW | |
|---|---|
| DANGER: | CAUSES SKIN IRRITATION.<br>MAY CAUSE AN ALLERGIC SKIN REACTION.<br>CAUSES SERIOUS EYE IRRITATION.<br>FATAL IF INHALED.<br>MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING DIFFICULTIES IF INHALED.<br>SUSPECTED OF CAUSING CANCER. |

| HAZARD CLASS | HAZARD CATEGORY |
|---|---|
| ACUTE TOXICITY INHALATION | 2 |
| SKIN IRRITATION | 2 |
| EYE IRRITATION | 2A |
| RESPIRATORY SENSITIZATION | 1 |
| SKIN SENSITIZATION | 1 |
| CARCINOGENICITY | 2 |

**PICTOGRAM(S)**

**Precautionary Statements**

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust or fumes. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection. [In case of inadequate ventilation] wear respiratory protection.

**Response:** IF ON SKIN: Wash with plenty of water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.

**Storage:** Store in a well-ventilated place. Keep container tightly closed. Store locked up.

**Disposal:** Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

3 % of the mixture consists of ingredient(s) of unknown acute toxicity.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

**See Section 11 for additional toxicological information.**

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s) | CAS Number | Percentage* |
|---|---|---|
| Chlorobenzene | 108-90-7 | >= 50 - <= 60 |
| Limestone | 1317-65-3 | >= 30 - <= 40 |
| Silicon dioxide | 7631-86-9 | 0 - 0.1 |
| Talc (Mg3H2(SiO3)4) | 14807-96-6 | 0 - 0.1 |
| Bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate | 59719-67-4 | 1 - 5 |
| Calcium oxide | 1305-78-8 | 1 - 5 |
| [3-(2,3-Epoxypropoxy)propyl]trimethoxysilane | 2530-83-8 | 1 - 5 |
| Toluene-2,6-diisocyanate | 91-08-7 | 1 - 5 |
| Carbon black - Nano | 1333-86-4 | 0.1 - 1 |

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

## 4. FIRST AID MEASURES

**Inhalation:** If inhaled, immediately remove the affected person to fresh air. Immediate medical treatment necessary.

**Skin contact:** Immediately wash skin thoroughly with soap and water. If symptoms develop and persist, get medical attention. Remove contaminated clothes.

**Eye contact:** In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.

**Ingestion:** Do not induce vomiting, seek medical advice immediately.

**Symptoms:** See Section 11.

**Notes to physician:** An individual having a dermal or pulmonary sensitization reaction to this material should be removed from further exposure to any diisocyanate.Treatment based on judgement of the physician in response to reactions of the patient.

## 5. FIRE FIGHTING MEASURES

**Extinguishing media:** Carbon dioxide, foam, powder Water fog.

**Special firefighting procedures:** Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.

**Unusual fire or explosion hazards:** None known.

**Hazardous combustion products:** Nitrous gases Irritating fumes. Isocyanate vapors.

## 6. ACCIDENTAL RELEASE MEASURES

**Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.**

**Environmental precautions:** Ventilated area. Wear appropriate protective equipment and clothing during clean-up. Prevent further leakage or spillage if safe to do so. Do not allow product to enter sewer or waterways.

**Clean-up methods:** Absorb spill with inert material. Shovel material into appropriate container for disposal. Dispose of according to Federal, State and local governmental regulations.

## 7. HANDLING AND STORAGE

**Handling:** Avoid contact with eyes, skin and clothing. Avoid extreme temperatures. Wash thoroughly after handling. Protect from moisture. Use only with adequate ventilation.

**Storage:** For safe storage, store between 18.3 °C (64.9 °F) and 40 °C (104°F) Avoid moisture. Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials.

**For information on product shelf life, please review labels on container or check the Technical Data Sheet.**

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.**

| Hazardous Component(s) | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER |
|---|---|---|---|---|
| Chlorobenzene | 10 ppm TWA | 75 ppm (350 mg/m3) PEL | None | None |
| Limestone | 10 mg/m3 TWA Total dust. | 5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. | None | None |
| Silicon dioxide | 6 mg/m3 TWA | 20 MPPCF TWA 0.8 mg/m3 TWA | None | 3 mg/m3 TWA Respirable fraction. |
| Talc (Mg3H2(SiO3)4) | 2 mg/m3 TWA Respirable fraction. | 0.1 mg/m3 TWA Respirable. 20 MPPCF TWA 2.4 MPPCF TWA Respirable. | None | None |
| Bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate | None | None | None | None |
| Calcium oxide | 2 mg/m3 TWA | 5 mg/m3 PEL | None | None |
| [3-(2,3-Epoxypropoxy)propyl]trimethoxysilane | None | None | None | None |
| Toluene-2,6-diisocyanate | 0.005 ppm STEL Inhalable fraction and vapor. 0.001 ppm TWA Inhalable fraction and vapor. (SKIN) Inhalable fraction and vapor. (Dermal sensitization) (Respiratory sensitization) | None | None | None |
| Carbon black - Nano | 3 mg/m3 TWA Inhalable fraction. | 3.5 mg/m3 PEL | None | None |

**Engineering controls:** Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits.

**Respiratory protection:** Observe OSHA regulations for respirator use (29 CFR 1910.134). Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists. Respirator with combination filter for vapor/particulate.

**Eye/face protection:** Safety glasses with side-shields. Full face protection should be used if the potential for splashing or spraying of product exists.

**Skin protection:** Use impermeable gloves and protective clothing as necessary to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|---|
| **Physical state:** | Solid |
| **Color:** | Black |
| **Odor:** | Slight |
| **Odor threshold:** | Not available. |
| **pH:** | Not applicable |
| **Vapor pressure:** | Not available. |
| **Boiling point/range:** | Not available. |
| **Melting point/ range:** | Not applicable |
| **Specific gravity:** | 1.20 at 25 °C (77°F) |
| **Vapor density:** | Not available. |
| **Flash point:** | Does not flash. |
| **Flammable/Explosive limits - lower:** | Not available. |
| **Flammable/Explosive limits - upper:** | Not available. |
| **Autoignition temperature:** | Not applicable |
| **Flammability:** | Not applicable |
| **Evaporation rate:** | Not available. |
| **Solubility in water:** | Insoluble |
| **Partition coefficient (n-octanol/water):** | Not available. |
| **VOC content:** | 2.2 %; 37 g/l (by weight, calculated using CARB method; g/L less water, less exempts calculated using SCAQMD method) |
| **Viscosity:** | Not available. |
| **Decomposition temperature:** | Not available. |

## 10. STABILITY AND REACTIVITY

| | |
|---|---|
| **Stability:** | Stable under normal conditions of storage and use. |
| **Hazardous reactions:** | Contact with moisture, other materials that react with isocyanates, or temperatures above 350° F (177° C), may cause polymerization. |
| **Hazardous decomposition products:** | Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition. nitrogen oxides Aromatic isocyanates. carbon oxides. carbon monoxide Hydrogen cyanide. |
| **Incompatible materials:** | Oxidizing agents. Alcohols. Water. Strong bases. |
| **Reactivity:** | Not available. |
| **Conditions to avoid:** | Avoid moisture. |

## 11. TOXICOLOGICAL INFORMATION

**Relevant routes of exposure:** Inhalation, Skin, Eyes, Ingestion

**Potential Health Effects/Symptoms**

**Inhalation:** As a result of previous repeated overexposures or a single large dose, certain individuals will develop isocyanate sensitization (chemical asthma) which will cause them to react to a later exposure to isocyanate at levels well below the TLV. Chronic overexposure to isocyanates has been reported to cause lung damage. Dryness of nasal passages, sore throat, cough, tightness of chest, shortness of breath. Persons suffering from allergic reactions to isocyanates should avoid contact with the product. This product may cause sensitization by inhalation and skin contact. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. May cause respiratory tract irritation.

**Skin contact:** Contact with skin can cause irritation and allergic reaction (sensitization) in some individuals. This product may discolor the skin.

**Eye contact:** Contact with eyes will cause irritation.

**Ingestion:** Ingestion of this product may cause nausea, vomiting and diarrhea.

| Hazardous Component(s) | LD50s and LC50s | Immediate and Delayed Health Effects |
|---|---|---|
| Chlorobenzene | Oral LD50 (Rat) = 2,290 mg/kg<br>Oral LD50 (Mouse) = 1,440 mg/kg<br>Oral LD50 (Rabbit) = 2,250 mg/kg | Irritant, Central nervous system, Blood, Liver, Kidney |
| Limestone | None | Nuisance dust |
| Silicon dioxide | Oral LD50 (Rat) = > 22,500 mg/kg<br>Oral LD50 (Mouse) = > 15,000 mg/kg | Nuisance dust |
| Talc (Mg3H2(SiO3)4) | None | No Data |
| Bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate | None | No Records |
| Calcium oxide | None | Irritant, Corrosive, Eyes |
| [3-(2,3-Epoxypropoxy)propyl]trimethoxysilane | None | Allergen, Irritant |
| Toluene-2,6-diisocyanate | None | Allergen, Bone Marrow, Corrosive, Eyes, Irritant, Mutagen, Respiratory, Some evidence of carcinogenicity |
| Carbon black - Nano | Oral LD50 (Rat) = > 8,000 mg/kg | No Data |

| Hazardous Component(s) | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|---|---|---|---|
| Chlorobenzene | No | No | No |
| Limestone | No | No | No |
| Silicon dioxide | No | No | No |
| Talc (Mg3H2(SiO3)4) | No | No | No |
| Bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate | No | No | No |
| Calcium oxide | No | No | No |
| [3-(2,3-Epoxypropoxy)propyl]trimethoxysilane | No | No | No |
| Toluene-2,6-diisocyanate | Reasonably Anticipated to be a Human Carcinogen. | Group 2B | No |
| Carbon black - Nano | No | Group 2B | No |

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

**Information provided is for unused product only.**

**Recommended method of disposal:** Dispose of according to Federal, State and local governmental regulations.

## 14. TRANSPORT INFORMATION

**The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.**

**U.S. Department of Transportation Ground (49 CFR)**

| | |
|---|---|
| **Proper shipping name:** | RQ, Environmentally hazardous substance, solid, n.o.s. |
| **Hazard class or division:** | 9 |
| **Identification number:** | UN 3077 |
| **Packing group:** | III |
| **DOT Hazardous Substance(s):** | Toluene diisocyanate, Toluene diisocyanate |

**International Air Transportation (ICAO/IATA)**

| | |
|---|---|
| **Proper shipping name:** | RQ, Environmentally hazardous substance, solid, n.o.s. |
| **Hazard class or division:** | 9 |
| **Identification number:** | UN 3077 |
| **Packing group:** | III |

**Water Transportation (IMO/IMDG)**

| | |
|---|---|
| **Proper shipping name:** | RQ, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. |
| **Hazard class or division:** | 9 |
| **Identification number:** | UN 3077 |
| **Packing group:** | III |

## 15. REGULATORY INFORMATION

**United States Regulatory Information**

| | |
|---|---|
| **TSCA 8 (b) Inventory Status:** | All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory. |
| **TSCA 12 (b) Export Notification:** | Toluene-2,6-diisocyanate (CAS# 91-08-7). |
| **CERCLA/SARA Section 302 EHS:** | Toluene-2,6-diisocyanate (CAS# 91-08-7). |
| **CERCLA/SARA Section 311/312:** | Immediate Health, Delayed Health |
| **CERCLA/SARA Section 313:** | This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Chlorobenzene (CAS# 108-90-7). Toluene-2,6-diisocyanate (CAS# 91-08-7). |
| **California Proposition 65:** | This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. |

**Canada Regulatory Information**

| | |
|---|---|
| **CEPA DSL/NDSL Status:** | All components are listed on or are exempt from listing on the Canadian Domestic Substances List. |

## 16. OTHER INFORMATION

**This safety data sheet contains changes from the previous version in sections:** This Safety Data Sheet contains changes from the previous version in Section(s): 2, 3, 8, 11, 15

**Prepared by:** Product Safety and Regulatory Affairs

**Issue date:** 10/14/2020

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.