

SAFETY DATA SHEET

Creation Date 03-Jun-2010 Revision Date 20-Mar-2018 Revision Number 1

1. Identification

Product Name 1-Propanol

Cat No.: 41465

CAS-No 71-23-8

Synonyms n-Propyl Alcohol; Propyl alcohol; n-Propanol

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet

Company

Alfa Aesar

Thermo Fisher Scientific Chemicals, Inc.

30 Bond Street

Ward Hill, MA 01835-8099 Tel: 800-343-0660

Fax: 800-322-4757 Email: tech@alfa.com

www.alfa.com

Emergency Telephone Number

During normal business hours (Monday-Friday, 8am-7pm EST), call (800) 343-0660. After normal business hours, call Carechem 24 at (866) 928-0789.

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 2
Serious Eye Damage/Eye Irritation Category 1
Specific target organ toxicity (single exposure) Category 3

Target Organs - Central nervous system (CNS).

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor Causes serious eye damage May cause drowsiness or dizziness

Revision Date 20-Mar-2018 1-Propanol



Precautionary Statements

Prevention

Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor/physician

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None identified

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
n-Propyl alcohol	71-23-8	> 99

4. First-aid measures

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. **Eye Contact**

Immediate medical attention is required.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if

symptoms occur.

Move to fresh air. Get medical attention if symptoms occur. If not breathing, give artificial Inhalation

respiration.

Ingestion Do not induce vomiting. Obtain medical attention.

Revision Date 20-Mar-2018 1-Propanol

Most important symptoms and

effects

Breathing difficulties, Causes eve burns, Causes severe eve damage. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea

and vomiting

Notes to Physician

Treat symptomatically

Fire-fighting measures

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Cool closed containers exposed to fire

with water spray.

Unsuitable Extinguishing Media

Water may be ineffective

Flash Point

15 °C / 59 °F

Method -

No information available

Autoignition Temperature

405 °C / 761 °F

Explosion Limits

Upper 13.7 vol % 2.2 vol % Lower

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Flammable. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

Carbon monoxide (CO) Carbon dioxide (CO2)

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health	Flammability	Instability	Physical hazards
1	3	0	N/A

Accidental release measures

Personal Precautions

Environmental Precautions

Use personal protective equipment. Remove all sources of ignition. Take precautionary measures against static discharges. Avoid contact with skin, eyes and clothing. Avoid release to the environment. See Section 12 for additional ecological information.

Up

Methods for Containment and Clean Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling

Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Use explosion-proof equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Flammables area.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
n-Propyl alcohol	TWA: 100 ppm	(Vacated) TWA: 200 ppm	IDLH: 800 ppm	TWA: 200 ppm
		(Vacated) TWA: 500 mg/m ³	TWA: 200 ppm	TWA: 500 mg/m ³
		(Vacated) STEL: 250 ppm	TWA: 500 mg/m ³	STEL: 250 ppm
		(Vacated) STEL: 625 mg/m ³	STEL: 250 ppm	STEL: 625 mg/m ³
		TWA: 200 ppm	STEL: 625 mg/m ³	-
		TWA: 500 mg/m ³		

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures Ensure adequate ventilation, especially in confined areas. Use explosion-proof

electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers

are close to the workstation location.

Personal Protective Equipment

Eye/face Protection Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Skin and body protectionWear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene MeasuresHandle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical StateLiquidAppearanceColorlessOdorAlcohol-like

Odor Threshold
pHNo information available720% aq. solutionMelting Point/Range-127 °C / -196.6 °F

Boiling Point/Range 97 °C / 206.6 °F @ 760 mmHg

Flash Point 15 °C / 59 °F

Evaporation RateNo information available

Flammability (solid,gas) Not applicable

Flammability or explosive limits

 Upper
 13.7 vol %

 Lower
 2.2 vol %

 por Pressure
 25 mbar @ 20 °C

Vapor Pressure 25 mbar @ 2 Vapor Density 2.07

Vapor Density 2.07 Specific Gravity 0.800

Solubility
Miscible with water
Partition coefficient; n-octanol/water
Autoignition Temperature
Decomposition Temperature
Miscible with water
No data available
405 °C / 761 °F
No information available

Viscosity 2.2 mPa.s at 20 °C

Molecular FormulaC3 H8 OMolecular Weight60.1

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stability Stable under normal conditions.

Conditions to Avoid Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong acids

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2)

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
n-Propyl alcohol	LD50 = 1870 mg/kg (Rat)	LD50 = 4049 mg/kg (Rabbit)	LC50 > 13548 ppm (Rat) 4 h

Toxicologically Synergistic

No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Severe eye irritant

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
n-Propyl alcohol	71-23-8	Not listed				

Mutagenic Effects No information available

Reproductive Effects

No information available.

Developmental Effects

No information available.

Teratogenicity No information available.

STOT - single exposure Central nervous system (CNS)

STOT - repeated exposure None known

Aspiration hazard No information available

delayed tiredness, nausea and vomiting

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

Ecotoxicity

Do not empty into drains. .

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
n-Propyl alcohol	Not listed	Pimephales promelas:	EC50 = 17700 mg/L 5 min	EC50: 3339 - 3977 mg/L,
		LC50=4480 mg/L 96h	EC50 = 45000 mg/L 5 h EC50 = 8686 mg/L 15 min EC50 = 980 mg/L 12 h	48h Static (Daphnia magna) EC50: = 3642 mg/L, 48h (Daphnia magna)

Persistence and Degradability

Persistence is unlikely

Bioaccumulation/ Accumulation

No information available.

Mobility

. Will likely be mobile in the environment due to its water solubility.

Component	log Pow
n-Propyl alcohol	0.34

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No UN1274

Proper Shipping Name N-PROPANOL

Hazard Class 3 Packing Group II

TDG

UN-No UN1274 Proper Shipping Name UN1274 n-Propanol

Hazard Class 3
Packing Group ||

<u>IATA</u>

UN-No UN1274
Proper Shipping Name n-PROPANOL

Hazard Class 3
Packing Group ||

IMDG/IMO

UN-No UN1274
Proper Shipping Name N-PROPANOL

Hazard Class 3
Packing Group ||

15. Regulatory information

International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
n-Propyl alcohol	Χ	Χ	-	200-746-9	-		Χ	Χ	Х	Х	KE-2936
											2

Legend:

- X Listed
- E Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.
- F Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.
- N Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.
- P Indicates a commenced PMN substance
- R Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.
- S Indicates a substance that is identified in a proposed or final Significant New Use Rule
- T Indicates a substance that is the subject of a Section 4 test rule under TSCA.

Revision Date 20-Mar-2018 1-Propanol

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

Not applicable **TSCA 12(b)**

SARA 313 Not applicable

See section 2 for more information SARA 311/312 Hazard Categories

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

OSHA Occupational Safety and Health Administration

Not applicable

CERCLA Not applicable

California Proposition 65 This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know

Regulations

Component	Massachusetts	New Jersey Pennsylvania		Illinois	Rhode Island	
n-Propyl alcohol	X	Х	Χ	<u>-</u>	Х	

U.S. Department of Transportation

Reportable Quantity (RQ): Ν **DOT Marine Pollutant** Ν **DOT Severe Marine Pollutant** Ν

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade Serious risk, Grade 3

Decreased Dec	Licelith Cefety and Environmental Department	
	16. Other information	

Health, Safety and Environmental Department Prepared By Email: tech@alfa.com

www.alfa.com

Creation Date 03-Jun-2010 **Revision Date** 20-Mar-2018 **Print Date** 20-Mar-2018

Revision Summary SDS authoring systems update, replaces ChemGes SDS No. 71-23-8/2.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS