



Safety Data Sheet

Copyright, 2017, 3M Canada Company

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	24-2334-1	Version number:	7.00
Issue Date:	2017/02/21	Supersedes Date:	2015/05/15

SECTION 1: Identification

1.1. Product identifier

Bondo® Fiberglass Resin Repair Kit, P.N. 420, 420M, 420C, 420E, 420ES, 420K, 420T, 422, 422M, 422C

Product Identification Numbers

60-4550-5647-7	60-4550-5648-5	60-4550-5657-6	60-4550-6593-2	60-4550-6595-7
60-4550-7380-3	60-4550-7388-6	60-4550-7389-4	60-4550-8103-8	60-4550-8104-6
60-4550-8290-3	60-4550-8291-1	60-4550-8300-0	60-4550-8328-1	60-4550-8329-9

1.2. Recommended use and restrictions on use

Recommended use

Automotive, Repairing Auto Body

1.3. Supplier's details

Company: 3M Canada Company
Division: Automotive Aftermarket
Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577
E Mail:

1.4. Emergency telephone number

Medical Emergency Telephone: (519) 451-2500, Ext. 2222; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS) or Article Information Sheet (AIS) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

24-2331-7, 24-2330-9

Transport in accordance with applicable regulations.

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR

PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M Canada SDSs are available at www.3M.ca



Safety Data Sheet

Copyright, 2017, 3M Canada Company

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	24-2331-7	Version number:	3.00
Issue Date:	2017/02/15	Supersedes Date:	2009/07/31

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3M™ Bondo® MEKP Liquid Hardener for Fiberglass Resin Repair Kit P.N. 420, 420C, 420E, 420K, 420T, 422, 422C

Product Identification Numbers

LB-K100-0410-6 LB-K100-0414-7

1.2. Recommended use and restrictions on use

Recommended use

Automotive, Curing Agent

1.3. Supplier's details

Company:	3M Canada Company
Division:	Automotive Aftermarket
Address:	1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
Telephone:	(800) 364-3577
Website:	www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone: (519) 451-2500, Ext. 2222; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Organic Peroxide: Type D.
Acute Toxicity (oral): Category 4.
Acute Toxicity (inhalation): Category 4.
Serious Eye Damage/Irritation: Category 1.
Skin Corrosion/Irritation: Category 1C.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Corrosion | Exclamation mark |

Pictograms



Hazard statements

Heating may cause a fire.

Harmful if swallowed. Causes severe skin burns and eye damage. Harmful if inhaled.

Precautionary statements

General:

Keep out of reach of children. Read label before use. If medical advice is needed, have product container or label at hand.

Prevention:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Keep only in original packaging. Keep cool. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, and eye/face protection. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE or doctor/physician. Wash contaminated clothing before reuse. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a POISON centre or doctor/physician if you feel unwell.

Storage:

Protect from sunlight. Store in a well-ventilated place. Store at temperatures not exceeding 5C/40F. Store locked up. Store separately.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

May cause chemical gastrointestinal burns.

64% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Dimethyl Phthalate	131-11-3	30 - 60
Methyl Ethyl Ketone Peroxide	1338-23-4	15 - 40
Phlegmatizer	Trade Secret	10 - 30
Methyl Ethyl Ketone	78-93-3	< 3
Hydrogen Peroxide	7722-84-1	< 3
Water	7732-18-5	< 3

Phlegmatizer is a non-hazardous Trade Secret material according to WHMIS criteria.

Methyl Ethyl Ketone Peroxide is a hazardous Trade Secret material according to WHMIS criteria. Refer to Section 15 for further information.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Irritant Vapours or Gases	During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Protect from sunlight. Store at temperatures not exceeding 25C/77F. Keep cool. Keep only in original container. Store away from acids. Store away from oxidizing agents. Store away from other materials. Keep/store away from clothing and other combustible materials.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Dimethyl Phthalate	131-11-3	ACGIH	TWA:5 mg/m ³	
Methyl Ethyl Ketone Peroxide	1338-23-4	ACGIH	CEIL:0.2 ppm	
Hydrogen Peroxide	7722-84-1	ACGIH	TWA:1 ppm	
Methyl Ethyl Ketone	78-93-3	ACGIH	TWA:200 ppm;STEL:300 ppm	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

3M™ Bondo® MEKP Liquid Hardener for Fiberglass Resin Repair Kit P.N. 420, 420C, 420E, 420K, 420T, 422, 422C

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield
Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance/Odour	Slight odour. Clear.
Odour threshold	No Data Available
pH	No Data Available
Melting point/Freezing point	No Data Available
Boiling point/Initial boiling point/Boiling range	117.8 °C
Flash Point	> 93.3 °C [Test Method:Closed Cup] [Details:No flash to boiling point.]
Evaporation rate	No Data Available
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Vapour Pressure	No Data Available
Vapour Density	> 1
Density	1.1 g/ml
Relative density	1.1 [Ref Std:WATER=1]
Water solubility	Negligible
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity	No Data Available
Volatile Organic Compounds	39 g/l [Test Method:calculated SCAQMD rule 443.1]
Volatile Organic Compounds	3.5 % weight [Test Method:Tested per ASTM protocol]
Percent volatile	45 % weight
VOC Less H2O & Exempt Solvents	39 g/l [Test Method:calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Light

Sparks and/or flames

Temperatures above the boiling point

10.5. Incompatible materials

Strong oxidizing agents

Alkali and alkaline earth metals

Strong acids

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Harmful if inhaled. Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin Contact:

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

3M™ Bondo® MEKP Liquid Hardener for Fiberglass Resin Repair Kit P.N. 420, 420C, 420E, 420K, 420T, 422, 422C

Ingestion:

Harmful if swallowed. Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

Additional Health Effects:

Single exposure may cause target organ effects:

Dermal Effects: Signs/symptoms may include changes in skin pigmentation and/or colouration.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE10 - 20 mg/l
Overall product	Ingestion		No data available; calculated ATE300 - 2,000 mg/kg
Dimethyl Phthalate	Inhalation-Dust/Mist (4 hours)	Other	LC50 > 15.1 mg/l
Dimethyl Phthalate	Dermal	Rabbit	LD50 > 11,940 mg/kg
Dimethyl Phthalate	Ingestion	Rat	LD50 6,800 mg/kg
Methyl Ethyl Ketone Peroxide	Dermal	Rabbit	LD50 4,000 mg/kg
Methyl Ethyl Ketone Peroxide	Inhalation-Vapor (4 hours)	Rat	LC50 15.4 mg/l
Methyl Ethyl Ketone Peroxide	Ingestion	Rat	LD50 484 mg/kg
Phlegmatizer	Dermal	Guinea pig	LD50 > 18,800 mg/kg
Phlegmatizer	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 8 mg/l
Phlegmatizer	Ingestion	Rat	LD50 > 3,200 mg/kg
Methyl Ethyl Ketone	Dermal	Rabbit	LD50 > 8,050 mg/kg
Methyl Ethyl Ketone	Inhalation-Vapor (4 hours)	Rat	LC50 34.5 mg/l
Methyl Ethyl Ketone	Ingestion	Rat	LD50 2,737 mg/kg
Hydrogen Peroxide	Dermal	Rabbit	LD50 > 2,000 mg/kg
Hydrogen Peroxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 2 mg/l
Hydrogen Peroxide	Ingestion	Rat	LD50 1,193 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Methyl Ethyl Ketone Peroxide	Rabbit	Corrosive
Methyl Ethyl Ketone	Rabbit	Minimal irritation
Hydrogen Peroxide	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Methyl Ethyl Ketone Peroxide	Human	Corrosive
Methyl Ethyl Ketone	Rabbit	Severe irritant
Hydrogen Peroxide	Rabbit	Corrosive

3M™ Bondo® MEKP Liquid Hardener for Fiberglass Resin Repair Kit P.N. 420, 420C, 420E, 420K, 420T, 422, 422C

Skin Sensitization

Name	Species	Value
Methyl Ethyl Ketone Peroxide	Human	Some positive data exist, but the data are not sufficient for classification
Hydrogen Peroxide	Guinea pig	Not sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Methyl Ethyl Ketone Peroxide	In vivo	Not mutagenic
Methyl Ethyl Ketone Peroxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
Methyl Ethyl Ketone	In Vitro	Not mutagenic
Hydrogen Peroxide	In vivo	Not mutagenic
Hydrogen Peroxide	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Methyl Ethyl Ketone Peroxide	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Methyl Ethyl Ketone	Inhalation	Human	Not carcinogenic
Hydrogen Peroxide	Dermal	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Hydrogen Peroxide	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Methyl Ethyl Ketone Peroxide	Dermal	Not toxic to female reproduction	Rat	NOAEL 70 mg/kg/day	13 weeks
Methyl Ethyl Ketone Peroxide	Ingestion	Not toxic to female reproduction	Rat	NOAEL 75 mg/kg/day	prematuring & during gestation
Methyl Ethyl Ketone Peroxide	Ingestion	Not toxic to male reproduction	Rat	NOAEL 75 mg/kg/day	28 days
Methyl Ethyl Ketone Peroxide	Dermal	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 70 mg/kg/day	13 weeks
Methyl Ethyl Ketone Peroxide	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 50 mg/kg/day	prematuring & during gestation
Methyl Ethyl Ketone	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	LOAEL 8.8 mg/l	during gestation
Hydrogen Peroxide	Ingestion	Some positive female reproductive data exist, but the data are not sufficient for classification	Rat	LOAEL 5 mg/kg/day	6 months
Hydrogen Peroxide	Ingestion	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	LOAEL 5 mg/kg/day	6 months
Hydrogen Peroxide	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Rat	LOAEL 5 mg/kg/day	during gestation

3M™ Bondo® MEKP Liquid Hardener for Fiberglass Resin Repair Kit P.N. 420, 420C, 420E, 420K, 420T, 422, 422C

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Methyl Ethyl Ketone Peroxide	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Methyl Ethyl Ketone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	official classification	NOAEL Not available	
Methyl Ethyl Ketone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Methyl Ethyl Ketone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Methyl Ethyl Ketone	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	not applicable
Methyl Ethyl Ketone	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1,080 mg/kg	not applicable
Hydrogen Peroxide	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	
Hydrogen Peroxide	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Human	LOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Methyl Ethyl Ketone Peroxide	Dermal	heart hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 70 mg/kg/day	13 weeks
Methyl Ethyl Ketone Peroxide	Ingestion	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 97 mg/kg/day	7 weeks
Methyl Ethyl Ketone	Dermal	nervous system	All data are negative	Guinea pig	NOAEL Not available	31 weeks
Methyl Ethyl Ketone	Inhalation	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 14.7 mg/l	90 days
Methyl Ethyl Ketone	Inhalation	heart endocrine system bone, teeth, nails, and/or hair hematopoietic system immune system muscles	All data are negative	Rat	NOAEL 14.7 mg/l	90 days
Methyl Ethyl Ketone	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	7 days
Methyl Ethyl Ketone	Ingestion	nervous system	All data are negative	Rat	NOAEL 173 mg/kg/day	90 days
Hydrogen Peroxide	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOEL 0.005 mg/kg/day	6 months
Hydrogen Peroxide	Ingestion	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL Not available	35 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

Trade Secret Information:

HMIRA Registry Number:	Filing date:	Claim status:	Date of decision:
TBD			

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 3 Flammability: 1 Instability: 1 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include

the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 3 Flammability: 1 Physical Hazard: 1 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca



Safety Data Sheet

Copyright, 2016, 3M Canada Company

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	24-2330-9	Version number:	5.00
Issue Date:	2016/07/27	Supersedes Date:	2015/05/15

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3M(TM) Bondo Fiberglass Resin for Fiberglass Resin Kit(s) 420, 420C, 420ES, 420K, 420T, 422, 422C

Product Identification Numbers

LB-K100-1561-6 LB-K100-1561-7 LB-K100-0410-5 LB-K100-0410-8 LB-K100-0543-7
41-0003-6797-3

1.2. Recommended use and restrictions on use

Recommended use

Automotive, Fiberglass Repair Resin

1.3. Supplier's details

Company: 3M Canada Company
Division: Automotive Aftermarket
Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
Telephone: (800) 364-3577
Website: www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone: (519) 451-2500, Ext. 2222; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Flammable Liquid: Category 3.
Serious Eye Damage/Irritation: Category 2B.
Carcinogenicity: Category 2.
Specific Target Organ Toxicity (single exposure): Category 1.
Specific Target Organ Toxicity (single exposure): Category 3.
Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Exclamation mark | Health Hazard |

Pictograms



Hazard statements

Flammable liquid and vapour.

Causes eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer.

Causes damage to organs: liver | sensory organs |

Causes damage to organs through prolonged or repeated exposure: sensory organs |

May cause damage to organs through prolonged or repeated exposure: liver |

Precautionary statements

General:

Keep out of reach of children. Read label before use. If medical advice is needed, have product container or label at hand.

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Use non-sparking tools. Take action to prevent static discharges. Use explosion-proof electrical/ventilating/lighting equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Get medical advice/attention if you feel unwell. In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Polyester Polymer	Trade Secret	40 - 70
Styrene Monomer	100-42-5	15 - 40
Silica	7631-86-9	0.5 - 1.5

3M(TM) Bondo Fiberglass Resin for Fiberglass Resin Kit(s) 420, 420C, 420ES, 420K, 420T, 422, 422C

Polyester Polymer is a non-hazardous Trade Secret material according to WHMIS criteria.
Styrene Monomer is a hazardous Trade Secret material according to WHMIS criteria. Refer to Section 15 for further information.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid eye contact. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Styrene Monomer	100-42-5	ACGIH	TWA:20 ppm;STEL:40 ppm	
Silica	7631-86-9	CMRG	TWA(as respirable dust):3 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face

3M(TM) Bondo Fiberglass Resin for Fiberglass Resin Kit(s) 420, 420C, 420ES, 420K, 420T, 422, 422C

protection(s) are recommended:
Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Polyvinyl Alcohol (PVA)

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Paste
Appearance/Odour	Pungent organic odour. Light straw colour.
Odour threshold	<i>No Data Available</i>
pH	<i>No Data Available</i>
Melting point/Freezing point	<i>No Data Available</i>
Boiling point/Initial boiling point/Boiling range	82.2 °C - 212.8 °C
Flash Point	31.1 °C [<i>Test Method</i> :Closed Cup]
Evaporation rate	[<i>Details</i> :Slower than ether.]
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	1.1 %
Flammable Limits(UEL)	<i>No Data Available</i>
Vapour Pressure	460 Pa
Vapour Density	<i>No Data Available</i>
Density	1.14 g/ml
Relative density	1.14 [<i>Ref Std</i> :WATER=1]
Water solubility	Negligible
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	<i>No Data Available</i>
Volatile Organic Compounds	386 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1]
Volatile Organic Compounds	33.8 % weight [<i>Test Method</i> :calculated per CARB title 2]
Percent volatile	33.8 % weight
VOC Less H ₂ O & Exempt Solvents	386 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

Sparks and/or flames

10.5. Incompatible materials

Strong acids

Strong bases

Strong oxidizing agents

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Hydrocarbons	Not Specified
Carbon monoxide	Not Specified
Carbon dioxide	Not Specified

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled. Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears. Liver

3M(TM) Bondo Fiberglass Resin for Fiberglass Resin Kit(s) 420, 420C, 420ES, 420K, 420T, 422, 422C

Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice. Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause target organ effects:

Ocular Effects: Signs/symptoms may include blurred or significantly impaired vision. Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears. Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Styrene Monomer	100-42-5	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Styrene Monomer	100-42-5	Anticipated human carcinogen	National Toxicology Program Carcinogens

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE20 - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Styrene Monomer	Dermal	Rat	LD50 > 2,000 mg/kg
Styrene Monomer	Inhalation-Vapor (4 hours)	Rat	LC50 8.3 mg/l
Styrene Monomer	Ingestion	Rat	LD50 5,000 mg/kg
Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silica	Ingestion	Rat	LD50 > 5,110 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Styrene Monomer	official classification	Mild irritant
Silica	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Styrene Monomer	official classification	Moderate irritant
Silica	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
Styrene Monomer	Guinea pig	Not sensitizing
Silica	Human and animal	Not sensitizing

3M(TM) Bondo Fiberglass Resin for Fiberglass Resin Kit(s) 420, 420C, 420ES, 420K, 420T, 422, 422C

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Styrene Monomer	In Vitro	Some positive data exist, but the data are not sufficient for classification
Styrene Monomer	In vivo	Some positive data exist, but the data are not sufficient for classification
Silica	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Styrene Monomer	Ingestion	Mouse	Carcinogenic
Styrene Monomer	Inhalation	Human and animal	Carcinogenic
Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Styrene Monomer	Ingestion	Not toxic to female reproduction	Rat	NOAEL 21 mg/kg/day	3 generation
Styrene Monomer	Inhalation	Not toxic to female reproduction	Rat	NOAEL 2.1 mg/l	2 generation
Styrene Monomer	Inhalation	Not toxic to male reproduction	Rat	NOAEL 2.1 mg/l	2 generation
Styrene Monomer	Ingestion	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 400 mg/kg/day	60 days
Styrene Monomer	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 400 mg/kg/day	during gestation
Styrene Monomer	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 2.1 mg/l	during gestation
Silica	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silica	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silica	Ingestion	Not toxic to development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Styrene Monomer	Inhalation	auditory system	Causes damage to organs	Multiple animal species	LOAEL 4.3 mg/l	not available
Styrene Monomer	Inhalation	liver	Causes damage to organs	Mouse	LOAEL 2.1 mg/l	not available
Styrene Monomer	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	occupational exposure
Styrene Monomer	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for	Human and	NOAEL Not available	

3M(TM) Bondo Fiberglass Resin for Fiberglass Resin Kit(s) 420, 420C, 420ES, 420K, 420T, 422, 422C

			classification	animal		
Styrene Monomer	Inhalation	endocrine system	All data are negative	Rat	NOAEL Not available	not available
Styrene Monomer	Inhalation	kidney and/or bladder	All data are negative	Multiple animal species	NOAEL 2.1 mg/l	not available

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Styrene Monomer	Inhalation	eyes	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Styrene Monomer	Inhalation	auditory system	May cause damage to organs though prolonged or repeated exposure	Multiple animal species	NOAEL 1.3 mg/l	not available
Styrene Monomer	Inhalation	liver	May cause damage to organs though prolonged or repeated exposure	Mouse	LOAEL 0.85 mg/l	13 weeks
Styrene Monomer	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	LOAEL 1.1 mg/l	not available
Styrene Monomer	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.85 mg/l	7 days
Styrene Monomer	Inhalation	endocrine system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.6 mg/l	10 days
Styrene Monomer	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	LOAEL 0.09 mg/l	not available
Styrene Monomer	Inhalation	heart bone, teeth, nails, and/or hair muscles kidney and/or bladder	All data are negative	Multiple animal species	NOAEL 4.3 mg/l	2 years
Styrene Monomer	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 500 mg/kg/day	8 weeks
Styrene Monomer	Ingestion	immune system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	not available
Styrene Monomer	Ingestion	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 677 mg/kg/day	6 months
Styrene Monomer	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 600 mg/kg/day	470 days
Styrene Monomer	Ingestion	heart respiratory system	All data are negative	Rat	NOAEL 35 mg/kg/day	105 weeks
Silica	Inhalation	respiratory system silicosis	All data are negative	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

3M(TM) Bondo Fiberglass Resin for Fiberglass Resin Kit(s) 420, 420C, 420ES, 420K, 420T, 422, 422C

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA.

Trade Secret Information:

HMIRA Registry Number: Filing date:
TBD

Claim status:

Date of decision:

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 3 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca