

DURO DYNE CORPORATION
BAY SHORE, N.Y. 11706
EMERGENCY PHONE NO. 800-424-9300 (CHEMTREC)
INFORMATION PHONE NO. 800-899-3876

H.M.I.S.	
HEALTH	1
FLAMMABILITY	3
REACTIVITY	0
PERSONAL PROTECTION	See Below
These ratings should be used only as part of fully implemented H.M.I.S. program.	

MATERIAL SAFETY DATA SHEET

PREPARED BY DURO DYNE 6/2005
REVISED 5/2005

SECTION I

TRADE NAME: DURO DYNE ASA-W - MULTI PURPOSE SPRAY-ON ADHESIVE
MANUFACTURER CODE I.D.: ASA-W

SECTION II - HAZARDOUS INGREDIENTS

CHEMICAL & COMMON NAME(s)	CAS NO.	TLV-TWA	VAPOR PRESSURE @ 25° C	LEL	UEL	FLASH POINT DEGREES	% BY WEIGHT	SARA TITLE III
ACETONE	67-64-1	750 ppm	185 mmHg	2.6	12.8	- 4(TCC)	30 - 50	NO
HEXANE	110-54-3	50 ppm	140 mmHg	1.2	7.5	< 0(TCC)	30 - 50	YES
PROPANE/ ISOBUTANE (Propellant)	68-476-85-7	800 ppm	3691 mmHg	2.0	10.0	- 138(TCC)	30 - 50	NO

SECTION III - PHYSICAL/CHEMICAL DATA

BOILING POINT: (°F): Concentrate: 132-159
Propellant: 21.6

SPECIFIC GRAVITY: (Water=1): Concentrate: 0.70
Propellant: 0.54

VAPOR DENSITY: (Air=1), >1

EVAPORATION RATE: (BA = 1) : >1

APPEARANCE & ODOR: Concentrate: Amber liquid w/
characteristic odor.

(Butyl Acetate =1)

Propellant: Clear odorless gas.

SOLUBILITY IN WATER: Slight

Finished Package: Pressurized containers.

REACTIVITY IN WATER: None

PERCENT VOLATILE BY WEIGHT: Approx. 80

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

EXTINGUISHING MEDIA: Carbon dioxide, Foam, Dry chemical

AUTO-IGNITION TEMPERATURE: Unknown

SPECIAL FIRE FIGHTING PROCEDURES: Water may be used to cool closed containers to prevent pressure build up and possible bursting when exposed to high temperatures. Firemen should wear self-contained respiratory protection.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Extremely flammable. Contents under pressure. Do not store or use near heat or ignition sources. Containers may burst at temperatures above 130°F.

SECTION V - REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: N/A

INCOMPATIBILITY (Materials to avoid): Nitric plus Acetic Acids, Nitric plus Sulfuric Acid, Amines
Strong Oxidizing Agents

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, Carbon dioxide

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION VI - HEALTH HAZARDS DATA

SIGNS & SYMPTOMS OF EXPOSURE:

EYES: May cause moderate corneal injury and eye. Vapors may irritate eyes.

SKIN: Prolonged contact may cause irritation, defatting of skin.

INHALATION: May cause nose & throat irritation. May cause nervous system depression characterized by the following progressive steps: Headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Repeated & prolonged overexposure to solvents may lead to permanent brain and nervous system damage.

INGESTION: If aspirated (liquid enters the lungs), it may be rapidly absorbed through the lungs and result in injury to other body systems. Gastro-intestinal distress.

CARCINOGENICITY: NTP: no IARC: no OSHA: no

SECTION VII- EMERGENCY AND FIRST AID

INHALATION: Remove to fresh air. If not breathing, give mouth-to-mouth. If breathing is difficult, give oxygen. Call a physician.

EYES: Flush with flowing water immediately and continuously for 15 minutes. Consult medical personnel.

SKIN: Wash off in flowing water or shower. Remove contaminated clothing and wash before reuse.

INGESTION: Do not induce vomiting. Call a physician immediately.

IMPORTANT NOTICE : *Repeated and prolonged overexposure to solvents may lead to permanent brain and nervous system damage. Eye watering, headaches, nausea, dizziness, and loss of coordination are signs that solvent levels are too high. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.*

CHRONIC EFFECTS: *This product contains n,Hexane. Overexposure may cause progressive and potentially irreversible damage to the peripheral nervous system, particularly in the arms and legs.*

Simultaneous exposure to the vapors of n,Hexane and Methyl ethyl ketone (MEK) or to n,Hexane and Methyl isobutyl ketone (MIBK) above the recommended workplace limits increases the risk of adverse effects from n,Hexane. Evidence in laboratory animals and humans indicated that in the presence of MEK or MIBK, the neuropathy associated with n,Hexane is produced in a shorter period of time or at lower exposure concentrations. There is no reported human evidence that these neurotoxic effects occur when exposure to these chemicals is maintained below established OSHA and ACGIH limits.

SECTION VIII - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Do not store above 120°F. Avoid breathing vapors. Avoid prolonged or repeated contact with skin.

OTHER PRECAUTIONS: EXTREME FLAMMABLE. Do not use or store near open flames, heat, or any sources of ignition. Contents under pressure. Do not puncture or incinerate. Vapors are heavier than air and will collect in low areas.

SECTION IX - CONTROL MEASURES

VENTILATION LOCAL EXHAUST: To keep below TLV

MECHANICAL:(GENERAL): To keep below TLV

OTHER: NO

SPECIAL: NO

PROTECTIVE GLOVES: Solvent resistant gloves - impervious gloves.

EYE PROTECTION: Wear safety goggles, glasses.

OTHER PROTECTIVE EQUIPMENT: None reasonably foreseeable.

RESPIRATORY: NIOSH or bureau of mines approved organic vapor-type respirator is required in absence of proper environmental control.

SECTION X - SPILL/LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

SMALL SPILLS: Remove ignition sources. Mop up, wipe up, or soak up immediately, use proper protective equipment.

LARGE SPILLS: Evacuate area. Remove ignition sources. Contain liquid, transfer to closed containers, keep out of water supplies.

WASTE DISPOSAL METHODS: Dispose in accordance with Federal, State, and Local regulations. Do not incinerate closed or empty containers.

THE INFORMATION AND RECOMMENDATIONS SET FORTH HEREIN ARE BELIEVED TO BE ACCURATE. BECAUSE SOME OF THE INFORMATION IS DERIVED FROM INFORMATION PROVIDED TO DURO DYNE CORPORATION FROM ITS SUPPLIERS, DURO DYNE CORPORATION MAKES NO WARRANTY, EXPRESSED OR IMPLIED, REGARDING THE ACCURACY OF THE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. SINCE THE USE OF THIS INFORMATION AND THE CONDITIONS AND THE USE OF THIS PRODUCT ARE CONTROLLED BY THE USER, IT IS THE USER'S OBLIGATION TO DETERMINE THE CONDITIONS OF SAFE USE OF THE PRODUCT. THE INFORMATION IS SUPPLIED SOLELY FOR YOUR INFORMATION AND CONSIDERATION AND DURO DYNE CORPORATION ASSUMES NO RESPONSIBILITY FOR USE OR RELIANCE THEREON. IT IS THE RESPONSIBILITY OF THE USER OF DURO DYNE CORPORATION PRODUCTS TO COMPLY WITH ALL APPLICABLE FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS.