

## SAFETY DATA SHEET

Version 6.8  
Revision Date 04/17/2021  
Print Date 10/24/2021**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifiers**

Product name : Ethyl acetate

Product Number : 319902  
Brand : SIGALD  
Index-No. : 607-022-00-5  
CAS-No. : 141-78-6

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Identified uses : Laboratory chemicals, Synthesis of substances

**1.3 Details of the supplier of the safety data sheet**

Company : Sigma-Aldrich Inc.  
3050 SPRUCE ST  
ST. LOUIS MO 63103  
UNITED STATES

Telephone : +1 314 771-5765  
Fax : +1 800 325-5052

**1.4 Emergency telephone**

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-527-3887 CHEMTREC (International) 24 Hours/day; 7 Days/week

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Flammable liquids (Category 2), H225  
Eye irritation (Category 2A), H319  
Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336  
For the full text of the H-Statements mentioned in this Section, see Section 16.

**2.2 GHS Label elements, including precautionary statements**

Pictogram



Signal word

Danger

Hazard statement(s)	
H225	Highly flammable liquid and vapor.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
Precautionary statement(s)	
P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ eye protection/ face protection.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

Repeated exposure may cause skin dryness or cracking.

---

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Formula	: C <sub>4</sub> H <sub>8</sub> O <sub>2</sub>
Molecular weight	: 88.11 g/mol
CAS-No.	: 141-78-6
EC-No.	: 205-500-4
Index-No.	: 607-022-00-5

Component	Classification	Concentration
<b>ethyl acetate</b>	Flam. Liq. 2; Eye Irrit. 2A; STOT SE 3; H225, H319, H336 Concentration limits: 20 %: STOT SE 3, H336;	<= 100 %

---

## SECTION 4: First aid measures

### 4.1 Description of first-aid measures

#### General advice

Show this material safety data sheet to the doctor in attendance.

#### If inhaled

After inhalation: fresh air. Call in physician.

#### In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

#### In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

#### If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>) Foam Dry powder

#### Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

### 5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

### 5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

### 5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

---

## **SECTION 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

### **6.2 Environmental precautions**

Do not let product enter drains. Risk of explosion.

### **6.3 Methods and materials for containment and cleaning up**

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemisorb® ). Dispose of properly. Clean up affected area.

### **6.4 Reference to other sections**

For disposal see section 13.

---

## **SECTION 7: Handling and storage**

### **7.1 Precautions for safe handling**

#### **Advice on safe handling**

Avoid generation of vapours/aerosols.

#### **Advice on protection against fire and explosion**

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

#### **Hygiene measures**

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

For precautions see section 2.2.

### **7.2 Conditions for safe storage, including any incompatibilities**

#### **Storage conditions**

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Storage class (TRGS 510): 3: Flammable liquids

### **7.3 Specific end use(s)**

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

---

## **SECTION 8: Exposure controls/personal protection**

### **8.1 Control parameters**

#### **Ingredients with workplace control parameters**

Component	CAS-No.	Value	Control parameters	Basis
ethyl acetate	141-78-6	TWA	400 ppm	USA. ACGIH Threshold Limit Values (TLV)
		TWA	400 ppm 1,400 mg/m <sup>3</sup>	USA. NIOSH Recommended Exposure Limits
		TWA	400 ppm 1,400 mg/m <sup>3</sup>	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		PEL	400 ppm 1,400 mg/m <sup>3</sup>	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

#### Derived No Effect Level (DNEL)

Application Area	Routes of exposure	Health effect	Value
Workers	Inhalation	Acute systemic effects	1468 mg/m <sup>3</sup>
Workers	Inhalation	Acute local effects	1468 mg/m <sup>3</sup>
Workers	Skin contact	Long-term systemic effects	63mg/kg BW/d
Workers	Inhalation	Long-term systemic effects	734 mg/m <sup>3</sup>
Workers	Inhalation	Long-term local effects	734 mg/m <sup>3</sup>
Consumers	Inhalation	Acute local effects, Acute systemic effects	734 mg/m <sup>3</sup>
Consumers	Skin contact	Long-term systemic effects	37mg/kg BW/d
Consumers	Inhalation	Long-term systemic effects	367 mg/m <sup>3</sup>
Consumers	Ingestion	Long-term systemic effects	4.5mg/kg BW/d
Consumers	Inhalation	Long-term local effects	367 mg/m <sup>3</sup>

#### Predicted No Effect Concentration (PNEC)

Compartment	Value
Soil	0.24 mg/kg
Sea water	0.026 mg/l
Fresh water	0.26 mg/l
Sea sediment	0.125 mg/kg
Fresh water sediment	1.25 mg/kg

## 8.2 Exposure controls

### Appropriate engineering controls

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

### Personal protective equipment

#### Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

#### Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).  
Splash contact

Material: butyl-rubber  
Minimum layer thickness: 0.7 mm  
Break through time: 120 min  
Material tested: Butoject® (KCL 898)

### **Body Protection**

Flame retardant antistatic protective clothing.

### **Respiratory protection**

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

### **Control of environmental exposure**

Do not let product enter drains. Risk of explosion.

---

## **SECTION 9: Physical and chemical properties**

### **9.1 Information on basic physical and chemical properties**

a) Appearance	Form: clear, liquid Color: colorless
b) Odor	No data available
c) Odor Threshold	No data available
d) pH	No data available
e) Melting point/freezing point	Melting point/range: 84 °C (183 °F) - lit.
f) Initial boiling point and boiling range	76.5 - 77.5 °C 169.7 - 171.5 °F - lit.
g) Flash point	-4 °C (25 °F) - closed cup
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	Lower explosion limit: 2.2 %(V)
k) Vapor pressure	No data available
l) Vapor density	No data available
m) Relative density	No data available
n) Water solubility	No data available
o) Partition coefficient: n-octanol/water	No data available
p) Autoignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	No data available

s) Explosive properties No data available

t) Oxidizing properties No data available

## 9.2 Other safety information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Vapors may form explosive mixture with air.

### 10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

### 10.3 Possibility of hazardous reactions

Risk of ignition or formation of inflammable gases or vapours with:

Exothermic reaction with:

Fluorine

chlorosulfonic acid

Strong oxidizing agents

fuming sulfuric acid

Risk of explosion with:

lithium aluminium hydride

Alkali metals

hydrides

Alkaline earth metals

Violent reactions possible with:

Strong acids and strong bases

### 10.4 Conditions to avoid

Warming.

### 10.5 Incompatible materials

various plastics

### 10.6 Hazardous decomposition products

In the event of fire: see section 5

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

LD50 Oral - Rat - 5,620 mg/kg

Remarks: (RTECS)

Inhalation: No data available

LD50 Dermal - Rabbit - male - > 20,000 mg/kg

Remarks: (ECHA)

No data available

#### Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation

SIGALD - 319902

Page 7 of 11

Remarks: (IUCLID)

### **Serious eye damage/eye irritation**

Eyes - Rabbit

Result: slight irritation

(OECD Test Guideline 405)

Remarks: (Regulation (EC) No 1272/2008, Annex VI)

### **Respiratory or skin sensitization**

Maximization Test - Guinea pig

Result: negative

(OECD Test Guideline 406)

### **Germ cell mutagenicity**

Test Type: UDS (Unscheduled DNA synthesis assay)

Test system: Escherichia coli

Metabolic activation: with and without metabolic activation

Method: US-EPA

Result: negative

Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

Test Type: Micronucleus test

Species: Chinese hamster

Cell type: Red blood cells (erythrocytes)

Application Route: Oral

Method: OECD Test Guideline 474

Result: negative

### **Carcinogenicity**

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

### **Reproductive toxicity**

No data available



**Specific target organ toxicity - single exposure**

May cause drowsiness or dizziness. - Central nervous system

**Specific target organ toxicity - repeated exposure**

No data available

**Aspiration hazard**

No data available

**11.2 Additional Information**

Repeated dose toxicity - Rat - male and female - Oral - 92 Days - NOAEL (No observed adverse effect level) - 900 mg/kg - LOAEL (Lowest observed adverse effect level) - 3,600 mg/kg

RTECS: AH5425000

Inhalation of high concentrations may cause:, Headache, Drowsiness, Dizziness, Vomiting, narcosis, anemia, Central nervous system depression  
To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Kidney - Irregularities - Based on Human Evidence

Kidney - Irregularities - Based on Human Evidence

---

**SECTION 12: Ecological information****12.1 Toxicity**

Toxicity to fish                      flow-through test LC50 - Pimephales promelas (fathead minnow) - 230 mg/l - 96 h (US-EPA)

Toxicity to algae                      static test NOEC - Desmodesmus subspicatus (green algae) - > 100 mg/l - 72 h (OECD Test Guideline 201)

**12.2 Persistence and degradability**

Biodegradability                      aerobic - Exposure time 20 d  
Result: ca.69 % - Readily biodegradable.  
Remarks: (ECHA)

Theoretical oxygen demand                      1,820 mg/g  
Remarks: (Lit.)

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

## 12.6 Other adverse effects

No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See [www.retrologistik.com](http://www.retrologistik.com) for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

---

## SECTION 14: Transport information

#### DOT (US)

UN number: 1173 Class: 3 Packing group: II  
Proper shipping name: Ethyl acetate  
Reportable Quantity (RQ): 5000 lbs  
Poison Inhalation Hazard: No

#### IMDG

UN number: 1173 Class: 3 Packing group: II EMS-No: F-E, S-D  
Proper shipping name: ETHYL ACETATE

#### IATA

UN number: 1173 Class: 3 Packing group: II  
Proper shipping name: Ethyl acetate

---

## SECTION 15: Regulatory information

#### SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

#### SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

#### Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

---

## SECTION 16: Other information

#### Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the

present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See [www.sigma-aldrich.com](http://www.sigma-aldrich.com) and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact [mlsbranding@sial.com](mailto:mlsbranding@sial.com).

Version: 6.8

Revision Date: 04/17/2021

Print Date: 10/24/2021