

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910 1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY

Dura Stripe White and Colors
(Aerosol Marking Paint)

Note: Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's name US Specialty Coatings	Emergency Telephone Number 404-408-0401
Address (Number, Street, City, State and ZIP Code) 1000 McFarland 400 Blvd Alpharetta, GA 30004	Telephone Number for Information 770-740-8549
	Date Prepared 01/27/11
	Signature of Preparer (optional)

Section II—Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Aliphatic &	100	50 (Skin)		15 – 20
Aromatic hydrocarbons	300			15 – 20
Isobutane / Propane blend	600 – 1000 (estimate)			20 – 30

This product may contain one or more materials subject to the reporting requirements of Section 313 of the emergency planning and community Right-To-Know Acts of 1986 and of 40 CFR 372, see Section X for specific materials.

Section III—Physical/Chemical Characteristics

Boiling Point	315 Deg F	Specific Gravity (H ₂ O = 1)	1.1
Vapor Pressure (mm Hg)	Not established	Melting Point	N/A
Vapor Density (AIR = 1)	Not established	Evaporation Rate (Butyl Acetate = 1)	Butyl Acetate=1) 1
Solubility in Water	Slight		
Appearance and Odor	White and various colors, Paint smell		

Section IV—Fire and Explosion Hazard Data

Flash Point (Method Used) TCC/PM deg F: 110 Extremely Flammable	Flammable Limits	LEL 1.0	UEL 6.0
---	------------------	---------	---------

Extinguishing Media Carbon monoxide, Dry foam, Chemical or and/or water fog.

Special Fire Fighting Procedures Fire Fighters must wear self-contained breathing apparatus or air masks.

Containers exposed to fire should be kept cool with water spray

Unusual Fire and Explosion Hazards Contains oxidizing materials. Contaminated rags, wipes, sawdust, etc. may catch fire spontaneously

Store waste in closed metal containers until disposed of in compliance with all applicable regulations.

(Reproduce locally)

OSHA 174 Sept. 1985

Section V—Reactivity Data			
Stability	This product is stable	Unstable	Conditions to Avoid Heat and flame
		Stable	
Incompatibility (Materials to Avoid) None			
Hazardous Decomposition or Byproducts Carbon monoxide, Carbon Dioxide			
Hazardous Polymerization	None	May Occur	Conditions to Avoid None
		Will Not Occur	
Section VI—Health Hazard Data			
Route(s) of Entry	Inhalation Yes	Skin Yes	Ingestion Yes
Health Hazards (Acute and Chronic) Eye irritation. Harmful if inhaled. May affect brain, nervous system or respiratory system, causing dizziness, headache, nausea or respiratory irritation. Overexposure to ingredients in this product may cause nose and throat irritation eye irritation, and skin irritation			
Carcinogenicity	NTP?	IARC Monographs?	OSHA Regulated?
Signs and Symptoms of Exposure Reports have associated repeated and long term and prolonged overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and Inhaling the contents may be harmful or fatal.			
Medical Conditions Generally Aggravated by Exposure Medical conditions generally aggravated by exposure: Any respiratory condition			
Emergency and First Aid Procedures Emergency procedures and first aid: Eye contact: Flush immediately with plenty of water for at least 15 minutes and get medical attention. Skin contact Wash thoroughly with soap and water Inhalation: If affected by inhalation of vapor or spray mist, remove to fresh air. Swallowing: If swallowed, get medical attention immediately			
Section VII—Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material Is Released or Spilled Ventilate area. Avoid breathing of vapors. Use self-contained breathing apparatus or air mask for large spill in confined area Avoid contacts with eyes			
Waste Disposal Method Waste disposal method: Dispose in chemical disposal area or in a manner that complies with local, state and federal regulations. Do not incinerate closed containers.			
Precautions to Be Taken in Handling and Storing Keep away from heat, sparks and open flames. Keep containers closed when not in use. Do not store above 120 deg. F, based on OSHA 1910.106.			
Other Precautions Empty containers may contain product residue, including flammable and explosive vapors. Do not cut puncture or weld on or near container. All label warnings must be observed until the container has been properly disposed.			
Section VII—Control Measures			
Respiratory Protection Wear appropriate, properly fitted respirator (NIOSH / MSHA approved) during and after application, unless air monitoring vapor / mist level are below applicable limits.			
Ventilation	Local Exhaust	Required for handling in confined areas.	Special Ventilation equipment must be explosion proof.
	Mechanical (General)		Other
Protective Gloves	Gloves impervious to solvents.		Eye Protection Chemical safety goggles.
Other Protective Clothing or Equipment Usual clothing and protective gear used for handling solvent based flammable products.			
Work/Hygienic Practices			

DISCLAIMER

The information contained herein is based on data and information considered and believed to be accurate.

US SPECIALTY COATINGS INC. makes no warranties expressed or implied and assume no responsibility for the accuracy or completeness of the data. US SPECIALTY COATINGS INC. further assumes no responsibility for personal injury or property damage to vendors, users or third parties caused by this material. Such vendors or users assume all risks associated with the use of this material.