

## SAFETY DATA SHEET

Version 6.2  
Revision Date 04/27/2021  
Print Date 06/04/2022**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifiers**

Product name : Acrylic acid

Product Number : 147230

Brand : Aldrich

Index-No. : 607-061-00-8

CAS-No. : 79-10-7

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Identified uses : Laboratory chemicals, Synthesis of substances

**1.3 Details of the supplier of the safety data sheet**

Company : Sigma-Aldrich Inc.  
3050 SPRUCE ST  
ST. LOUIS MO 63103  
UNITED STATES

Telephone : +1 314 771-5765

Fax : +1 800 325-5052

**1.4 Emergency telephone**

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-527-3887 CHEMTREC (International) 24 Hours/day; 7 Days/week

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Flammable liquids (Category 3), H226

Acute toxicity, Oral (Category 4), H302

Acute toxicity, Inhalation (Category 4), H332

Acute toxicity, Dermal (Category 4), H312

Skin corrosion (Category 1A), H314

Serious eye damage (Category 1), H318

Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335

Short-term (acute) aquatic hazard (Category 1), H400

Long-term (chronic) aquatic hazard (Category 2), H411

For the full text of the H-Statements mentioned in this Section, see Section 16.

**2.2 GHS Label elements, including precautionary statements**

Aldrich - 147230

Page 1 of 11

Pictogram



Signal word

Danger

Hazard statement(s)

H226 Flammable liquid and vapor.  
H302 + H312 + H332 Harmful if swallowed, in contact with skin or if inhaled.  
H314 Causes severe skin burns and eye damage.  
H335 May cause respiratory irritation.  
H400 Very toxic to aquatic life.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary statement(s)

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.  
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.  
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.  
P363 Wash contaminated clothing before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.  
P391 Collect spillage.  
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.  
P501 Dispose of contents/ container to an approved waste disposal plant.

### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

---

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Formula : C<sub>3</sub>H<sub>4</sub>O<sub>2</sub>

Aldrich - 147230

Page 2 of 11

Molecular weight : 72.06 g/mol  
 CAS-No. : 79-10-7  
 EC-No. : 201-177-9  
 Index-No. : 607-061-00-8

Component	Classification	Concentration
<b>acrylic acid</b>		
	Flam. Liq. 3; Acute Tox. 4; Skin Corr. 1A; Eye Dam. 1; Aquatic Acute 3; Aquatic Chronic 2; H226, H302, H332, H312, H314, H318, H402, H411 Concentration limits: >= 1 %: STOT SE 3, H335;	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

---

## SECTION 4: First aid measures

### 4.1 Description of first-aid measures

#### General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

#### If inhaled

After inhalation: fresh air. Call in physician.

#### In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

#### In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

#### If swallowed

After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Call a physician immediately. Do not attempt to neutralise.

### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Water Foam Carbon dioxide (CO<sub>2</sub>) Dry powder

### **Unsuitable extinguishing media**

For this substance/mixture no limitations of extinguishing agents are given.

### **5.2 Special hazards arising from the substance or mixture**

Carbon oxides

Flash back possible over considerable distance.

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air at elevated temperatures.

Development of hazardous combustion gases or vapours possible in the event of fire.

### **5.3 Advice for firefighters**

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

### **5.4 Further information**

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

---

## **SECTION 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

### **6.2 Environmental precautions**

Do not let product enter drains. Risk of explosion.

### **6.3 Methods and materials for containment and cleaning up**

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemizorb® ).

Dispose of properly. Clean up affected area.

### **6.4 Reference to other sections**

For disposal see section 13.

---

## **SECTION 7: Handling and storage**

### **7.1 Precautions for safe handling**

#### **Advice on safe handling**

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

#### **Advice on protection against fire and explosion**

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

#### **Hygiene measures**

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

### **7.2 Conditions for safe storage, including any incompatibilities**

#### **Storage conditions**

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Hygroscopic.

Storage class (TRGS 510): 3: Flammable liquids

### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
acrylic acid	79-10-7	TWA	2 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Not classifiable as a human carcinogen Danger of cutaneous absorption		
		TWA	2 ppm 6 mg/m <sup>3</sup>	USA. NIOSH Recommended Exposure Limits
		Potential for dermal absorption		
		TWA	10 ppm 30 mg/m <sup>3</sup>	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		Skin notation		
		PEL	2 ppm 5.9 mg/m <sup>3</sup>	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		Skin		

### 8.2 Exposure controls

#### Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

#### Personal protective equipment

##### Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles

##### Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Butoject® (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm

Break through time: 120 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

### **Body Protection**

Flame retardant antistatic protective clothing.

### **Respiratory protection**

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

### **Control of environmental exposure**

Do not let product enter drains. Risk of explosion.

---

## **SECTION 9: Physical and chemical properties**

### **9.1 Information on basic physical and chemical properties**

- |   |   |
|---|---|
| a) Appearance                                   | Form: liquid<br>Color: colorless                                  |
| b) Odor   | No data available   |
| c) Odor Threshold                               | No data available   |
| d) pH   | No data available   |
| e) Melting point/freezing point                 | Melting point/range: 13 °C (55 °F) - lit.                         |
| f) Initial boiling point and boiling range      | 139 °C 282 °F - lit.  |
| g) Flash point                                  | 48.5 °C (119.3 °F) - closed cup - DIN 51755 Part 1                |
| h) Evaporation rate                             | No data available   |
| i) Flammability (solid, gas)                    | No data available   |
| j) Upper/lower flammability or explosive limits | No data available   |
| k) Vapor pressure                               | 5.29 hPa at 25 °C (77 °F)   |
| l) Vapor density                                | No data available   |
| m) Relative density                             | 1.05 at 20 °C (68 °F)   |
| n) Water solubility                             | 1,000 g/l at 25 °C (77 °F)  |
| o) Partition coefficient: n-octanol/water       | log Pow: 0.46 at 25 °C (77 °F) - Bioaccumulation is not expected. |

- p) Autoignition temperature 438 °C (820 °F) at 1,013 hPa
- q) Decomposition temperature No data available
- r) Viscosity No data available
- s) Explosive properties No data available
- t) Oxidizing properties No data available

## 9.2 Other safety information

- Surface tension 69.6 mN/m at 1g/l at 20 °C (68 °F) - Surface tension
- Dissociation constant 4.26 at 25 °C (77 °F)

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Vapor/air-mixtures are explosive at intense warming.

### 10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

### 10.3 Possibility of hazardous reactions

Reacts violently in contact with acids, amines, driers, polymerization accelerators and easily oxidized materials.  
Polymerization can occur.

### 10.4 Conditions to avoid

Heating.

### 10.5 Incompatible materials

Copper, Nickel, Mild steel, Zinc

### 10.6 Hazardous decomposition products

In the event of fire: see section 5

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Acute toxicity estimate Oral - 500 mg/kg  
(Calculation method)

LD50 Oral - Rat - male - 1,000 - < 2,000 mg/kg  
(OECD Test Guideline 423)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the esophagus and the stomach.

Acute toxicity estimate Inhalation - 4 h - 11 mg/l  
(Calculation method)

LC50 Inhalation - Rat - 4 h - 3.6 mg/l

Remarks: (Lit.)(Regulation (EC) No 1272/2008, Annex VI)Symptoms: mucosal irritations,  
Cough, Shortness of breath, Possible damages:, damage of respiratory tractInhalation:  
Corrosive to respiratory system.

Acute toxicity estimate Dermal - 1,100 mg/kg  
(Calculation method)

LD50 Dermal - Rabbit - male - 1,000 mg/kg

Remarks: (Regulation (EC) No 1272/2008, Annex VI)  
No data available

#### **Skin corrosion/irritation**

Skin - Rabbit

Result: Causes severe burns.

(OECD Test Guideline 404)

Remarks: (Regulation (EC) No 1272/2008, Annex VI)

#### **Serious eye damage/eye irritation**

Eyes - Rabbit

Result: Causes burns.

Remarks: (IUCLID)

Causes serious eye damage.

#### **Respiratory or skin sensitization**

Sensitisation test: - Guinea pig

Result: negative

Remarks:

(Lit.)

#### **Germ cell mutagenicity**

Test Type: Ames test

Test system: Salmonella typhimurium

Result: negative

Remarks: (National Toxicology Program)

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Test Type: unscheduled DNA synthesis assay

Test system: rat hepatocytes

Metabolic activation: without metabolic activation

Method: OECD Test Guideline 482

Result: negative

Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Species: Rat

Cell type: Bone marrow

Application Route: Oral

Method: OECD Test Guideline 475

Result: negative



Test Type: dominant lethal test  
Species: Mouse  
Cell type: Intrauterine  
Application Route: Oral

Result: negative  
Remarks: (ECHA)

### **Carcinogenicity**

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

### **Reproductive toxicity**

No data available

### **Specific target organ toxicity - single exposure**

No data available

### **Specific target organ toxicity - repeated exposure**

No data available

### **Aspiration hazard**

No data available

## **11.2 Additional Information**

Repeated dose toxicity - Rat - male - Oral - NOAEL (No observed adverse effect level) - 40 mg/kg - LOAEL (Lowest observed adverse effect level) - 100 mg/kg  
RTECS: AS4375000

burning sensation, Cough, wheezing, laryngitis, Shortness of breath, spasm, inflammation and edema of the larynx, spasm, inflammation and edema of the bronchi, pneumonitis, pulmonary edema, Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

Liver - Irregularities - Based on Human Evidence

Liver - Irregularities - Based on Human Evidence

---

## SECTION 12: Ecological information

### 12.1 Toxicity

Toxicity to fish	flow-through test LC50 - Oncorhynchus mykiss (rainbow trout) - 27 mg/l - 96 h (US-EPA)
Toxicity to daphnia and other aquatic invertebrates	flow-through test EC50 - Daphnia magna (Water flea) - 95 mg/l - 48 h (US-EPA)
Toxicity to algae	NOEC - Chlorella vulgaris (Fresh water algae) - 0.2 mg/l - 72 h (OECD Test Guideline 201)

### 12.2 Persistence and degradability

Biodegradability	Result: 100 % - Readily eliminated from water (OECD Test Guideline 302B) Result: 81 % - Readily biodegradable. (OECD Test Guideline 301D)
------------------	--

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

### 12.6 Other adverse effects

Biological effects:  
Neutralise before sewage disposal.  
Discharge into the environment must be avoided.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See [www.retrologistik.com](http://www.retrologistik.com) for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

---

## SECTION 14: Transport information

### DOT (US)

UN number: 2218 Class: 8 (3) Packing group: II  
Proper shipping name: Acrylic acid, stabilized  
Reportable Quantity (RQ): 5000 lbs  
1) Marine pollutant: yes Poison Inhalation Hazard: No

### IMDG

UN number: 2218 Class: 8 (3) Packing group: II EMS-No: F-E, S-C

Aldrich - 147230

Page 10 of 11

Proper shipping name: ACRYLIC ACID, STABILIZED  
Marine pollutant : yes  
Marine pollutant : yes

**IATA**

UN number: 2218 Class: 8 (3) Packing group: II  
Proper shipping name: Acrylic acid, stabilized

---

**SECTION 15: Regulatory information**

**SARA 302 Components**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 313 Components**

The following components are subject to reporting levels established by SARA Title III, Section 313:

	CAS-No.	Revision Date
acrylic acid	79-10-7	2007-07-01

**SARA 311/312 Hazards**

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

**Massachusetts Right To Know Components**

No components are subject to the Massachusetts Right to Know Act.

---

**SECTION 16: Other information**

**Further information**

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See [www.sigma-aldrich.com](http://www.sigma-aldrich.com) and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact [mlsbranding@sial.com](mailto:mlsbranding@sial.com).

Version: 6.2

Revision Date: 04/27/2021

Print Date: 06/04/2022