

PRODUCT TRADE NAME:

HOMAX PRODUCTS, INC. TILE GUARD SILICONE GROUT SEALER ITEM #9320,9320-26,9321,9322,9323,9324,9326

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: HOMAX PRODUCTS, INC. 468 WEST HORTON ROAD BELLINGHAM, WA 98226 24 HOUR EMERGENCY PHONE NUMBER:CHEMTREC1-800-424-9300INFORMATION PHONE NUMBER:1-800-729-9029

DATE OF PREPARATION:

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

CAS NUMBER DESCRIPTION

016589438 SODIUM SILICONATE

EXPOSURE LIMITS

SAME LIMITS AS FOR SODIUM HYDROXIDE OSHA PEL AND ACGIH TLV 2 MG/M3 CEILING

03/27/03

NOTE: ALL OTHER INGREDIENTS HAVE BEEN DEFINED AS NON-HAZARDOUS BY OSHA STANDARDS 29CFR1910.1200

%

3

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

| APPEARANCE AND ODOR: | SEMI CLEAR LIQUID, NO ODOR |
|-----------------------|----------------------------|
| BOILING POINT: | 212F |
| PH: | 11.85 |
| VAPOR PRESSURE (MMHG) | APPROX. 24@77 |
| WATER SOLUBILITY (%): | 100% |
| VAPOR DENSITY: | SAME AS MOIST AIR |
| SPECIFIC GRAVITY: | APPROX. 1 |
| MELTING POINT: | 32F |
| VOC CONTENT: | <0.1% |
| | |

SECTION IV - FIRE AND EXPLOSION DATA

FLASH POINT (METHOD USED): NONE FLAMMABLE LIMITS IN AIR % N/A BY VOL: PRODUCT DOES NOT BURN

SECTION V – REACTIVITY DATA

STABILITY:

STABLE.

INCOMPATIBILITY (MATERIALS TO AVOID): STRONG OXIDIZERS

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE

HAZARDOUS POLYMERIZATION: SHOULD NOT OCCUR

SECTION VI – HEALTH HAZARD DATA

PRIMARY ROUTE OF ENTRY: SKIN,INHALATION

EFFECTS OF OVEREXPOSURE:

INHALATION: MIST MAY IRRITATE NOSE AND THROAT EYES: DIRECT CONTACT BURNS EYES WITH POSSIBLE INJURY. SKIN: BURNS SKIN UPON LONG PERIODS OF CONTACT. INGESTION: SMALL AMOUNTS SHOULD NOT INJURE. SWALLOWING LARGE AMOUNTS MAY BE HARMFUL.

EMERGENCY AND FIRST AID PROCEDURES:

INGESTION: DO NOT INDUCE VOMITING. TREAT SAME AS FOR SODIUM HYDROXIDE, 3% SOLUTION.

GET

IMMEDIATE MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR. GET IMMEDIATE MEDICAL ATTENTION. EYES: FLUSH IMMEDIATELY WITH WATER FOR 15 MINUTES. GET IMMEDIATE MEDICAL ATTENTION. SKIN: FLUSH IMMEDIATELY WITH WATER FOR 15 MINUTES. GET IMMEDIATE MEDICAL ATTENTION.

SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN INCASE MATERIAL IS RELEASED OR SPILLED: USE ABSORBENT MATERIAL TO COLLECT, CONTAIN FOR DISPOSAL.

WASTE DISPOSAL METHOD:

DISPOSE ACCORDING TO APPLICABLE REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE IN COOL, DRY PLACE.

SHIPPING INFORMATION:

THIS PRODUCT IS NOT HAZARDOUS MATERIAL OR HAZARDOUS SUBSTANCE DEFINED BY THE DEPARTMENT OF TRANSPORTATION, NOR IS IT A DANGEROUS GOOD AS DEFINED BY IATA FOR AIR

SECTION VIII – CONTROL MEASURES

RESPIRATORY PROTECTION:

USE A NIOSH APPROVED MIST FILTER IF MISTING IS LIKELY.

VENTILATION RECOMMENDATIONS:

AS NECESSARY TO KEEP EXPOSURE WITHIN TLV AND PEL GUIDELINES.

SKIN:

AVOID CONTACT BY WEARING IMPERVIOUS CLOTHING. RUBBER GLOVES, APRON, BOOTS ARE REQUIRED.

EYE PROTECTION:

USE CHEMICAL WORKER GOGGLES.

SECTION XI - DISCLAIMER

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HERE IN IS ACCURATE, OBTAINED FROM SOURCES BELIEVED BY HOMAX CORPORATION TO BE ACCURATE. SINCE THE CONDITIONS AND METHODS OF USE OF OUR PRODUCTS ARE BEYOND OUR CONTROL, WE DISCLAIM ANY AND ALL LIABILITY ARISING OUT OF THE IMPROPER USE OF THESE PRODUCTS OR THE INFORMATION PROVIDED HEREWITH.

SHIPPING INFORMATION: THIS PRODUCT IS NOT A HAZARDOUS MATERIAL OR HAZARDOUS