

Safety Data Sheet

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Revision date: 31.07.2020

Version: 6.1

Print date: 31.07.2020

SECTION 1: Identification

Product identifier

Trade name/designation:	Reagent Grade Alcohol, 95%
Product No.:	89370-082
Synonymes:	none/none
CAS No.:	not applicable
Other means of identification:	

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use:	For Further Manufacturing Use Only
Uses advised against:	Not for Human or Animal Drug Use

Details of the supplier of the safety data sheet

Supplier

VWR International LLC

Street	100 Matsonford Road Radnor Corporate Center, Building One, Suite 200 P. O. Box 6660
Postal code/City	Radnor, PA 19087
Telephone	+1-800-932-5000 toll-free within US/Canada +1-610-386-1700
Telefax:	+1-610-728-2103

Emergency phone number

Telephone +1-800-424-9300 (Chemtrec, 24 hrs/day, 7 days/week, USA)

Preparation Information

VWR International - Product Information Compliance

E-mail sds@vwr.com

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910.1200 (OSHA HCS)

Hazard classes and hazard categories	Hazard statements
Flammable liquid, category 2	H225
Acute toxicity, category 4, oral	H302
Skin irritation, category 2	H315
Eye irritation, category 2	H319
Specific target organ toxicity (single exposure), category 1	H370
Specific target organ toxicity (single exposure), category 3, vascular	H335

2.2 Label elements

Labelling in accordance with 29 CFR 1910.1200 (OSHA HCS)

Hazard pictograms



Signal word: Danger

Hazard statements	
H225	Highly flammable liquid and vapor.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H370	Causes damage to organs.
H335	May cause respiratory irritation.

Precautionary statements	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P311	IF exposed or concerned: Call a POISON CENTER/doctor/...

Hazards not otherwise classified (HNOC)

none/none

SECTION 3: Composition / information on ingredients

3.1 Substances

not applicable

3.2 Mixtures

Hazardous ingredients Classification according to the OSHA Hazard Communication Standard 29 CFR 1910.1200

Substance name	Concentration	Identifier	Hazard classes and hazard categories
Methanol	3 - 5%	CAS No.: 67-56-1	Flam. Liq. 2 - H225 Acute Tox. 3 - H301+H311+H331 STOT SE 1 - H370
Ethanol absolute	80 - 90%	CAS No.: 64-17-5	Flam. Liq. 2 - H225 Eye Irrit. 2 - H319
2-Propanol	3 - 8%	CAS No.: 67-63-0	Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336

SECTION 4: First aid measures

4.1 General information

IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician. If unconscious but breathing normally, place in recovery position and seek medical advice. Never give anything by mouth to an unconscious person or a person with cramps. Change contaminated, saturated clothing. Do not leave affected person unattended.

In case of inhalation

Call a POISON CENTER/doctor. Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Remove contaminated, saturated clothing immediately. In case of skin reactions, consult a physician.

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye. Remove contact lenses, if present and easy to do. Continue rinsing.

In case of ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do NOT induce vomiting. Give nothing to eat or drink.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms/effects, acute and delayed

no data available

4.3 Indication of any immediate medical attention and special treatment needed

no data available

SECTION 5: Fire fighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Water spray
ABC-powder
Carbon dioxide (CO₂)
Nitrogen

Extinguishing media which must not be used for safety reasons

no restriction

5.2 Specific hazards arising from the chemical

In case of fire may be liberated:
Pyrolysis products, toxic

5.3 Advice for firefighters

DO NOT fight fire when fire reaches explosives.
Protective equipment and precautions for firefighters
Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Do not allow run-off from fire-fighting to enter drains or water courses.
Do not inhale explosion and combustion gases.
Use caution when applying carbon dioxide in confined spaces. Carbon dioxide can displace oxygen.
Use water spray/stream to protect personnel and to cool endangered containers.
In case of fire: Evacuate area.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Use personal protection equipment. Special danger of slipping by leaking/spilling product. In case of major fire and large quantities: Remove persons to safety. Wear a self-contained breathing apparatus and chemical protective clothing.

6.2 Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up

Spilled product must never be returned to the original container for recycling. Clean contaminated articles and floor according to the environmental legislation. Collect in closed and suitable containers for disposal.

6.4 Additional information

Clear spills immediately.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

All work processes must always be designed so that the following is as low as possible:

Inhalation

skin contact

Eye contact

Use extractor hood (laboratory).

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

7.2 Conditions for safe storage, including any incompatibilities

Recommended storage temperature: no data available

Keep container tightly closed and in a well-ventilated place. Keep/Store only in original container.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredient (Designation)	Regulatory information	Country	Limit value type (country of origin)	Limit value
Methanol	NIOSH	US	LTV	260 mg/m ³ - 200 ppm
Methanol	NIOSH	US	STV	325 mg/m ³ (1) - 250 ppm (1)
Methanol	OSHA	US	LTV	260 mg/m ³ - 200 ppm
Ethanol absolute	NIOSH	US	LTV	1900 mg/m ³ - 1000 ppm
Ethanol absolute	OSHA	US	LTV	1900 mg/m ³ - 1000 ppm
2-Propanol	NIOSH	US	LTV	980 mg/m ³ - 400 ppm
2-Propanol	NIOSH	US	STV	1225 mg/m ³ - 500 ppm
2-Propanol	OSHA	US	LTV	980 mg/m ³ - 400 ppm

8.2 Engineering controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment. If handled uncovered, arrangements with local exhaust ventilation have to be used.

Personal protection equipment (PPE)

Wear suitable protective clothing. When handling with chemical substances, protective clothing must be worn.

Eye/face protection

Eye glasses with side protection

Skin protection

Wear suitable gloves. When handling with chemical substances, protective gloves must be worn. In the case of wanting to use the gloves again, clean them before taking off and air them well. Check leak tightness/impermeability prior to use.

By short-term hand contact

Suitable material:	NBR (Nitrile rubber)
Thickness of the glove material:	0,38 mm
Breakthrough time::	38 min

By long-term hand contact

Suitable material:	Butyl caoutchouc (butyl rubber)
Thickness of the glove material:	0,30 mm
Breakthrough time::	480 min

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation If exposure limits are exceeded or irritation is experienced, NIOSH approved respiratory protection should be worn.

Additional information

Wash hands before breaks and after work. Avoid contact with eyes and skin. When using do not eat, drink or smoke. Provide eye shower and label its location conspicuously.

Environmental exposure controls

no data available

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

(a) Appearance	
Physical state:	liquid
Color:	colorless
(b) Odour:	no data available
(c) Odour threshold:	no data available

Safety relevant basic data

(d) pH:	no data available
(e) Melting point/freezing point:	no data available
(f) Initial boiling point and boiling range:	no data available
(g) Flash point:	no data available
(h) Evaporation rate:	no data available
(i) Flammability (solid, gas):	Highly flammable liquid and vapor.
(j) Flammability or explosive limits	
Lower explosion limit:	no data available
Upper explosion limit:	no data available
(k) Vapour pressure:	no data available
(l) Vapour density:	no data available
(m) Relative density:	no data available
(n) Solubility(ies)	
Water solubility (g/L):	no data available
Soluble (g/L) in Ethanol:	no data available
(o) Partition coefficient: n-octanol/water:	no data available
(p) Auto-ignition temperature:	no data available
(q) Decomposition temperature:	no data available
(r) Viscosity	
Kinematic viscosity:	no data available
Dynamic viscosity:	no data available
(s) Explosive properties:	not applicable
(t) Oxidising properties:	not applicable

9.2 Other information

Bulk density:	no data available
Refraction index:	no data available
Dissociation constant:	no data available
Surface tension:	no data available
Henry's Law Constant:	no data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixtures with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Formation of explosive mixtures with:

Oxidising agent

Nitrogen oxides (NO_x)

Material, oxygen-rich, oxidizing

Nitric acid

Chlorine

Bromine

Exothermic reaction with:

Reducing agent

Acid

Acid halides

Alkali (lye), concentrated

Violent reaction with:

Alkali metals

Alkaline earth metal

Formation of:

Hydrogen

10.4 Conditions to avoid

UV-radiation/sunlight

Heat

This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment).

10.5 Incompatible materials

light metals

Plastic articles

10.6 Hazardous decomposition products

no data available

10.7 Additional information

Slowly corrodes aluminium and zinc under hydrogen evolution.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute effects

Acute oral toxicity:

Methanol - LD50: > 5628 mg/kg - Rat - (IUCLID)

Methanol - LDLo: > 143 mg/kg - Human - (RTECS)

Ethanol absolute - LD50: > 6200 mg/kg - Rat - (Merck KGaA)

2-Propanol - LD50: > 5045 mg/kg - Rat - (RTECS)

2-Propanol - LDLo: > 3570 mg/kg - Human - (RTECS)

Acute dermal toxicity:

Methanol - LD50: > 15800 mg/kg - Rabbit

Ethanol absolute - LD50: < 20000 mg/kg - Rabbit - (CHP)

2-Propanol - LD50: > 12800 mg/kg - Rabbit - (RTECS)

Acute inhalation toxicity:

Methanol - TCLo: > 160 ppm (4h) - Human

Ethanol absolute - LC50: < 8000 mg/l (4h) - Rat - (CHP)

2-Propanol - LC50: 72600 mg/m³ - Rat - (Japan GHS Basis for Classification Data)

Irritant and corrosive effects

Primary irritation to the skin:

Causes skin irritation.

Irritation to eyes:

Causes serious eye irritation.

Irritation to respiratory tract:

May cause respiratory irritation.

Respiratory or skin sensitization

In case of skin contact: not sensitising

In case of inhalation: not sensitising

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

not applicable

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

no data available	ACGIH	IARC	NTP	OSHA

Germ cell mutagenicity

No indications of human germ cell mutagenicity exist.

Reproductive toxicity

No indications of human reproductive toxicity exist.

Aspiration hazard

not applicable

Other adverse effects

no data available

Additional information

no data available

SECTION 12: Ecological information

12.1 Ecotoxicity

Fish toxicity:

Methanol - LC50: 24000 mg/l (96 h) - Poirier, S.H., M.L. Knuth, C.D. Anderson-Buchou, L.T. Brooke, A.R. Lima, and P.J. Shubat 1986. Comparative Toxicity of Methanol and N,N-Dimethylformamide to Freshwater Fish and Invertebrates. Bull.Environ.Contam.Toxicol. 37(4):615-621

Ethanol absolute - LC50: 11000 mg/l (96 h) - Bengtsson, B.E., L. Renberg, and M. Tarkpea 1984. Molecular Structure and Aquatic Toxicity - an Example with C1-C13 Aliphatic Alcohols. Chemosphere 13(5/6):613-622

2-Propanol - LC50: 9640 mg/l (96 h) - Brooke, L.T., D.J. Call, D.L. Geiger, and C.E. Northcott 1984. Acute Toxicities of Organic Chemicals to Fathead Minnows (Pimephales promelas), Vol. 1. Center for Lake Superior Environmental Stud., Univ.of Wisconsin-Superior, Superior, WI :414

Daphnia toxicity:

Methanol - LC50: 3290 mg/l (48 h) - Guilhermino, L., T. Diamantino, M.C. Silva, and A.M.V.M. Soares 2000. Acute Toxicity Test with Daphnia magna: An Alternative to Mammals in the Prescreening of Chemical Toxicity?. Ecotoxicol.Environ.Saf. 46(3):357-362

Methanol - EC50: 24500 mg/l (48 h) - Randall, T.L., and P.V. Knopp 1980. Detoxification of Specific Organic Substances by Wet Oxidation. J.Water Pollut.Control Fed. 52(8):2117-2130

Ethanol absolute - LC50: 9280 mg/l (48 h) - Takahashi, I.T., U.M. Cowgill, and P.G. Murphy 1987. Comparison of Ethanol Toxicity to Daphnia magna and Ceriodaphnia dubia Tested at Two Different Temperatures: Static Acute Toxicity Test Results. Bull.Environ.Contam.Toxicol. 39(2):229-236

Ethanol absolute - EC50: 9950 mg/l (48 h) - Barera, Y., and W.J. Adams 1983. Resolving Some Practical Questions About Daphnia Acute Toxicity Tests. In: W.E.Bishop (Ed.), Aquatic Toxicology and Hazard Assessment, 6th Symposium, ASTM STP 802, Philadelphia, PA :509-518

2-Propanol - LC50: 1400 mg/l (48 h) - Blackman, R.A.A. 1974. Toxicity of Oil-Sinking Agents. Mar.Pollut.Bull. 5:116-118

Algae toxicity:

no data available

Bacteria toxicity:

no data available

12.2 Persistence and degradability

no data available

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water: no data available

12.4 Mobility in soil:

no data available

12.5 Results of PBT/vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Other adverse effects

no data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Appropriate disposal / Product

Dispose according to legislation. Consult the appropriate local waste disposal expert about waste disposal.

Waste code product: no data available

Appropriate disposal / Package

Dispose according to legislation. Handle contaminated packages in the same way as the substance itself.

Additional information

no data available

SECTION 14: Transport information

Land transport (DOT)

UN-No.:	UN1987
Proper Shipping Name:	ALCOHOLS, N.O.S. (ETHANOL / 2-PROPANOL / METHANOL)
Class(es):	3
Hazard label(s):	3
Packing group:	II
Environmental hazards:	No
Marine pollutant:	No
Special precautions for user:	

Sea transport (IMDG)

UN-No.:	1987
Proper Shipping Name:	ALCOHOLS, N.O.S. (ETHANOL / 2-PROPANOL / METHANOL)
Class(es):	3
Classification code:	

Hazard label(s):	3
Packing group:	II
Environmental hazards:	No
Marine pollutant:	No
Special precautions for user:	
Segregation group:	-
EmS-No.	F-E S-D
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	
not relevant	

Air transport (ICAO-TI / IATA-DGR)

UN-No.:	1987
Proper Shipping Name:	ALCOHOLS, N.O.S. (ETHANOL / 2-PROPANOL / METHANOL)
Class(es):	3
Classification code:	
Hazard label(s):	3
Packing group:	II
Special precautions for user:	

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA 313 Components

- Methanol - CAS No.: 67-56-1
- 2-Propanol - CAS No.: 67-63-0

Massachusetts Right To Know Components

- Methanol - CAS No.: 67-56-1
- Ethanol absolute - CAS No.: 64-17-5
- 2-Propanol - CAS No.: 67-63-0

Pennsylvania Right To Know Components

- Methanol - CAS No.: 67-56-1
- Ethanol absolute - CAS No.: 64-17-5
- 2-Propanol - CAS No.: 67-63-0

New Jersey Right To Know Components

- Methanol - CAS No.: 67-56-1
- Ethanol absolute - CAS No.: 64-17-5
- 2-Propanol - CAS No.: 67-63-0

California Prop. 65 Components



WARNING:

This product can expose you to chemicals including Methanol which is known to the State of California to cause birth defects or other reproductive harm.

For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

Abbreviations and acronyms

H225 - Highly flammable liquid and vapor.

H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

H370 - Causes damage to organs.

ACGIH - American Conference of Governmental Industrial Hygienists

DOT - Department of Transportation

IARC - International Agency for Research on Cancer

IATA-DGR - International Air Transport Association-Dangerous Goods Regulations

ICAO-TI - International Civil Aviation Organization-Technical Instructions

IMDG - International Maritime Code for Dangerous Goods

LTV - Long Term Value

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety & Health Administration

PBT - Persistent, Bioaccumulative and Toxic

PEL - Permissible Exposure Limit

STV - Short Term Value

SVHC - Substances of Very High Concern

TDG - Transport of Dangerous Goods

TLV - Threshold Limit Value

vPvB - very Persistent, very Bioaccumulative

Training advice: Provide adequate information, instruction and training for operators.

Classification according to Regulation (EC) No 1272/2008 [CLP] - Classification procedure

Hazard statements	Hazard classes and hazard categories	Classification procedure
H225	Flam. Liq. 2	Data obtained by expert judgement.
H302	Acute Tox. 4	Calculation method.
H315	Skin Irrit. 2	Calculation method.
H319	Eye Irrit. 2	Calculation method.
H370	STOT SE 1	Calculation method.
H335	STOT SE 3	Calculation method.

Additional information

Indication of changes general update

If you need an explanation of the change, contact the supplier. (SDS@avantorsciences.com)

The above information is believed to be correct but does not purport to be all-inclusive and shall be used only as a guidance. The information in this document is based on the present state knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. VWR International and his Affiliates shall not be held liable for any damage resulting from handling.