

Revision Date: August 17, 2011 Supersedes: March 21, 2011

Section 1 • Product and Company Identification

Product Name: LPS® ThermaPlex® Multi-Purpose Bearing Grease

Part Number(s): 70614, 70606, 70635, 70655, C70614, C70606, C70635, C70655

Chemical Name: Petroleum Hydrocarbon

Product Use: A lubricating grease intended for all types of industrial bearing applications.

Manufacturer Information: LPS Laboratories, 4647 Hugh Howell Road, Tucker, GA, USA 30084

TEL: USA & Canada: 1 800 241-8334

Outside USA and Canada: +1 770 243-8800

FAX: USA & Canada: 1 800 543-1563

Outside USA and Canada: +1 770 243-8899

Emergency Telephone Number: Chemtrec: USA & Canada: 1 800 424-9300

Outside USA and Canada: +1 703 527-3887

Website: http://www.lpslabs.com

Section 2 • Hazards Identification

This material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Emergency Overview:

Aerosol: Not applicable

Bulk: WARNING: Prolonged or repeated skin contact may cause irritation.

Primary route(s) of entry: Skin and eye contact.

Potential Acute Health Effects:

Eyes: Irritating to eyes.

Skin: Repeated exposure may cause skin dryness or defatting of the skin.

Inhalation: Oil mist may cause irritation of the respiratory tract.

Ingestion: Product has a low order of acute oral toxicity, but ingestion of large quantities may cause nausea, vomiting, and gastrointestinal

irritation.

Potential Chronic Health Effects:

Carcinogenic Effects: NTP: No IARC: No OSHA: No ACGIH: No

Mutagenic Effects: None

Teratogenic Effects: None

Target Organs: None

Medical conditions aggravated by exposure:

None known from normal exposure.

Signs and Symptoms

Stinging in eyes. Repeated or prolonged skin contact can cause redness, irritation, and scaling of the skin (dermatitis).



Revision Date: August 17, 2011 Supersedes: March 21, 2011

Section 3 • Composition / Information on Ingredients

Component CASRN Weight Percent

Distillates (Petroleum), Hydrotreated Heavy Naphthenic 64742-52-5 60 - 100%

Section 4 • First Aid Measures

Eyes: Check for and remove contact lenses. Immediately, flush eyes with cool, clean, low-pressure water for at least 15 minutes. Hold eyelids

apart to ensure complete irrigation of the eye and eyelid tissue. DO NOT use eye ointment. Seek medical attention if irritation persists.

Skin: Remove contaminated shoes and clothing. Clean affected area thoroughly with mild soap and water. DO NOT use ointments. Seek medical

attention if irritation persists.

Inhalation: Immediately move victim to fresh air. If victim is not breathing, immediately begin rescue breathing. If heart has stopped, immediately begin

cardiopulmonary resuscitation (CPR). If breathing is difficult, seek medical attention immediately.

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If

spontaneous vomiting is about to occur, place victim's head below knees. If victim is drowsy or unconscious, place on the left side with head

down. DO NOT leave victim unattended. Seek medical attention immediately.

Section 5 • Fire Fighting Measures

Products of Combustion: Carbon monoxide and carbon dioxide.

General Fire Hazards: High heat will cause product to boil, evolving vapor that could cause explosive rupture of closed containers.

Firefighting media: SMALL FIRE: Use DRY chemical powder.

LARGE FIRE: Use CO2, water spray, fog or foam.

Sensitivity to Impact: None Sensitivity to Static Discharge: None

Protection Clothing (Fire): Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing

apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.

Special Remarks on Explosion Hazards:

None

Section 6 • Accidental Release Measures

Containment Procedures: Small Spill and Leak: Absorb with an inert material and dispose of properly.

Large Spill and Leak: Prevent material from entering sewers and drains. Pick up for disposal using absorbant pads,

sand or other inert non-combustible materials. Place into appropriate waste containers for later

disposal.

Clean-Up Procedures: Recover free product and place in a suitable container for disposal.

Evacuation Procedures: Ventilate area of leak or spill. Keep unnecessary and unprotected people away.

Special Procedures: Remove all sources of ignition. Ventilate area. Wear personal protective equipment during cleanup. Be aware of spilled material

on walking surfaces - this product is slippery.



Revision Date: August 17, 2011 Supersedes: March 21, 2011

Section 7 • Handling and Storage

Handling: Avoid contact with skin and eyes. Wash thoroughly after handling.

Storage: Keep container sealed until ready for use. Keep container in a cool, well-ventilated area. Store between 40°F and 120°F (4.4°C and 49°C).

Precautions to be taken in handling and storage:

Keep container in a cool, well-ventilated area. Avoid breathing vapors.

Section 8 • Exposure Controls / Personal Protection

Engineering Controls: Provide general and/or local exhaust ventilation to keep exposures below 5 mg/m3 oil mist in air.

Personal protective equipment

Eye protection: Safety glasses with side shields conforming to appropriate regulations. Eye wash fountain and emergency shower facilities are

recommended.

Hand protection: Normally no hand protection is required; however, using chemical resistant gloves is recommended.

Respiratory protection: Typical use of this product under normal conditions does not require the use of respiratory protection. If airborne concentrations

are above the applicable exposure limits (listed above), use NIOSH approved respiratory protection (i.e. organic vapor cartridge).

General Hygiene Wash thoroughly after handling. Have eye-wash facilities immediately available.

Section 9 • Physical and Chemical Properties

Appearance: Paste Color: Blue / Black

Odor: Petroleum Evaporation Rate: <1 (BuAc = 1)

Solubility Description: Not soluble in water Flash Point: > 230°C (446°F)

Boiling Point: Not established Flash Point Method: Tag-Closed Cup

Specific Gravity (H2O=1): 0.89 - 0.94 @ 20°C Decomposition Temperature: Not established

Vapor Density (air = 1): > 1 Auto ignition temperature: Not established

 Vapor Pressure:
 Not established
 Flammable limits (estimated):
 LOWER:
 N.E.

UPPER: N.E.

Not established

Rule 1171 PPc: Not applicable Partition Coefficient (octanol/water): Not established

V.O.C. Content: Aerosol: Not applicable Odor Threshold:

Bulk: 0% per State & Federal

Consumer Product Regulations

Melting Point: Not established Viscosity: Not established

pH: Not applicable Volatiles: 0%

Heat of combustion: Aerosol: Not applicable

Bulk: Not established



Revision Date: August 17, 2011 Supersedes: March 21, 2011

Section 10 • Stability and Reactivity

Chemical Stability: Product is stable under recommended storage conditions.

Conditions to Avoid: No specific measures to avoid.

Incompatibility: Reactive or incompatible with oxidizing agents.

Hazardous Decomposition: These products are carbon oxides (CO, CO2).

Hazardous Polymerization: Will not occur.

Section 11 • Toxicological Information

Acute and Chronic Toxicity

A: General Product Information

An acute toxicity study of this product has not been conducted. Information given in this section relates only to individual constituents contained in this preparation.

B: Component Analysis

Component	CASRN	LC-50	LD-50		
Distillates (Petroleum), Hydrotreated Heavy	64742-52-5	2.18 mg/L / rat / 4 hr	> 5000 mg/kg / oral / rat		
Naphthenic	04742-32-3	2.10 Hig/L / Tat / 4 Hi	> 2000 mg/kg / dermal / rabbit		

^{*} Supplier Data

Section 12 • Ecological Information

Mobility: Non-volatile. Absorbed only slowly into soil. **Persistence / Degradability:** Only slightly biodegradable

Bioaccumulative potential: No bioaccumulation potential Other adverse effects: None known

Section 13 • Disposal Considerations

Waste Status: In its purchased form, this material does not meet the definition of a RCRA hazardous waste (40 CFR 261).

Disposal: Waste must be disposed of in accordance with any and all applicable environmental control rules and/or regulations.

Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information inaccurate,

incomplete, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive than federal laws

and regulations.

Section 14 • Transport Information

This product is not regulated by any mode of transportation.

The preceding information is subject to change and must be verified prior to shipment. It is the responsibility of anyone offering hazardous materials for shipment to ensure compliance with all applicable regulations.



MATERIAL SAFETY DATA SHEET

LPS® ThermaPlex® Multi-Purpose Bearing Grease

Revision Date: August 17, 2011 Supersedes: March 21, 2011

Section 15 • Regulatory Information

U.S. Federal Regulations

RCRA Hazardous Waste No.: None

Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA):

None

Toxic Substances Control Act (TSCA):

All components of this product are TSCA inventory listed and/or are exempt.

Superfund Amendments and Reauthorization Act (SARA) Title III SARA Section 311/312 (40 CFR 370) Hazard Categories:

None

This product contains the following toxic chemical(s) subject to reporting requirements of SARA Section 313 (40 CFR 372):

No individual section 313 component is present at or above 1%.

Section 112 Hazardous Air Pollutants (HAPs): None

State Regulations

California: This product does not contain chemical(s) known to the State of California to cause cancer, birth defects or other

reproductive harm.

California and OTC States: This product is not regulated by consumer product regulations.

New Jersey Right to Know:

Aerosol: Not applicable

Bulk: Petroleum Oil 64742-52-5 ● Calcium Carbonate 471-34-1 ● Lithium 12-Hydroxystearate 7620-77-1 ● Olefin Sulfide NJ TS RN 800969-5422P

International Regulations

Canadian Environmental Protection Act (CEPA):

All of the components of this product are included on the Canadian Domestic Substances list (DSL).

Canadian Workplace Hazardous Materials Information System WHMIS:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Classification:	
NOT WHMIS controlled	

Other Regulations:

Montreal Protocol listed ingredients:

None
Stockholm Convention listed ingredients:

None
Rotterdam Convention listed engredients:

None
RoHS Compliant:

Yes



Revision Date: August 17, 2011 Supersedes: March 21, 2011

Section 16 • Other Information

MSDS#:	70614	HMIS 1996		HMIS III		NFPA Flammability		
MSDS Preparation Responsible Name:		Health:	1	Health:	[/] 1			
Elena Badiuzzi Compliance Manager		Flammability:	1	Flammability Aerosol: Flammability Bulk:	NA 1	Health	***	Reactivity
Telephone: +1 770 243-8800		Reactivity:	0	Physical Hazard Aerosol: Physical Hazard Bulk:	NA 0		Special	

Notice to Reader:

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Elena Badiuzzi, Compliance Manager LPS Laboratories, a division of Illinois Tool Works