

## SAFETY DATA SHEET

Creation Date 17-Jun-2014

Revision Date 17-Jun-2014

Revision Number 1

### 1. Identification

**Product Name** Shandon Xylene Substitute Mountant

**Cat No. :** 1900231, 1900233, 9999122

**Synonyms** No information available

**Recommended Use** Laboratory chemicals.

**Uses advised against** No Information available

**Details of the supplier of the safety data sheet**

**Company**

Richard Allan Scientific  
A Subsidiary of Thermo Fisher Scientific  
4481 Campus Drive  
Kalamazoo, MI 49008  
Tel: (800) 522-7270

**Emergency Telephone Number**

Chemtrec US: (800) 424-9300  
Chemtrec EU: 001 (202) 483-7616

### 2. Hazard(s) identification

**Classification**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

|   |            |
|---|------------|
| Flammable liquids   | Category 1 |
| Skin Corrosion/irritation   | Category 2 |
| Serious Eye Damage/Eye Irritation                                 | Category 2 |
| Skin Sensitization  | Category 1 |
| Reproductive Toxicity   | Category 2 |
| Specific target organ toxicity (single exposure)                  | Category 3 |
| Target Organs - Respiratory system, Central nervous system (CNS). |            |
| Specific target organ toxicity - (repeated exposure)              | Category 1 |
| Target Organs - Kidney, Liver, Heart, Blood.                      |            |
| Aspiration Toxicity   | Category 1 |

**Label Elements**

**Signal Word**

Danger

**Hazard Statements**

Extremely flammable liquid and vapor  
May be fatal if swallowed and enters airways  
Causes skin irritation  
Causes serious eye irritation  
May cause an allergic skin reaction  
May cause respiratory irritation  
May cause drowsiness or dizziness  
Suspected of damaging the unborn child  
Causes damage to organs through prolonged or repeated exposure



### Precautionary Statements

#### Prevention

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Contaminated work clothing should not be allowed out of the workplace  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Do not eat, drink or smoke when using this product  
 Use only outdoors or in a well-ventilated area  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Keep cool  
 Wear protective gloves/protective clothing/eye protection/face protection

#### Response

IF exposed or concerned: Get medical attention/advice

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

#### Skin

If skin irritation or rash occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

#### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

#### Fire

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

#### Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

#### Disposal

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Very toxic to aquatic life

#### Unknown Acute Toxicity

.? % of the mixture consists of ingredients of unknown toxicity.

### 3. Composition / information on ingredients

| Component             | CAS-No   | Weight % |
|-----------------------|----------|----------|
| Toluene               | 108-88-3 | 62-64    |
| Isobutyl methacrylate | 97-86-9  | 36-38    |

## 4. First-aid measures

|  |   |
|--|---|
| <b>General Advice</b>                  | If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.   |
| <b>Eye Contact</b>                     | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.   |
| <b>Skin Contact</b>                    | Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required. Call a physician immediately. <b>SPEEDY ACTION IS CRITICAL, GET MEDICAL AID IMMEDIATELY.</b> If symptoms persist, call a physician. If skin irritation persists, call a physician. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.  |
| <b>Inhalation</b>                      | Move to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth resuscitation if victim ingested or inhaled the substance; induce artificial respiration with a respiratory medical device. Immediate medical attention is required. Artificial respiration and/or oxygen may be necessary. Consult a physician. Immediate medical attention is not required. Move to fresh air in case of accidental inhalation of vapors. If symptoms persist, call a physician. |
| <b>Ingestion</b>                       | Do not induce vomiting. Call a physician or Poison Control Center immediately. Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Consult a physician.  |
| <b>Most important symptoms/effects</b> | Breathing difficulties. May cause allergic skin reaction. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing  |
| <b>Notes to Physician</b>              | Treat symptomatically   |

## 5. Fire-fighting measures

|   |  |
|---|--|
| <b>Suitable Extinguishing Media</b>     | CO <sub>2</sub> , dry chemical, dry sand, alcohol-resistant foam. Cool closed containers exposed to fire with water spray. |
| <b>Unsuitable Extinguishing Media</b>   | Water may be ineffective   |
| <b>Flash Point</b>                      | 4.4 °C / 39.9 °F   |
| <b>Method -</b>                         | No information available   |
| <b>Autoignition Temperature</b>         | No information available   |
| <b>Explosion Limits</b>                 |  |
| <b>Upper</b>                            | No data available  |
| <b>Lower</b>                            | No data available  |
| <b>Sensitivity to Mechanical Impact</b> | No information available   |
| <b>Sensitivity to Static Discharge</b>  | No information available   |

### Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

### Hazardous Combustion Products

Carbon monoxide (CO) Carbon dioxide (CO<sub>2</sub>)

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

**NFPA**

**Health**  
3

**Flammability**  
4

**Instability**  
0

**Physical hazards**  
N/A

**6. Accidental release measures****Personal Precautions**

Use personal protective equipment. Remove all sources of ignition. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

**Environmental Precautions**

Should not be released into the environment. Do not flush into surface water or sanitary sewer system. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. See Section 12 for additional ecological information. Avoid release to the environment. Collect spillage.

**Methods for Containment and Clean Up**

Remove all sources of ignition. Soak up with inert absorbent material. Take precautionary measures against static discharges. Keep in suitable, closed containers for disposal.

**7. Handling and storage****Handling**

Use only under a chemical fume hood. Use explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing. Do not breathe vapors or spray mist. Pay attention to flashback. No information available. Do not take internally.

**Storage**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Flammables area. Keep containers tightly closed in a cool, well-ventilated place. Keep in properly labeled containers.

**8. Exposure controls / personal protection****Exposure Guidelines**

| Component | ACGIH TLV   | OSHA PEL   | NIOSH IDLH  |
|-----------|-------------|--|---|
| Toluene   | TWA: 20 ppm | (Vacated) TWA: 100 ppm<br>(Vacated) TWA: 375 mg/m <sup>3</sup><br>Ceiling: 300 ppm<br>(Vacated) STEL: 150 ppm<br>(Vacated) STEL: 560 mg/m <sup>3</sup><br>TWA: 200 ppm | IDLH: 500 ppm<br>TWA: 100 ppm<br>TWA: 375 mg/m <sup>3</sup><br>STEL: 150 ppm<br>STEL: 560 mg/m <sup>3</sup> |

| Component | Quebec  | Mexico OEL (TWA)                          | Ontario TWAEV |
|-----------|---|---|---------------|
| Toluene   | TWA: 50 ppm<br>TWA: 188 mg/m <sup>3</sup><br>Skin | TWA: 50 ppm<br>TWA: 188 mg/m <sup>3</sup> | TWA: 20 ppm   |

**Legend**

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

**Engineering Measures**

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

**Personal Protective Equipment****Eye/face Protection**

Tightly fitting safety goggles. Face-shield.

**Skin and body protection**

Long sleeved clothing. Apron. Impervious gloves.

|                               |   |
|-------------------------------|---|
| <b>Respiratory Protection</b> | Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. |
| <b>Hygiene Measures</b>       | When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.  |

## 9. Physical and chemical properties

|   |                          |
|---|--------------------------|
| <b>Physical State</b>                         | Liquid                   |
| <b>Appearance</b>                             | Clear Colorless          |
| <b>Odor</b>                                   | hydrocarbon-like         |
| <b>Odor Threshold</b>                         | No information available |
| <b>pH</b>                                     | No information available |
| <b>Melting Point/Range</b>                    | No data available        |
| <b>Boiling Point/Range</b>                    | Not applicable           |
| <b>Flash Point</b>                            | 4.4 °C / 39.9 °F         |
| <b>Evaporation Rate</b>                       | No information available |
| <b>Flammability (solid,gas)</b>               | No information available |
| <b>Flammability or explosive limits</b>       |                          |
| <b>Upper</b>                                  | No data available        |
| <b>Lower</b>                                  | No data available        |
| <b>Vapor Pressure</b>                         | No information available |
| <b>Vapor Density</b>                          | No information available |
| <b>Relative Density</b>                       | No information available |
| <b>Solubility</b>                             | No information available |
| <b>Partition coefficient; n-octanol/water</b> | No data available        |
| <b>Autoignition Temperature</b>               | No information available |
| <b>Decomposition temperature</b>              | No information available |
| <b>Viscosity</b>                              | No information available |

## 10. Stability and reactivity

|   |   |
|---|---|
| <b>Reactive Hazard</b>                  | None known, based on information available              |
| <b>Stability</b>                        | Stable under normal conditions.                         |
| <b>Conditions to Avoid</b>              | Incompatible products. Heat, flames and sparks.         |
| <b>Incompatible Materials</b>           | Strong oxidizing agents, Strong acids                   |
| <b>Hazardous Decomposition Products</b> | Carbon monoxide (CO), Carbon dioxide (CO <sub>2</sub> ) |
| <b>Hazardous Polymerization</b>         | Hazardous polymerization does not occur.                |
| <b>Hazardous Reactions</b>              | None under normal processing.                           |

## 11. Toxicological information

### Acute Toxicity

|                            |   |
|----------------------------|---|
| <b>Product Information</b> | No acute toxicity information is available for this product                   |
| <b>Oral LD50</b>           | Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. |
| <b>Dermal LD50</b>         | Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. |
| <b>Vapor LC50</b>          | Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.    |

### **Component Information**

| Component             | LD50 Oral            | LD50 Dermal           | LC50 Inhalation       |
|-----------------------|----------------------|-----------------------|-----------------------|
| Toluene               | > 5000 mg/kg ( Rat ) | 8390 mg/kg ( Rabbit ) | 26700 ppm ( Rat ) 1 h |
| Isobutyl methacrylate | 6400 mg/kg ( Rat )   | Not listed            | Not listed            |

|   |                          |
|---|--------------------------|
| <b>Toxicologically Synergistic Products</b> | No information available |
|---|--------------------------|

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

|                        |  |
|------------------------|--|
| <b>Irritation</b>      | Irritating to eyes, respiratory system and skin  |
| <b>Sensitization</b>   | No information available   |
| <b>Carcinogenicity</b> | The table below indicates whether each agency has listed any ingredient as a carcinogen. |

| Component             | CAS-No   | IARC       | NTP        | ACGIH      | OSHA       | Mexico     |
|-----------------------|----------|------------|------------|------------|------------|------------|
| Toluene               | 108-88-3 | Not listed | Not listed | Not listed | Not listed | Not listed |
| Isobutyl methacrylate | 97-86-9  | Not listed | Not listed | Not listed | Not listed | Not listed |

|   |  |
|---|--|
| <b>Mutagenic Effects</b>                          | Mutagenic effects have occurred in humans.   |
| <b>Reproductive Effects</b>                       | Experiments have shown reproductive toxicity effects on laboratory animals.  |
| <b>Developmental Effects</b>                      | Developmental effects have occurred in experimental animals.   |
| <b>Teratogenicity</b>                             | Teratogenic effects have occurred in experimental animals.   |
| <b>STOT - single exposure</b>                     | Respiratory system Central nervous system (CNS)  |
| <b>STOT - repeated exposure</b>                   | Kidney Liver Heart Blood   |
| <b>Aspiration hazard</b>                          | No information available   |
| <b>Symptoms / effects, both acute and delayed</b> | Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing |
| <b>Endocrine Disruptor Information</b>            | No information available   |
| <b>Other Adverse Effects</b>                      | See actual entry in RTECS for complete information.  |

## 12. Ecological information

### Ecotoxicity

. Very toxic to aquatic organisms.

| Component             | Freshwater Algae                              | Freshwater Fish  | Microtox                | Water Flea  |
|-----------------------|---|--|-------------------------|---|
| Toluene               | 433 mg/L EC50 > 96 h<br>12.5 mg/L EC50 = 72 h | 50-70 mg/L LC50 96 h<br>5-7 mg/L LC50 96 h<br>15-19 mg/L LC50 96 h<br>28 mg/L LC50 96 h<br>12 mg/L LC50 96 h | EC50 = 19.7 mg/L 30 min | 11.5 mg/L EC50 = 48 h<br>5.46 - 9.83 mg/L EC50 48 h |
| Isobutyl methacrylate | 0.29 mg/L EC50 = 96 h                         | 20 mg/L LC50 96 h  | Not listed              | 23 mg/L EC50 = 48 h                                 |

**Persistence and Degradability** No information available

**Bioaccumulation/ Accumulation** No information available.

**Mobility** .

| Component             | log Pow |
|-----------------------|---------|
| Toluene               | 2.65    |
| Isobutyl methacrylate | 2.01    |

## 13. Disposal considerations

**Waste Disposal Methods** Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

| Component          | RCRA - U Series Wastes | RCRA - P Series Wastes |
|--------------------|------------------------|------------------------|
| Toluene - 108-88-3 | U220                   | -                      |

## 14. Transport information

**DOT**

UN-No UN1866  
 Proper Shipping Name RESIN SOLUTION  
 Hazard Class 3  
 Packing Group II

**TDG**

UN-No UN1866  
 Proper Shipping Name RESIN SOLUTION  
 Hazard Class 3  
 Packing Group II

**IATA**

UN-No UN1866  
 Proper Shipping Name RESIN SOLUTION  
 Hazard Class 3  
 Packing Group II

**IMDG/IMO**

UN-No UN1866  
 Proper Shipping Name RESIN SOLUTION  
 Hazard Class 3  
 Packing Group II

## 15. Regulatory information

All of the components in the product are on the following Inventory lists: Australia X = listed China Canada Europe TSCA Korea Philippines Japan

**International Inventories**

| Component             | TSCA | DSL | NDSL | EINECS    | ELINCS | NLP | PICCS | ENCS | AICS | IECSC | KECL |
|-----------------------|------|-----|------|-----------|--------|-----|-------|------|------|-------|------|
| Toluene               | X    | X   | -    | 203-625-9 | -      |     | X     | X    | X    | X     | X    |
| Isobutyl methacrylate | X    | X   | -    | 202-613-0 | -      |     | X     | X    | X    | X     | X    |

**Legend:**

X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B)).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

**U.S. Federal Regulations**

TSCA 12(b)

Not applicable

SARA 313

| Component | CAS-No   | Weight % | SARA 313 - Threshold Values % |
|-----------|----------|----------|-------------------------------|
| Toluene   | 108-88-3 | 62-64    | 1.0                           |

**SARA 311/312 Hazardous Categorization**

Acute Health Hazard Yes  
 Chronic Health Hazard Yes

|                                   |     |
|-----------------------------------|-----|
| Fire Hazard                       | Yes |
| Sudden Release of Pressure Hazard | No  |
| Reactive Hazard                   | No  |

**Clean Water Act**

| Component | CWA - Hazardous Substances | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants |
|-----------|----------------------------|-----------------------------|------------------------|---------------------------|
| Toluene   | X                          | 1000 lb                     | X                      | X                         |

**Clean Air Act**

| Component | HAPS Data | Class 1 Ozone Depletors | Class 2 Ozone Depletors |
|-----------|-----------|-------------------------|-------------------------|
| Toluene   | X         |                         | -                       |

**OSHA** Occupational Safety and Health Administration  
Not applicable

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Component | Hazardous Substances RQs | CERCLA EHS RQs |
|-----------|--------------------------|----------------|
| Toluene   | 1000 lb                  | -              |

**California Proposition 65** This product contains the following Proposition 65 chemicals:

| Component | CAS-No   | California Prop. 65                  | Prop 65 NSRL | Category      |
|-----------|----------|--------------------------------------|--------------|---------------|
| Toluene   | 108-88-3 | Developmental<br>Female Reproductive | -            | Developmental |

**State Right-to-Know**

| Component             | Massachusetts | New Jersey | Pennsylvania | Illinois | Rhode Island |
|-----------------------|---------------|------------|--------------|----------|--------------|
| Toluene               | X             | X          | X            | X        | X            |
| Isobutyl methacrylate | -             | X          | -            | -        | -            |

**U.S. Department of Transportation**

Reportable Quantity (RQ): Y  
DOT Marine Pollutant N  
DOT Severe Marine Pollutant N

**U.S. Department of Homeland Security**

This product does not contain any DHS chemicals.

**Other International Regulations**

**Mexico - Grade** No information available

**Canada**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

**WHMIS Hazard Class** B2 Flammable liquid  
D2A Very toxic materials





---

## 16. Other information

|                         |  |
|-------------------------|--|
| <b>Prepared By</b>      | Regulatory Affairs<br>Thermo Fisher Scientific<br>Email: EMSDS.RA@thermofisher.com   |
| <b>Creation Date</b>    | 17-Jun-2014  |
| <b>Revision Date</b>    | 17-Jun-2014  |
| <b>Print Date</b>       | 17-Jun-2014  |
| <b>Revision Summary</b> | This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS) |

### Disclaimer

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of SDS**