

## SAFETY DATA SHEET

Creation Date 16-Jan-2015

Revision Date 18-Jan-2018

Revision Number 3

### 1. Identification

**Product Name** Ethylenediamine

**Cat No. :** E479-4; E479-500; S80006

**Synonyms** 1,2-Diaminoethane; 1,2-Ethanediamine; Dimethylenediamine

**Recommended Use** Laboratory chemicals.

**Uses advised against** Not for food, drug, pesticide or biocidal product use

#### Details of the supplier of the safety data sheet

##### Company

Fisher Scientific  
One Reagent Lane  
Fair Lawn, NJ 07410  
Tel: (201) 796-7100

##### **Emergency Telephone Number**

CHEMTREC®, Inside the USA: 800-424-9300  
CHEMTREC®, Outside the USA: 001-703-527-3887

### 2. Hazard(s) identification

#### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 3
Acute oral toxicity	Category 4
Acute dermal toxicity	Category 3
Skin Corrosion/irritation	Category 1 B
Serious Eye Damage/Eye Irritation	Category 1
Respiratory Sensitization	Category 1
Skin Sensitization	Category 1

#### Label Elements

##### **Signal Word**

Danger

##### **Hazard Statements**

Flammable liquid and vapor  
Harmful if swallowed  
Toxic in contact with skin  
Causes severe skin burns and eye damage  
May cause allergy or asthma symptoms or breathing difficulties if inhaled  
May cause an allergic skin reaction

**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
 Do not eat, drink or smoke when using this product  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 In case of inadequate ventilation wear respiratory protection  
 Contaminated work clothing should not be allowed out of the workplace  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge

**Response**

Immediately call a POISON CENTER or doctor/physician

**Inhalation**

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

**Skin**

Wash contaminated clothing before reuse  
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
 If skin irritation or rash occurs: Get medical advice/attention

**Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

**Ingestion**

Rinse mouth  
 Do NOT induce vomiting

**Fire**

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep cool

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

None identified

### 3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Ethylene diamine	107-15-3	> 98

### 4. First-aid measures

**Eye Contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.

**Skin Contact**

Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.

<b>Inhalation</b>	Move to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required.
<b>Ingestion</b>	Do not induce vomiting. Call a physician or Poison Control Center immediately.
<b>Most important symptoms and effects</b>	Breathing difficulties. Causes burns by all exposure routes. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause allergic skin reaction. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing
<b>Notes to Physician</b>	Treat symptomatically

## 5. Fire-fighting measures

<b>Suitable Extinguishing Media</b>	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
<b>Unsuitable Extinguishing Media</b>	No information available
<b>Flash Point</b>	34 °C / 93.2 °F
<b>Method -</b>	No information available
<b>Autoignition Temperature</b>	385 °C / 725 °F
<b>Explosion Limits</b>	
<b>Upper</b>	14.2 vol %
<b>Lower</b>	2.6 vol %
<b>Sensitivity to Mechanical Impact</b>	No information available
<b>Sensitivity to Static Discharge</b>	No information available

### Specific Hazards Arising from the Chemical

Flammable. Corrosive Material. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

### Hazardous Combustion Products

Nitrogen oxides (NOx) Ammonia Hydrogen cyanide (hydrocyanic acid)

### Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### NFPA

<b>Health</b>	<b>Flammability</b>	<b>Instability</b>	<b>Physical hazards</b>
3	2	0	N/A

## 6. Accidental release measures

<b>Personal Precautions</b>	Use personal protective equipment. Evacuate personnel to safe areas. Remove all sources of ignition. Take precautionary measures against static discharges. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing.
<b>Environmental Precautions</b>	Avoid release to the environment. See Section 12 for additional ecological information.
<b>Methods for Containment and Clean Up</b>	Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

## 7. Handling and storage

<b>Handling</b>	Use only under a chemical fume hood. Wear personal protective equipment. Use spark-proof tools and explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapors or spray mist. Do not get in eyes, on skin, or on clothing. Do not ingest.
<b>Storage</b>	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Flammables area.

## 8. Exposure controls / personal protection

### Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Ethylene diamine	TWA: 10 ppm Skin	(Vacated) TWA: 10 ppm (Vacated) TWA: 25 mg/m <sup>3</sup> TWA: 10 ppm TWA: 25 mg/m <sup>3</sup>	IDLH: 1000 ppm TWA: 10 ppm TWA: 25 mg/m <sup>3</sup>	TWA: 10 ppm TWA: 25 mg/m <sup>3</sup> STEL: 3 mg/m <sup>3</sup>

### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

**Engineering Measures** Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location.

### Personal Protective Equipment

<b>Eye/face Protection</b>	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
<b>Skin and body protection</b>	Wear appropriate protective gloves and clothing to prevent skin exposure.
<b>Respiratory Protection</b>	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
<b>Hygiene Measures</b>	Handle in accordance with good industrial hygiene and safety practice.

## 9. Physical and chemical properties

<b>Physical State</b>	Liquid
<b>Appearance</b>	Clear, Viscous
<b>Odor</b>	Ammonia-like
<b>Odor Threshold</b>	No information available
<b>pH</b>	11.9 (25 %)
<b>Melting Point/Range</b>	8.5 °C / 47.3 °F
<b>Boiling Point/Range</b>	118 °C / 244.4 °F @ 760 mmHg
<b>Flash Point</b>	34 °C / 93.2 °F
<b>Evaporation Rate</b>	0.91 (Butyl Acetate = 1.0)
<b>Flammability (solid,gas)</b>	No information available
<b>Flammability or explosive limits</b>	
<b>Upper</b>	14.2 vol %
<b>Lower</b>	2.6 vol %
<b>Vapor Pressure</b>	12 mmHg @ 25 °C
<b>Vapor Density</b>	2.07 (Air = 1.0)

Specific Gravity	.8980
Solubility	Soluble in water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	385 °C / 725 °F
Decomposition Temperature	No information available
Viscosity	No information available
Molecular Formula	C <sub>2</sub> H <sub>8</sub> N <sub>2</sub>
Molecular Weight	60.1
VOC Content(%)	98

## 10. Stability and reactivity

<b>Reactive Hazard</b>	None known, based on information available
<b>Stability</b>	Stable under normal conditions.
<b>Conditions to Avoid</b>	Incompatible products. Excess heat.
<b>Incompatible Materials</b>	Acids, Acid anhydrides, Acid chlorides, Oxidizing agents
<b>Hazardous Decomposition Products</b>	Nitrogen oxides (NO <sub>x</sub> ), Ammonia, Hydrogen cyanide (hydrocyanic acid)
<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur.
<b>Hazardous Reactions</b>	None under normal processing.

## 11. Toxicological information

### Acute Toxicity

#### Product Information

#### Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethylene diamine	637 mg/kg ( Rat ) 866 mg/kg ( Rat )	LD50 = 560 mg/kg ( Rabbit )	14.7 mg/L/4h ( Rat )

**Toxicologically Synergistic Products** No information available

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Irritation</b>	Causes burns by all exposure routes
<b>Sensitization</b>	May cause sensitization by inhalation and skin contact
<b>Carcinogenicity</b>	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Ethylene diamine	107-15-3	Not listed	Not listed	Not listed	Not listed	Not listed

**Mutagenic Effects** No information available

**Reproductive Effects** No information available.

**Developmental Effects** No information available.

**Teratogenicity** No information available.

**STOT - single exposure** None known

**STOT - repeated exposure** None known

**Aspiration hazard** No information available

**Symptoms / effects, both acute and** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting:

**delayed** Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

**Endocrine Disruptor Information** No information available

**Other Adverse Effects** The toxicological properties have not been fully investigated.

## 12. Ecological information

### Ecotoxicity

This product contains the following substance(s) which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Ethylene diamine	EC50: = 151 mg/L, 96h (Pseudokirchneriella subcapitata) EC50: = 645 mg/L, 72h (Pseudokirchneriella subcapitata)	LC50: 180 - 560 mg/L, 96h semi-static (Poecilia reticulata) LC50: = 115.7 mg/L, 96h semi-static (Pimephales promelas) LC50: 191 - 254 mg/L, 96h flow-through (Pimephales promelas) LC50: 98.6 - 131.6 mg/L, 96h static (Pimephales promelas)	EC50 = 20 mg/L 15 min EC50 = 29 mg/L 17 h	EC50: = 17 mg/L, 48h (Daphnia magna)

**Persistence and Degradability** No information available

**Bioaccumulation/ Accumulation** No information available.

**Mobility** .

Component	log Pow
Ethylene diamine	-1.221

## 13. Disposal considerations

**Waste Disposal Methods** Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

## 14. Transport information

### DOT

UN-No UN1604  
 Proper Shipping Name ETHYLENEDIAMINE  
 Hazard Class 8  
 Subsidiary Hazard Class 3  
 Packing Group II

### TDG

UN-No UN1604  
 Proper Shipping Name ETHYLENEDIAMINE  
 Hazard Class 8  
 Subsidiary Hazard Class 3  
 Packing Group II

### IATA

UN-No UN1604  
 Proper Shipping Name ETHYLENEDIAMINE  
 Hazard Class 8  
 Subsidiary Hazard Class 3

<b>Packing Group</b>	II
<b>IMDG/IMO</b>	
<b>UN-No</b>	UN1604
<b>Proper Shipping Name</b>	ETHYLENEDIAMINE
<b>Hazard Class</b>	8
<b>Subsidiary Hazard Class</b>	3
<b>Packing Group</b>	II

## 15. Regulatory information

All of the components in the product are on the following Inventory lists: Australia X = listed China Canada The product is classified and labeled according to EC directives or corresponding national laws The product is classified and labeled in accordance with Directive 1999/45/EC Europe TSCA Korea Philippines Japan

### International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Ethylene diamine	X	X	-	203-468-6	-		X	X	X	X	X

#### Legend:

X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B)).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

### U.S. Federal Regulations

TSCA 12(b) Not applicable

SARA 313 Not applicable

SARA 311/312 Hazard Categories See section 2 for more information

### CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Ethylene diamine	X	5000 lb	-	-

Clean Air Act Not applicable

OSHA Occupational Safety and Health Administration  
Not applicable

### CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs
Ethylene diamine	5000 lb	5000 lb

California Proposition 65 This product does not contain any Proposition 65 chemicals

### U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Ethylene diamine	X	X	X	-	X

**U.S. Department of Transportation**

Reportable Quantity (RQ): N  
DOT Marine Pollutant N  
DOT Severe Marine Pollutant N

**U.S. Department of Homeland Security**

This product contains the following DHS chemicals:

Component	DHS Chemical Facility Anti-Terrorism Standard
Ethylene diamine	15000 lb STQ

**Other International Regulations**

**Mexico - Grade** Serious risk, Grade 3

**16. Other information**

**Prepared By** Regulatory Affairs  
Thermo Fisher Scientific  
Email: EMSDS.RA@thermofisher.com

**Creation Date** 16-Jan-2015

**Revision Date** 18-Jan-2018

**Print Date** 18-Jan-2018

**Revision Summary** This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**