

VIRGINIA METAL CLEANING DETERGENT
Material Safety Data Sheet

SECTION I - COMPANY IDENTIFICATION

PRODUCT: VIRGINIA METAL CLEANING DETERGENT

CAT. NO.: WD-1, WD-5, WD-55

MANUFACTURED BY:
Virginia KMP Corporation
4100 Platinum Way
Dallas, Texas 75237

TELEPHONE NUMBERS:
Office: 1-(214) 330-7731
Emergency Only: 1-(800) 424-9300

SECTION II - HAZARDOUS INGREDIENTS

OSHA Hazardous Components (29 CFR 1910.1200)

EXPOSURE LIMITS: 8 HR. TWA
OSHA PEL **ACGIH TLV**

Ethylene glycol monobutyl ether (CAS# 111-76-2)
Dodecylbenzene sulfonic acid (CAS# 27176-87-0)

25 ppm (skin) 25 ppm (skin)
NE NE

SECTION III - HAZARDS IDENTIFICATIONS

EMERGENCY OVERVIEW: WARNING! Eye and skin irritant. Harmful if swallowed or inhaled.

POTENTIAL HEALTH EFFECTS:

INHALATION: Inhalation of vapors in high concentration may cause headache, nausea, vomiting.

EYE CONTACT: Irritation develops immediately on contact.

SKIN CONTACT: Irritation develops on contact.

INGESTION: Harmful if swallowed. May cause headache, nausea, vomiting.

CHRONIC Effects: Not established.

NOTE:

CARCINOGENICITY: LISTED IN NTP? No

IARC? No

OSHA Regulated? No

SECTION IV - FIRST AID MEASURES

INHALATION: Remove victim to fresh air and, if needed, immediately begin artificial respiration. Give oxygen if breathing is labored. Get emergency medical help. Contact a physician immediately.

EYE CONTACT: Flush eyes with water for 15 minutes. Get medical attention if symptoms develop and persist.

SKIN CONTACT: Flush with water or soap and water for 15 minutes or until all traces have been removed. Seek medical attention if symptoms develop and persist.

INGESTION: Do not induce vomiting. Rinse mouth out with water. Get immediate medical attention.

SECTION V - FIRE FIGHTING MEASURES

FLASHPOINT (TEST METHOD): Not flammable - aqueous solution.

FLAMMABLE LIMITS: NA

LOWER: NA

UPPER: NA

AUTOIGNITION TEMPERATURE:

NE

GENERAL HAZARD:

FIRE FIGHTING INSTRUCTIONS: Approach fire from upwind side. Avoid breathing smoke, fumes, mist, or vapors on the downwind side. Firefighters wear protective clothing and self contained breathing apparatus.

EXTINGUISHING MEDIA: Dry powder, carbon dioxide (CO₂), water fog or spray.

HAZARDOUS COMBUSTION PRODUCTS: Acrid smoke, irritating and toxic fumes of SO_x, H₂S, PO_x.

SECTION VI - ACCIDENTAL RELEASE MEASURES

LAND SPILL: SMALL SPILLS: Flush to sewer with large amounts of water. 10 parts water to 1 part product.

LARGE SPILLS: Pick up with absorbent media, place in non-leaking containers for proper disposal or reuse.

WATER SPILL: Notify proper authorities.

Clean up leaks/spills immediately to prevent soil or water contamination.

SECTION VII - HANDLING AND STORAGE

HANDLING: Avoid contact with skin, eyes, and clothing. After handling this product, wash hands before eating, drinking, or smoking. If contact occurs, remove contaminated clothing. If needed, take first aid action shown in section IV. Launder contaminated clothing before reuse.

STORAGE: Store away from food stuffs.

VIRGINIA METAL CLEANING DETERGENT

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Local exhaust ventilation.
PERSONAL PROTECTION: Respiratory protection not normally needed under normal conditions of use. Use rubber or latex gloves, chemical goggles or full face shields. Use boots, aprons, drench showers, eye wash as needed for protection against spills and/or splashes.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

VAPOR PRESSURE: ND
SPECIFIC GRAVITY (H₂O=1): 1.02
SOLUBILITY IN WATER: Complete
pH: 11-12
BOILING POINT: 212 F
APPEARANCE & ODOR: Yellow liquid, with lemon odor.

VAPOR DENSITY (Air=1): ND
EVAPORATION RATE(BuAc=1): <1
VOC (G/L): ND
FREEZING POINT: ND

SECTION X - STABILITY AND REACTIVITY

STABILITY: Stable.
CONDITIONS TO AVOID: High temperatures.
MATERIALS TO AVOID: Oxidizers.
HAZARDOUS DECOMPOSITION PRODUCTS: SO_x, H₂S, PO_x and from combustion - smoke and toxic fumes.
HAZARDOUS POLYMERIZATION: Will not occur.

SECTION XI - TOXICOLOGICAL INFORMATION

Ethylene Glycolmonobutylether	TDL _o :	600 mg/kg	(oral - wmn)
	TCL _o :	195 ppm/8hr	(inh - human) GIT
	TCL _o :	100 ppm	(inh - human) NOSE, EYE, CNS
	LD50:	470 mg/kg	(oral - rat)
	LC50:	2900 mg/m ³	(inh - rat)
Dodecyl benzene sulfonic acid	LD50:	50-500 mg/kg	(oral - mouse)

SECTION XII - ECOLOGICAL INFORMATION

Harmful to aquatic life in very low concentrations. Ethylene Glycolmonobutylether 1000 ppm / 24 hr / brine shrimp / TLm
Dodecyl benzene sulfonic acid 5 - 15 ppm / guppy / lethal conc

SECTION XIII - DISPOSAL CONSIDERATIONS

Dispose as hazardous waste. Classification and documentation is required before disposal. Follow all local, state and federal regulations.

SECTION XIV - TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: Not regulated if container holds less than 1175 gallons.

HAZARD CLASS: NA
IDENTIFICATION NUMBER: NA
DOT Emergency Guide #: NA
Reportable Quantity (RQ): 1175 gallons (dodecyl benzene sulfonic acid)
International: NA

SECTION XV - REGULATORY INFORMATION

TSCA (Toxic Substance Control Act): Components of this product are listed on the TSCA Inventory.
CERCLA (Comprehensive Environmental Response, Compensation and Liability Act):
Reportable quantity is 1175 gallons (dodecyl benzene sulfonic acid). Contact local authorities for other reporting requirements.

SARA TITLE III (Superfund Amendments and Reauthorization Act):
Section 313: Ethylene Glycol Monobutyl Ether (a glycol ether) <10%

CALIFORNIA PROPOSITION 65: Not listed.

SECTION XVI - OTHER INFORMATION

State Right-to-Know Programs: MA, NJ, PA

NFPA Ratings

Health: 1
Flammability: 0
Reactivity: 0

HMIS Protective Equipment: X See your supervisor

Prepared by: Virginia KMP Corporation

revised: 8/29/99

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Virginia KMP. The data on this sheet related only to specific material designated herein. Virginia KPM assumes no legal responsibility for use or reliance upon these data.