Safety Data Sheet

Printing date 02/04/2016 Revised On 02/04/2016

1 Identification of the substance and manufacturer

Trade name: **HI TECH LIGHT GRAY PRIMER**

Product code: 0000160831
Product category PC9a Paints and coatings.
Manufacturer/Supplier: Seymour of Sycamore
917 Crosby Avenue
Sycamore, IL 60178
Phone: 815-895-9101 www.seymourpaint.com
Emergency telephone number: CHEMTEL 1-800-255-3924, or 813-248-0585.

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1	H222	Extremely flammable aerosol.
Press. Gas	H280	Contains gas under pressure; may explode if heated.
Eye Irrit. 2A	H319	Causes serious eye irritation.
Repr. 2	H361	Suspected of damaging fertility or the unborn child.
STOT SE 3	H336	May cause drowsiness or dizziness.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

Signal word Danger
Hazard statements
Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes serious eye irritation.
Suspected of damaging fertility or the unborn child.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.

Precautionary statements
Obtain special instructions before use.
Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Wash hands thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
Do not handle until all safety precautions have been read and understood.
Do not breathe dust/fume/gas/mist/vapors/spray.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Call a POISON CENTER/doctor if you feel unwell.
If eye irritation persists: Get medical advice/attention.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Protect from sunlight. Store in a well-ventilated place.
Store in a well-ventilated place. Keep container tightly closed.
Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures
Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	Acetone	24.23%
74-98-6	propane	13.87%
106-97-8	n-butane	8.15%
64742-89-8	VM&P Naphtha	5.58%
13463-67-7	titanium dioxide	5.13%
108-88-3	Toluene	5.07%
14807-96-6	Talc	4.49%
1330-20-7	xylene (mix)	4.09%
64-17-5	ethyl alcohol	3.98%
123-86-4	n-butyl acetate	2.78%
64742-47-8	Mineral Spirits	2.63%
110-19-0	isobutyl acetate	1.62%
67-63-0	isopropyl alcohol	1.39%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
After swallowing: Rinse out mouth and then drink plenty of water.
Rinse mouth with water. Do not induce vomiting.

(Contd. on page 2)

Safety Data Sheet

Trade name: HI TECH LIGHT GRAY PRIMER

(Contd. of page 1)

Most important symptoms and effects: Dizziness
Indication of any immediate medical attention needed: No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.
Special hazards: Can form explosive gas-air mixtures.
Protective equipment for firefighters: A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures: Wear protective equipment. Keep unprotected persons away.
Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up: Ensure adequate ventilation.
Dispose contaminated material as waste according to section 13.

7 Handling and storage

Precautions for safe handling Use only in well ventilated areas.
Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

67-64-1 Acetone	
PEL (USA)	Long-term value: 2400 mg/m³, 1000 ppm
REL (USA)	Long-term value: 590 mg/m³, 250 ppm
TLV (USA)	Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm BEI
74-98-6 propane	
PEL (USA)	Long-term value: 1800 mg/m³, 1000 ppm
REL (USA)	Long-term value: 1800 mg/m³, 1000 ppm
TLV (USA)	refer to Appendix F inTLVs and BEIs book
106-97-8 n-butane	
REL (USA)	Long-term value: 1900 mg/m³, 800 ppm
TLV (USA)	Short-term value: 2370 mg/m³, 1000 ppm
108-88-3 Toluene	
PEL (USA)	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL (USA)	Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm
TLV (USA)	Long-term value: 75 mg/m³, 20 ppm BEI
1330-20-7 xylene (mix)	
PEL (USA)	Long-term value: 435 mg/m³, 100 ppm
REL (USA)	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm
TLV (USA)	Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI
64-17-5 ethyl alcohol	
PEL (USA)	Long-term value: 1900 mg/m³, 1000 ppm
REL (USA)	Long-term value: 1900 mg/m³, 1000 ppm
TLV (USA)	Short-term value: 1880 mg/m³, 1000 ppm
123-86-4 n-butyl acetate	
PEL (USA)	Long-term value: 710 mg/m³, 150 ppm
REL (USA)	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm
TLV (USA)	Short-term value: (950) NIC-712 mg/m³, (200) NIC-150 ppm Long-term value: (713) NIC-238 mg/m³, (150) NIC-50 ppm
110-19-0 isobutyl acetate	
PEL (USA)	Long-term value: 700 mg/m³, 150 ppm
REL (USA)	Long-term value: 700 mg/m³, 150 ppm
TLV (USA)	Short-term value: NIC-712 mg/m³, NIC-150 ppm Long-term value: (713) NIC-238 mg/m³, (150) NIC-50 ppm

(Contd. on page 3)

Safety Data Sheet

Trade name: HI TECH LIGHT GRAY PRIMER

(Contd. of page 2)

67-63-0 isopropyl alcohol	
PEL (USA)	Long-term value: 980 mg/m³, 400 ppm
REL (USA)	Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm
TLV (USA)	Short-term value: 984 mg/m³, 400 ppm Long-term value: 492 mg/m³, 200 ppm BEI

Ingredients with biological limit values:

67-64-1 Acetone	
BEI (USA)	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)

108-88-3 Toluene	
BEI (USA)	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene 0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene 0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

1330-20-7 xylene (mix)	
BEI (USA)	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids

67-63-0 isopropyl alcohol	
BEI (USA)	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use.
Immediately remove all soiled and contaminated clothing.
Wash hands after use.
Avoid contact with the eyes and skin.
Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.

Hand protection: Nitrile gloves.
Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol.
Odor: Aromatic
Odor threshold: Not determined.

pH-value: Not determined.
Melting point/Melting range Undetermined.
Boiling point: -110 °C (-166 °F)

Flash point: -19 °C (-2 °F)
Flammability (solid, gas): Extremely flammable.

Decomposition temperature: Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit: 1.7 Vol %
Upper Explosion Limit: 10.9 Vol %

Vapor pressure: Not determined.
Relative Density: Between 0.77 and 0.85 (Water equals 1.00)
Vapour density Not determined.
Evaporation rate Not applicable.
Partition coefficient: n-octonal/water: Not determined.

Solubility: Not determined.
Viscosity: Not determined.

VOC content: 538.5 g/l / 4.49 lb/gl
VOC content (less exempt solvents): 51.7 %

(Contd. on page 4)

Safety Data Sheet

Printing date 02/04/2016 Revised On 02/04/2016

Trade name: HI TECH LIGHT GRAY PRIMER

(Contd. of page 3)

MIR Value: 1.09

Solids content: 23.6 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.
Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Chemical stability: Not fully evaluated.
Possibility of hazardous reactions: No dangerous reactions known.
Incompatible materials: No further relevant information available.
Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

106-97-8 n-butane		
Inhalative	LC50/4 h	658 mg/l (rat)
13463-67-7 titanium dioxide		
Oral	LD50	>20000 mg/kg (rat)
Dermal	LD50	>10000 mg/kg (rbt)
Inhalative	LC50/4 h	>6.82 mg/l (rat)
1330-20-7 xylene (mix)		
Oral	LD50	8700 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)
Inhalative	LC50/4 h	6350 mg/l (rat)
64-17-5 ethyl alcohol		
Oral	LD50	7060 mg/kg (rat)
Inhalative	LC50/4 h	20000 mg/l (rat)
123-86-4 n-butyl acetate		
Oral	LD50	14000 mg/kg (rat)
Inhalative	LC50/4 h	>21.0 mg/l (rat)
110-19-0 isobutyl acetate		
Oral	LD50	4763 mg/kg (rbt)
67-63-0 isopropyl alcohol		
Oral	LD50	4570 mg/kg (rat)
Dermal	LD50	13400 mg/kg (rab)
Inhalative	LC50/4 h	30 mg/l (rat)

Information on toxicological effects: No data available.
Skin effects: No irritant effect.
Eye effects: Irritating effect.
Sensitization: No sensitizing effects known.

Carcinogenic categories

IARC (International Agency for Research on Cancer)		
13463-67-7	titanium dioxide	2B
108-88-3	Toluene	3
14807-96-6	Talc	2B
1330-20-7	xylene (mix)	3
64-17-5	ethyl alcohol	1
67-63-0	isopropyl alcohol	3

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.
Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.
Bioaccumulative potential: No further relevant information available.
Mobility in soil: No further relevant information available.
Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950
DOT N/A
DOT Consumer Commodity ORM-D
Aerosols, flammable

(Contd. on page 5)

Safety Data Sheet

Trade name: HI TECH LIGHT GRAY PRIMER

(Contd. of page 4)

ADR	1950 Aerosols
Transport hazard class(es):	
Class	2.1
Marine pollutant:	No
Special precautions for user:	Warning: Gases
EMS Number:	F-D,S-U
Packaging Group:	--
UN "Model Regulation":	UN1950, Aerosols, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-88-3	Toluene
1330-20-7	xylene (mix)
67-63-0	isopropyl alcohol

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

13463-67-7	titanium dioxide
100-41-4	ethyl benzene
1333-86-4	Carbon black
108-10-1	methyl isobutyl ketone

California Proposition 65 chemicals known to cause developmental toxicity: 108-88-3 Toluene
67-56-1 Methanol

CANADIAN ENVIRONMENTAL PROTECTION ACT: All hazardous ingredients for this product appear on the Canadian Domestice Substance List.

WHMIS Symbols for Canada: A - Compressed gas
D2A - Very toxic material causing other toxic effects

EPA:

67-64-1	Acetone	I
108-88-3	Toluene	II
1330-20-7	xylene (mix)	I
110-19-0	isobutyl acetate	D

16 Other information

Contact:	Regulatory Affairs
Date of preparation / last revision	02/04/2016 / -