

SAFETY DATA SHEET

Version 6.7 Revision Date 06/30/2021 Print Date 09/25/2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 **Product identifiers**

Product name : Lithium aluminium hydride

Product Number : 199877 Brand Aldrich

Index-No. : 001-002-00-4 : 16853-85-3 CAS-No.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company Sigma-Aldrich Inc.

3050 SPRUCE ST ST. LOUIS MO 63103 **UNITED STATES**

Telephone : +1 314 771-5765 +1 800 325-5052 Fax

Emergency telephone

800-424-9300 CHEMTREC (USA) +1-703-Emergency Phone #

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Chemicals which, in contact with water, emit flammable gases (Category 1), H260 Skin corrosion (Category 1A), H314

Serious eye damage (Category 1), H318

Short-term (acute) aquatic hazard (Category 3), H402

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram

Signal word Danger



Hazard statement(s)	
H260	In contact with water releases flammable gases which may ignite spontaneously.
H314	Causes severe skin burns and eye damage.
H402	Harmful to aquatic life.
Precautionary statement(s)	
P223	Do not allow contact with water.
P231 + P232	Handle under inert gas. Protect from moisture.
P260	Do not breathe dusts or mists.
P264	Wash skin thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 +	IF IN EYES: Rinse cautiously with water for several minutes.
P310	Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P335 + P334	Brush off loose particles from skin. Immerse in cool water/ wrap in wet bandages.
P363	Wash contaminated clothing before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P402 + P404	Store in a dry place. Store in a closed container.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

plant.

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : LAH

Formula : H₄AlLi

Molecular weight : 37.95 g/mol

CAS-No. : 16853-85-3

EC-No. : 340-877-9

EC-No. : 240-877-9 Index-No. : 001-002-00-4

Component	Classification	Concentration				
aluminium lithium hydride						
	1; Skin Corr. 1A; Eye	<= 100 %				
	Dam. 1; Aquatic Acute 3;					
	H260, H314, H318, H402					

For the full text of the H-Statements mentioned in this Section, see Section 16.



SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Call a physician immediately. Do not attempt to neutralise.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Sand Dry powder Cement

Unsuitable extinguishing media

Water Carbon dioxide (CO2) Foam

5.2 Special hazards arising from the substance or mixture

Lithium oxides

Aluminum oxide

Combustible.

Risk of dust explosion.

May not get in touch with: Water

Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

Millipore

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid inhalation of dusts. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Sweep up and shovel. Do not flush with water. Keep in suitable, closed containers for disposal. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up dry. Dispose of properly. Clean up affected area. Avoid generation of dusts.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Keep workplace dry. Do not allow product to come into contact with water. **Advice on safe handling**

Keep workplace dry. Do not allow product to come into contact with water.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Keep away from heat and sources of ignition.

Never allow product to get in contact with water during storage.

Handle and store under inert gas. Reacts violently with water.

Storage class (TRGS 510): 4.3: Hazardous materials, which set free flammable gases upon contact with water

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

Aldrich - 199877

Millipore SiGMa

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles

Skin protection

Handle with impervious gloves.

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm Break through time: 480 min

Material tested: KCL 741 Dermatril® L

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm Break through time: 480 min

Material tested: KCL 741 Dermatril® L

Body Protection

protective clothing

Respiratory protection

required when dusts are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance Form: powder

b) Odor No data availablec) Odor Threshold No data availabled) pH No data available

e) Melting point/range: 125 °C (257 °F) - dec.

point/freezing point

f) Initial boiling point 89 - 90 °C 192 - 194 °F at 2.66 hPa

Aldrich - 199877

Millipore SiGMa and boiling range

g) Flash point ()Not applicable
 h) Evaporation rate No data available
 i) Flammability (solid, No data available

gas)

j) Upper/lower No data available flammability or explosive limits

k) Vapor pressure No data available
 l) Vapor density No data available
 m) Relative density No data available
 n) Water solubility No data available

o) Partition coefficient: Not applicable for inorganic substances

n-octanol/water

p) Autoignition temperature No data available

q) Decomposition temperature

No data available

r) Viscosity No data availables) Explosive properties No data availablet) Oxidizing properties No data available

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

The following applies in general to flammable organic substances and mixtures: in correspondingly fine distribution, when whirled up a dust explosion potential may generally be assumed.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature).

10.3 Possibility of hazardous reactions

Risk of ignition or formation of inflammable gases or vapours with:

Water

Oxygen

Alcohols

acids

Risk of explosion with:

boron compounds

Ether

Dioxane

Organic Substances

Oxidizing agents

amides



hydrogen peroxide Esters acetonitrile Peroxides Exothermic reaction with: Aldehydes pyridine

10.4 Conditions to avoid

Moisture.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Oral: No data available Inhalation: No data available Dermal: No data available

No data available

Skin corrosion/irritation

Causes severe burns. Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Serious eye damage/eye irritation

Causes serious eye damage. Risk of corneal clouding.

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

Reproductive toxicity

Lithium and its compounds are possible teratogens by analogy to lithium carbonate which has equivocal human teratogenic data and positive animal teratogenic data.

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available



Aspiration hazard

No data available

11.2 Additional Information

Large doses of lithium ion have caused dizziness and prostration, and can cause kidney damage if sodium intake is limited. Dehydration, weight loss, dermatological effects, and thyroid disturbances have been reported. Central nervous system effects that include slurred speech, blurred vision, sensory loss, ataxia, and convulsions may occur. Diarrhea, vomiting, and neuromuscular effects such as tremor, clonus, and hyperactive reflexes may occur as a result of repeated exposure to lithium ion.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Decomposition of the substance with tissue moisture.

The following applies to lithium compounds in general: when handled or used inappropriately, the absorption of large quantities is followed by CNS disorders, agitation, spasms, ataxia (impaired locomotor coordination) due to disturbed electrolyte balance.

The following applies to aluminium compounds in general: After swallowing: only slightly absorbable via the gastrointestinal tract. Serious disorders in man (from about 4000 mg aluminium up): phosphate metabolism, calcium metabolism.

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

Liver - Irregularities - Based on Human Evidence

Liver - Irregularities - Based on Human Evidence

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish	static test LC50 - Danio rerio ((zebra fish) - 99 mg/l - 96	h

(OECD Test Guideline 203)

Toxicity to daphnia and other aquatic

static test EC50 - Daphnia magna (Water flea) - 54.4 mg/l - 48 h

and other aquatic invertebrates

(OECD Test Guideline 202)

Toxicity to algae static test ErC50 - Pseudokirchneriella subcapitata - 138.76 mg/l -

72 h

(OECD Test Guideline 201)

Toxicity to bacteria static test EC50 - activated sludge - 286.4 mg/l - 3 h

(OECD Test Guideline 209)

12.2 Persistence and degradability

The methods for determining biodegradability are not applicable to inorganic substances.

12.3 Bioaccumulative potential

No data available



12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

Biological effects:

Harmful effect due to pH shift.

Forms corrosive mixtures with water even if diluted.

Discharge into the environment must be avoided.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

DOT (US)

UN number: 1410 Class: 4.3 Packing group: I

Proper shipping name: Lithium aluminum hydride

Reportable Quantity (RQ): Poison Inhalation Hazard: No

IMDG

UN number: 1410 Class: 4.3 Packing group: I EMS-No: F-G, S-M

Proper shipping name: LITHIUM ALUMINIUM HYDRIDE

IATA

UN number: 1410 Class: 4.3 Packing group: I

Proper shipping name: Lithium aluminium hydride IATA Passenger: Not permitted for transport

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

CAS-No.

Massachusetts Right To Know Components

aluminium lithium hydride 16853-85-3

Aldrich - 199877 Page 9 of 10

Revision Date

1993-04-24

No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know Components

aluminium lithium hydride CAS-No. Revision Date

16853-85-3 1993-04-24

New Jersey Right To Know Components

aluminium lithium hydride CAS-No. Revision Date

16853-85-3 1993-04-24

SECTION 16: Other information

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.7 Revision Date: 06/30/2021 Print Date: 09/25/2021

