

MATERIAL SAFETY DATA SHEET
Required under USDL Safety and Health Regulations

SECTION I - CHEMICAL COMPANY AND PRODUCT IDENTIFICATION

POWER SERVICE PRODUCTS

P.O. BOX 1089

WEATHERFORD, TEXAS 76086

817/599-9486

e-mail: psp@powerservice.com

Product Name: DIESEL FUEL SUPPLEMENT
Synonyms: DIESEL FUEL ADDITIVE
Generic/Chemical Name: HYDROCARBONS, HYDROXY COMPOUNDS
MSDS Preparation Date: March 23, 2000 – supersedes July 1, 1999
Emergency Phone Number: 800/424-9300

SECTION II - COMPOSITION/INFORMATION OF INGREDIENTS

<u>INGREDIENT</u>	<u>PERCENT</u>
HYDROCARBONS	1 - 3
HYDROXY COMPOUNDS	70 - 80
AROMATICS	20 - 30

This product is a proprietary complex mixture of petroleum Hydrocarbons and Hydroxy Compounds. Specific chemical information is being withheld as a Trade Secret. Specific chemical information will be made available to health professionals in accordance with 29 CFR 1910.1200.

SECTION III - HAZARD IDENTIFICATION

EMERGENCY AND FIRST AID PROCEDURES: If overcome by vapors, remove from exposure immediately; call a physician. If breathing is irregular or stopped, start resuscitation, administer oxygen. If swallowed, do not induce vomiting; call a physician. Remove contaminated clothing and wash skin with soap and water. Flush eyes with water until irritation subsides.

PRIMARY ROUTE (S) OF ENTRY: INGESTION AND INHALATION

VARIABILITY AMONG INDIVIDUALS: Health Studies have shown that many petroleum hydrocarbons and synthetic lubricants pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists and fumes should be minimized.

NATURE OF HAZARD AND TOXICITY INFORMATION: Prolonged or repeated skin contact with this product tends to remove skin oils possibly leading to irritation and dermatitis; however, based on human experiences and available toxicological data, this product is judged to be neither a "corrosive" nor an "irritant".

Potential risk to humans can be minimized by observing good work practices and personal hygiene procedures generally recommended for petroleum products. The product has a low order of acute toxicity, but minute amounts aspirated into the lungs during ingestion may cause severe pulmonary injury or death.

WASHINGTON COUNTY

SEP 25 2001

RISK MANAGEMENT

PAGE 2: DIESEL FUEL SUPPLEMENT**SECTION IV - FIRST AID MEASURES**

EYE CONTACT: Flush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention.

SKIN CONTACT: Flush with large amounts of water, use soap if available. Remove grossly contaminated clothing, including shoes and launder before re-use.

INHALATION: Using proper respiration protection. Immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention.

INGESTION: If swallowed do not induce vomiting. Keep at rest. Get prompt medical attention.

SECTION V - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT53°F (TCC)

FLAMMABLE LIMITS: lower2 upper12

EXTINGUISHING MEDIA: Alcohol resistant foam, dry chemical, CO₂, waterspray or fog.

SPECIAL FIRE FIGHTING PROCEDURES: Use air-supplied rescue equipment for enclosed areas. Cool exposed containers with water.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Do not store or mix with strong oxidants or combustible liquids.

EMPTY CONTAINERS CONTAIN FLAMMABLE VAPORS: "DO NOT USE CUTTING TORCH EQUIPMENT OR ANY OTHER FLAME ON ANY EMPTY CONTAINER".

SECTION VI - ACCIDENTAL RELEASE PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all ignition sources. Keep people away. Recover free liquid. Add absorbent to spill area. Avoid breathing vapors. Ventilate enclosed spaces. Open all windows and doors. Keep petroleum products out of public sewers, streams and waterways.

SECTION VII - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep containers closed. Keep away from heat, sparks and open flames.

CONTAINERS ARE STRICTLY "SINGLE TRIP CONTAINERS." THEY ARE NOT TO BE USED FOR ANY REASON AFTER BEING EMPTIED.

OTHER PRECAUTIONS: Avoid breathing vapors. Avoid prolonged or repeated contact with skin. Remove contaminated clothing; wash before re-use. Wash skin with soap and water after contact.

PAGE 3: DIESEL FUEL SUPPLEMENT

SECTION VIII - EXPOSURE CONTROLS AND PERSONAL PROTECTION

	OSHA		ACGIH
	TWA	STEL	
	PPM	MgM3	PPM
	400	980	400
			MgM3
			980
Carcinogen - NTP Program		500	
		1225	
Carcinogen - IARC Program			

EFFECTS OF OVEREXPOSURE: Avoid breathing vapor. Inhalation of high vapor concentrations may have results ranging from dizziness and headaches to unconsciousness. Prolonged or repeated liquid contact will dry and defat the skin leading to irritation and dermatitis.

RESPIRATORY PROTECTION (Specify type): Hydrocarbon vapor canister or supplied-air hose if needed.

VENTILATION:

- LOCAL EXHAUSTFace velocity > 60 fpm
- MECHANICAL (General)Explosion - proof ventilation equipment.
- SPECIALUse only with adequate ventilation.
- OTHERNo smoking or open flames.

PROTECTIVE GLOVES: Normally not needed. Use chemical resistant gloves if necessary.

EYE PROTECTION: Normally not needed.

OTHER PROTECTION EQUIPMENT: Hydrocarbon insoluble apron if needed.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT	176°F
VAPOR PRESSURE (mmHG).....	32 @ 68°F
VAPOR DENSITY (AIR =1).....	2.1
SOLUBILITY IN WATER	partial
SPECIFIC GRAVITY (H2O =1)	0.82
PERCENT, VOLATILE BY VOLUME (%)	100
VAPORATION RATE	1.4
APPEARANCE	yellow
ODOR	solvent

PAGE 4: DIESEL FUEL SUPPLEMENT**SECTION X - STABILITY AND REACTIVITY**

STABILITY	Stable
INCOMPATIBILITY (Materials to avoid)	NONE
HAZARDOUS DECOMPOSITION PRODUCTS	Will not occur
HAZARDOUS POLYMERIZATION	Will not occur

CONDITIONS TO AVOID:

1. Prolonged or repeated breathing of vapors
2. Contact with eyes
3. Prolonged or repeated contact with skin

SECTION XI - TOXICOLOGICAL INFORMATION

This product does not contain any toxic chemicals that are subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

SECTION XII - ECOLOGICAL INFORMATION

THIS PRODUCT DOES NOT CONTAIN ANY OZONE DEPLETING CHEMICALS

SECTION XIII - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: This product, if discarded, becomes a hazardous waste under CERCLA. Use the following information:

Proper Shipping Name: **RQ Waste Flammable Liquid N.O.S.**
Class: **3**
I.D. Number: **UN 1993**
Pk Group: **II**
RCRA WASTE Number: **D001**

Waste disposal should be in compliance with federal, state and local law.

SECTION XIV - TRANSPORTATION INFORMATION

Part #1155 - 55 gal. (drums)
PROPER SHIPPING NAME: **FLAMMABLE LIQUID, NOS (HYDROCARBONS)**
HAZARD CLASS: **3**
I.D. NUMBER: **UN 1993**
PACKING GROUP: **II**
PLACARDING: **REQUIRED WHEN WEIGHT IS OVER 1000 POUNDS**

PAGE 5: DIESEL FUEL SUPPLEMENT**Part #1041- 96 oz. (case)****PROPER SHIPPING NAME: FLAMMABLE LIQUID, NOS (HYDROCARBONS)****HAZARD CLASS: 3****I.D. NUMBER: UN 1993 "LIMITED QUANTITY"****PACKING GROUP: 3****PLACARDING: NOT REQUIRED****SPECIAL PACKING: NOT REQUIRED****Part #1025 - 32 oz. (case)****PROPER SHIPPING NAME: CONSUMER COMMODITY ORM-D****HAZARD CLASS: NA****I.D. NUMBER: NA****PACKING GROUP: 3****PLACARDING: NOT REQUIRED****SPECIAL PACKING: NOT REQUIRED****SECTION XV - REGULATORY INFORMATION****RIGHT TO KNOW TIER II REPORTING INFORMATION SECTION 311-312****CHEMICAL DESCRIPTION: HYDROXY COMPOUNDS AND HYDROCARBONS****COMMON (LABEL) NAME: DIESEL FUEL SUPPLEMENT****TYPE OF PRODUCT: MIX - LIQUID****PHYSICAL HAZARD: FIRE****HEALTH HAZARD: IMMEDIATE (ACUTE)****REACTIVITY: NONE****EXTREMELY HAZARDOUS SUBSTANCES: NONE****EMERGENCY RESPONSE GUIDEBOOK PAGE NUMBER: 26****NFPA RATING:****HEALTH: 2****FIRE: 3****REACTIVITY: 0**