

SAFETY DATA SHEET

Version 8.15 Revision Date 03/02/2024 Print Date 06/15/2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name	:	Methanol GR ACS
Product Number Brand Index-No. CAS-No.	:	MX0485 Millipore 603-001-00-X 67-56-1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	:	Reagent for analysis
Uses advised against	:	The product is being supplied under the TSCA R&D Exemption (40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by MilliporeSigma.

1.3 Details of the supplier of the safety data sheet

Company	:	Sigma-Aldrich Inc. 3050 SPRUCE ST ST. LOUIS MO 63103 UNITED STATES
Telephone Fax		+1 314 771-5765 +1 800 325-5052

1.4 Emergency telephone

Emergency Phone #	: 800-424-9300 CHEMTREC (USA) +1-703-
	527-3887 CHEMTREC (International) 24
	Hours/day; 7 Days/week

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Acute toxicity, Oral (Category 3), H301 Acute toxicity, Inhalation (Category 3), H331 Acute toxicity, Dermal (Category 3), H311

Millipore - MX0485

Page 1 of 14



Specific target organ toxicity - single exposure (Category 1), Eyes, Central nervous system, H370

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pi	ct	oa	ra	m	
	υu	υg	ıч		

Pictogram	
Signal Word	Danger
Hazard Statements H225 H301 + H311 + H331 H370	Highly flammable liquid and vapor. Toxic if swallowed, in contact with skin or if inhaled. Causes damage to organs (Eyes, Central nervous system).
Precautionary Statements P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 P240 P241 P242	Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools.
P243 P260 P264 P270	Take precautionary measures against static discharge. Do not breathe mist or vapors. Wash skin thoroughly after handling.
P270 P271 P280 P301 + P310 + P330	Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/ eye protection/ face protection. IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353	Rinse mouth. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P311	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor.
P307 + P311 P362 P370 + P378	IF exposed: Call a POISON CENTER or doctor/ physician. Take off contaminated clothing and wash before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant
P403 + P233 P403 + P235 P405 P501	foam to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances Formula Molecular weight

: CH4O : 32.04 g/mol

Millipore - MX0485

Page 2 of 14



CAS-No.	:	67-56-1
EC-No.	:	200-659-6
Index-No.	:	603-001-00-X

Component	Classification	Concentration
Methanol		
	Flam. Liq. 2; Acute Tox. 3; STOT SE 1; H225, H301, H331, H311, H370 Concentration limits: >= 10 %: STOT SE 1, H370; 3 - < 10 %: STOT SE 2, H371;	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: fresh air. Make victim drink ethanol (e.g. 1 drinking glass of a 40% alcoholic beverage). Call a doctor immediately (mention methanol ingestion). Only in exceptional cases, if no medical care is available within one hour, induce vomiting (only in fully conscious persons) and make victim drink ethanol again (approx. 0.3 ml of a 40% alcoholic beverage/kg body weight/hour).

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed No data available

Millipore - MX0485

Page 3 of 14



SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water Foam Carbon dioxide (CO2) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides Combustible. Pay attention to flashback. Vapors are heavier than air and may spread along floors. Development of hazardous combustion gases or vapours possible in the event of fire. Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions Do not let product enter drains. Risk of explosion.

- **6.3 Methods and materials for containment and cleaning up** Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.
- **6.4 Reference to other sections** For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Millipore - MX0485

Page 4 of 14



Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons.

Recommended storage temperature see product label.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Ingreatents with				
Component	CAS-No.	Value	Control parameters	Basis
Methanol	67-56-1	TWA	200 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Danger of o	cutaneous absor	ption
		STEL	250 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Danger of o	cutaneous absor	ption
		ST	250 ppm	USA. NIOSH Recommended
			325 mg/m3	Exposure Limits
		Potential for dermal absorption		tion
		TWA	200 ppm	USA. NIOSH Recommended
			260 mg/m3	Exposure Limits
		Potential for	or dermal absorp	tion
		TWA	200 ppm 260 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		PEL	200 ppm 260 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		Skin		

Millipore - MX0485

Page 5 of 14



C	1,000 ppm	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
Skin		
STEL	250 ppm 325 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
Skin	•	

Biological occupational exposure limits

Diviogical occi	biological occupational exposure mints					
Component	CAS-No.	Parameters	Value	Biological specimen	Basis	
Methanol	67-56-1	Methanol	15 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)	
	Remarks	End of shift ('As soon as	s possible after ex	(posure ceases)	

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact Material: butyl-rubber Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested:Butoject® (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Splash contact Material: Viton® Minimum layer thickness: 0.7 mm Break through time: 120 min Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Millipore - MX0485

Page 6 of 14



Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

Recommended Filter type: Filter type AX

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a)	Appearance	Form: liquid Color: colorless
b)	Odor	characteristic
c)	Odor Threshold	10 ppm
d)	рН	No data available
e)	Melting point/freezing point	Melting point: -97.8 °C (-144.0 °F) - (ECHA)
f)	Initial boiling point and boiling range	64.7 °C 148.5 °F at 1,013 hPa - (ECHA)
g)	Flash point	9.7 °C (49.5 °F) - closed cup - Regulation (EC) No. 440/2008, Annex, A.9
h)	Evaporation rate	6.3 - Diethyl ether1.9 - n-butyl acetate
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	Upper explosion limit: 44 %(V) Lower explosion limit: 5.5 %(V)
k)	Vapor pressure	169.27 hPa at 25 °C (77 °F)
I)	Vapor density	1.11
m)	Density	0.79 g/cm3 at 20 °C (68 °F)
	Relative density	0.79 - 0.820 °C
n)	Water solubility	1,000 g/l at 20 °C (68 °F) - completely miscible
0)	Partition coefficient: n-octanol/water	log Pow: -0.77 at 25 °C (77 °F) - (HSDB), Bioaccumulation is not expected.

Millipore - MX0485

Page 7 of 14



p)	Autoignition temperature	455.0 °C (851.0 °	F) at 1,013	hPa - DIN 5179	4

- q) Decomposition Distillable in an undecomposed state at normal pressure.
 temperature
- r) Viscosity 0.54 0.59 mm2/s at 20 °C (68 °F) -
- s) Explosive properties No data available
- t) Oxidizing properties none

9.2 Other safety information

Minimum ignition	0.14 mJ
energy	
Conductivity	< 1 µS/cm
Relative vapor density	1.11

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Risk of explosion with: Oxidizing agents perchloric acid perchlorates salts of oxyhalogenic acids chromium(VI) oxide halogen oxides nitrogen oxides nonmetallic oxides chromosulfuric acid chlorates hydrides zinc diethyl halogens powdered magnesium hydrogen peroxide Nitric acid sulfuric acid permanganic acid sodium hypochlorite Exothermic reaction with: acid halides Acid anhydrides

Millipore - MX0485

Page 8 of 14



Reducing agents acids Bromine Chlorine Chloroform magnesium tetrachloromethane Risk of ignition or formation of inflammable gases or vapours with: Fluorine Oxides of phosphorus Raney-nickel Generates dangerous gases or fumes in contact with: Alkaline earth metals Alkali metals

10.4 Conditions to avoid

Warming.

10.5 Incompatible materials No data available

10.6 Hazardous decomposition products In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute toxicity estimate Oral - 100.1 mg/kg (Expert judgment) Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2) Symptoms: Nausea, Vomiting Acute toxicity estimate Inhalation - 4 h - 3.1 mg/l - vapor

(Expert judgment) Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2) Symptoms: Irritation symptoms in the respiratory tract. Acute toxicity estimate Dermal - 300.1 mg/kg (Expert judgment) Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Skin corrosion/irritation

Skin - Rabbit Result: No skin irritation Remarks: (ECHA) Remarks: Drying-out effect resulting in rough and chapped skin.

Serious eye damage/eye irritation

Eyes - Rabbit Result: No eye irritation Remarks: (ECHA)

Millipore - MX0485

Page 9 of 14



Respiratory or skin sensitization

Sensitisation test: - Guinea pig Result: negative (OECD Test Guideline 406)

Germ cell mutagenicity

Based on available data the classification criteria are not met. Test Type: Ames test Test system: Salmonella typhimurium Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471 Result: negative Test Type: In vitro mammalian cell gene mutation test Test system: Chinese hamster lung cells Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 476 Result: negative

Test Type: Micronucleus test Species: Mouse Cell type: Bone marrow Application Route: Intraperitoneal injection Method: OECD Test Guideline 474 Result: negative

Carcinogenicity

Did not show carcinogenic effects in animal experiments.

- IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

Causes damage to organs. - Eyes, Central nervous system Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Specific target organ toxicity - repeated exposure No data available

Aspiration hazard No data available

11.2 Additional Information

Acute effects:, Headache, Dizziness, Drowsiness, narcosis, Blindness, Impairment of vision, irritant effects, Nausea, Vomiting, agitation, spasms, inebriation, Coma Drying-out effect resulting in rough and chapped skin. To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Millipore - MX0485

Page 10 of 14



Systemic effects:

acidosis drop in blood pressure agitation, spasms inebriation Dizziness Drowsiness Headache Impairment of vision Blindness narcosis Coma

Symptoms may be delayed.

Damage to:

Liver Kidney Cardiac Irreversible damage of the optical nerve.

Other dangerous properties can not be excluded.

This substance should be handled with particular care.

Stomach - Irregularities - Based on Human Evidence

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish	flow-through test LC50 - Lepomis macrochirus (Bluegill) - 15,400.0 mg/l - 96 h (US-EPA)
Toxicity to daphnia and other aquatic invertebrates	semi-static test EC50 - Daphnia magna (Water flea) - 18,260 mg/l - 96 h (OECD Test Guideline 202)
Toxicity to algae	static test ErC50 - Pseudokirchneriella subcapitata (green algae) - ca. 22,000.0 mg/l - 96 h (OECD Test Guideline 201)
Toxicity to bacteria	static test IC50 - activated sludge - > 1,000 mg/l - 3 h (OECD Test Guideline 209)
Toxicity to fish(Chronic toxicity)	NOEC - Oryzias latipes (Orange-red killifish) - 7,900 mg/l - 200 h Remarks: (External MSDS)

Millipore - MX0485

Page 11 of 14



12.2 Persistence and degradability

Biodegradability	Result: 99 % - Readily biodegradable. (OECD Test Guideline 301D)
Biochemical Oxygen	600 - 1,120 mg/g
Demand (BOD)	Remarks: (IUCLID)
Chemical Oxygen	1,420 mg/g
Demand (COD)	Remarks: (IUCLID)
Theoretical oxygen	1,500 mg/g
demand	Remarks: (Lit.)
Ratio BOD/ThBOD	76 % Remarks: Closed Bottle test(IUCLID)

12.3 Bioaccumulative potential

Bioaccumulation Cyprinus carpio (Carp) - 72 d at 20 °C - 5 mg/l(Methanol)

Bioconcentration factor (BCF): 1.0

12.4 Mobility in soil

Will not adsorb on soil.

12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted 12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Additional ecological information	Avoid release to the environment.
Stability in water	at 19 °C83 - 91 % - 72 h Remarks: Hydrolyzes on contact with wa

Remarks: Hydrolyzes on contact with water.Hydrolyzes readily. - 2.2 yr Remarks: reaction with hydroxyl radicals(IUCLID)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

Millipore - MX0485

Page 12 of 14



SECTION 14: Transport information				
DOT (US) UN number: 1230 Class: 3 Proper shipping name: Methanol Reportable Quantity (RQ): 5000 lbs Poison Inhalation Hazard: No	Packing group: II			
IMDG UN number: 1230 Class: 3 (6.1) Proper shipping name: METHANOL	Packing group: II	EMS-No: F-E, S-D		
IATA UN number: 1230 Class: 3 (6.1) Proper shipping name: Methanol	Packing group: II			

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

Methanol	CAS-No. 67-56-1	Revision Date 2007-07-01
Massachusetts Right To Know Components	CAS-No.	Revision Date
Methanol	67-56-1	2007-07-01
Pennsylvania Right To Know Components	CAS-No.	Revision Date
Methanol	67-56-1	2007-07-01
California Prop. 65 Components , which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.Methanol	CAS-No. 67-56-1	Revision Date 2012-03-16

SECTION 16: Other information

Further information

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture Millipore - MX0485

Page 13 of 14



and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com. Version: 8.15 Revision Date: 03/02/2024 Print Date: 06/15/2024

Millipore - MX0485

Page 14 of 14

