

Material Safety Data Sheet

Version 3.0
Revision Date 07/13/2007
Print Date 07/28/2010

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : **Diisopropylamine**

Product Number : D3022
Brand : Sigma

Company : Sigma-Aldrich
3050 Spruce Street
SAINT LOUIS MO 63103
USA

Telephone : +18003255832
Fax : +18003255052
Emergency Phone # : (314) 776-6555

2. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms : DIPA

Formula : C₆H₁₅N
Molecular Weight : 101.19 g/mol

CAS-No.	EC-No.	Index-No.	Concentration [%]
Diisopropylamine			
108-18-9	203-558-5	612-129-00-5	-

3. HAZARDS IDENTIFICATION**Emergency Overview****OSHA Hazards**

Flammable Liquid
Delayed target organ effects
Corrosive

Target Organs

Eyes

HMIS Classification

Health Hazard: 3
Chronic Health Hazard: *
Flammability: 3
Physical hazards: 0

NFPA Rating

Health Hazard: 3
Fire : 3
Reactivity Hazard: 0

Potential Health Effects

Inhalation	May be harmful if inhaled. May cause respiratory tract irritation. Material is extremely destructive to the tissue of the mucous membranes and upper respiratory tract.
Skin	May be harmful if absorbed through skin. Causes skin burns.
Eyes	May cause eye irritation. Causes eye burns.
Ingestion	May be harmful if swallowed. Causes burns.

4. FIRST AID MEASURES

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing give artificial respiration. Consult a physician.

In case of skin contact

Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Continue rinsing eyes during transport to hospital. Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

5. FIRE-FIGHTING MEASURES

Flammable properties

Flash point -17 °C (1 °F) - closed cup

Ignition temperature 315 °C (599 °F)

Suitable extinguishing media

For small (incipient) fires, use media such as "alcohol" foam, dry chemical, or carbon dioxide. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.

Specific hazards

Flash back possible over considerable distance. Container explosion may occur under fire conditions.

Special protective equipment for fire-fighters

Wear self contained breathing apparatus for fire fighting if necessary.

Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Methods for cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

7. HANDLING AND STORAGE

Handling

Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

Storage

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in cool place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters	Update	Basis
Diisopropylamine	108-18-9	TWA	5 ppm 21 mg/m ³	1994-09-01	US. American Conference of Governmental and Industrial Hygienists Threshold Limit Values for Chemical Substances in the Work Environment; Annual Reports for the Year 2004: Committees on Threshold Limit Values (TLVs) and Biological Exposure Indices (BEIs)
		TWA	5 ppm 20 mg/m ³	1989-03-01	US. Department of Labor - Occupational Safety and Health Administration (OSHA) 29 CFR 1910.1000 Z-1-A
		TWA	5 ppm 20 mg/m ³	1993-06-30	US. Department of Labor - Occupational Safety and Health Administration (OSHA) Permissible Exposure Limits (PEL) 29 CFR 1910.1000 Air Contaminants.

Personal protective equipment

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection

Handle with gloves.

Eye protection

Safety glasses

Skin and body protection

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form	liquid, clear
Colour	colourless

Safety data

pH	no data available
Melting point	-61 °C (-78 °F)
Boiling point	83 - 84 °C (181 - 183 °F)
Flash point	-17 °C (1 °F) - closed cup
Ignition temperature	315 °C (599 °F)
Lower explosion limit	1.1 %(V)
Upper explosion limit	8.5 %(V)
Vapour pressure	67 hPa (50 mmHg) at 20 °C (68 °F)
Density	0.716 g/cm ³
Water solubility	no data available
Vapour density	3.49 - (Air = 1.0)

10. STABILITY AND REACTIVITY

Storage stability

Stable under recommended storage conditions.

Conditions to avoid

Heat, flames and sparks.

Materials to avoid

Strong acids, Strong bases, Strong oxidizing agents, Plastics

Hazardous decomposition products

Hazardous decomposition products formed under fire conditions.

Carbon oxides, nitrogen oxides (NO_x)

Hazardous reactions

Vapours may form explosive mixture with air.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

LD50 Oral - rat - 770 mg/kg

LC50 Inhalation - rat - 2 h - 4,800 mg/m³

LD50 Dermal - rabbit - > 10,000 mg/kg

Irritation and corrosion

no data available

Sensitisation

no data available

Chronic exposure

no data available

Potential Health Effects

Inhalation	May be harmful if inhaled. May cause respiratory tract irritation. Material is extremely destructive to the tissue of the mucous membranes and upper respiratory tract.
Skin	May be harmful if absorbed through skin. Causes skin burns.
Eyes	May cause eye irritation. Causes eye burns.
Ingestion	May be harmful if swallowed. Causes burns.
Target Organs	Eyes,

12. ECOLOGICAL INFORMATION

Elimination information (persistence and degradability)

no data available

Ecotoxicity effects

Toxicity to fish	LC50 - Oncorhynchus mykiss (rainbow trout) - 37 mg/l - 96 h
Toxicity to daphnia and other aquatic invertebrates.	LC50 - Daphnia magna (Water flea) - 448 mg/l - 48 h
Toxicity to algae	Growth inhibition EC50 - Scenedesmus pannonicus - 490 mg/l - 14 d Growth inhibition EC50 - Scenedesmus pannonicus - 170 mg/l - 96 h

Further information on ecology

no data available

13. DISPOSAL CONSIDERATIONS

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Observe all federal, state, and local environmental regulations. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN-Number: 1158 Class: 3 (8) Packing group: II
Proper shipping name: Diisopropylamine

IMDG

UN-Number: 1158 Class: 3 (8) Packing group: II EMS-No: F-E, S-C
Proper shipping name: DIISOPROPYLAMINE
Marine pollutant: No

IATA

UN-Number: 1158 Class: 3 (8) Packing group: II
Proper shipping name: Diisopropylamine

15. REGULATORY INFORMATION

OSHA Hazards

Flammable Liquid, Delayed target organ effects, Corrosive

TSCA Status

On TSCA Inventory

DSL Status

All components of this product are on the Canadian DSL list.

SARA 302 Components

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

	CAS-No.	Revision Date
Diisopropylamine	108-18-9	1989-12-01

Pennsylvania Right To Know Components

	CAS-No.	Revision Date
Diisopropylamine	108-18-9	1989-12-01

New Jersey Right To Know Components

	CAS-No.	Revision Date
Diisopropylamine	108-18-9	1989-12-01

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects.

16. OTHER INFORMATION**Further information**

Copyright 2007 Sigma-Aldrich Co. License granted to make unlimited paper copies for internal use only., The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Co., shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale.