

SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Revision Date 06/05/2018

Version 1.1

SECTION 1. Identification**Product identifier**

Product number	AX0612
Product name	Alumina 80-200 Mesh Chromatographic Grade Material must be activated before use.
CAS-No.	1344-28-1

Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Reagent for analysis
-----------------	----------------------

Details of the supplier of the safety data sheet

Company	EMD Millipore Corporation 400 Summit Drive Burlington Massachusetts 01803 United States of America General Inquiries: +1 800-645-5476 Monday to Friday, 9:00 AM to 4:00 PM Eastern Time (GMT-5) MilliporeSigma is a business of Merck KGaA, Darmstadt, Germany.
---------	---

Emergency telephone	800-424-9300 CHEMTREC (USA) +1-703-527-3887 CHEMTREC (International) 24 Hours/day; 7 Days/week
---------------------	--

SECTION 2. Hazards identification**GHS-Labeling**

Not a dangerous substance according to GHS.

Other hazards

None known.

SECTION 3. Composition/information on ingredients

Formula	Al ₂ O ₃ (Hill)
Molar mass	101.96 g/mol

Hazardous ingredients*Chemical name (Concentration)*

CAS-No.

Aluminium oxide (>= 90 % - <= 100 %)

1344-28-1

Exact percentages are being withheld as a trade secret.

SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number

AX0612

Version 1.1

Product name

Alumina 80-200 Mesh Chromatographic Grade
Material must be
activated before use.

SECTION 4. First aid measures

Description of first-aid measures

Inhalation

After inhalation: fresh air.

Skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/shower.

Eye contact

After eye contact: rinse out with plenty of water. Remove contact lenses.

Ingestion

After swallowing: make victim drink water (two glasses at most). Consult doctor if feeling unwell.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

We have no description of any toxic symptoms.

Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

Special hazards arising from the substance or mixture

Not combustible.

Ambient fire may liberate hazardous vapors.

Advice for firefighters

Special protective equipment for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Further information

none

SECTION 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid inhalation of dusts. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders:

Protective equipment see section 8.

SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number

AX0612

Version 1.1

Product name

Alumina 80-200 Mesh Chromatographic Grade
Material must be
activated before use.

Environmental precautions

No special precautionary measures necessary.

Methods and materials for containment and cleaning up

Observe possible material restrictions (see sections 7 and 10). Take up dry. Dispose of properly.

Clean up affected area. Avoid generation of dusts.

SECTION 7. Handling and storage

Precautions for safe handling

Observe label precautions.

Conditions for safe storage, including any incompatibilities

Tightly closed. Dry.

Store at room temperature.

SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number

AX0612

Version 1.1

Product name

Alumina 80-200 Mesh Chromatographic Grade
Material must be

activated before use.**SECTION 8. Exposure controls/personal protection****Exposure limit(s)***Ingredients*

Basis	Value	Threshold limits	Remarks
<i>General threshold limit value for dust</i>			
Z1A	Time Weighted Average (TWA):	5 mg/m ³	Form of exposure: Respirable fraction.
	Time Weighted Average (TWA):	15 mg/m ³	Form of exposure: Total dust.
	Time Weighted Average (TWA):	50millions of particles per cubic foot of air	Form of exposure: Total dust.
	Time Weighted Average (TWA):	15millions of particles per cubic foot of air	Form of exposure: Respirable fraction.
	Time Weighted Average (TWA):	15 mg/m ³	Form of exposure: Total dust.
ACGIH	Time Weighted Average (TWA):	5 mg/m ³	Form of exposure: Respirable fraction.
	Time Weighted Average (TWA):	10 mg/m ³	Form of exposure: Inhalable particles.
	Time Weighted Average (TWA):	3 mg/m ³	Form of exposure: Respirable particles.
<i>Aluminium oxide 1344-28-1</i>			
ACGIH	Time Weighted Average (TWA):	1 mg/m ³	Form of exposure: Respirable fraction.
OSHA_TRANS	PEL:	5 mg/m ³	Form of exposure: Respirable fraction.
	PEL:	15 mg/m ³	Form of exposure: Total dust.
Z1A	Time Weighted Average (TWA):	10 mg/m ³	Form of exposure: Total dust.
	Time Weighted Average (TWA):	5 mg/m ³	Form of exposure: Respirable fraction.
	Time Weighted Average (TWA):	15 mg/m ³	Form of exposure: Total dust.
	Time Weighted Average (TWA):	50millions of particles per cubic foot of air	Form of exposure: Total dust.
	Time Weighted Average (TWA):	15millions of particles per cubic foot of air	Form of exposure: Respirable fraction.
	Time Weighted Average (TWA):	5 mg/m ³	Form of exposure: Respirable fraction.

Engineering measures

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number

AX0612

Version 1.1

Product name

Alumina 80-200 Mesh Chromatographic Grade
Material must be
activated before use.

Individual protection measures

Protective clothing should be selected specifically for the workplace, depending on concentration and quantity of the hazardous substances handled. The chemical resistance of the protective equipment should be inquired at the respective supplier.

Hygiene measures

Change contaminated clothing. Wash hands after working with substance.

Eye/face protection

Safety glasses

Hand protection

full contact:

Glove material:	Nitrile rubber
Glove thickness:	0.11 mm
Break through time:	480 min

splash contact:

Glove material:	Nitrile rubber
Glove thickness:	0.11 mm
Break through time:	480 min

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374, for example KCL 741 Dermatril® L (full contact), KCL 741 Dermatril® L (splash contact).

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types.

This recommendation applies only to the product stated in the safety data sheet and supplied by us as well as to the purpose specified by us. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Respiratory protection

required when dusts are generated.

Recommended Filter type: Filter P 1 (acc. to DIN 3181) for solid particles of inert substances

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are performed according to the instructions of the producer. These measures have to be properly documented.

SECTION 9. Physical and chemical properties

Physical state	solid
Color	white
Odor	odorless
Odor Threshold	Not applicable
pH	No information available.
Melting point	3,722 °F (2,050 °C)

SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number

AX0612

Version 1.1

Product name

Alumina 80-200 Mesh Chromatographic Grade
Material must be
activated before use.

Boiling point/boiling range	5,396 °F (2,980 °C) at 1,013 hPa
Flash point	Not applicable
Evaporation rate	No information available.
Flammability (solid, gas)	The product is not flammable.
Lower explosion limit	Not applicable
Upper explosion limit	Not applicable
Vapor pressure	at 68 °F (20 °C) Not applicable
Relative vapor density	No information available.
Density	3.94 g/cm ³ at 68 °F (20 °C)
Relative density	No information available.
Water solubility	at 68 °F (20 °C) insoluble
Partition coefficient: n-octanol/water	No information available.
Autoignition temperature	No information available.
Decomposition temperature	No information available.
Viscosity, dynamic	No information available.
Explosive properties	Not classified as explosive.
Oxidizing properties	none
Ignition temperature	Not applicable

SECTION 10. Stability and reactivity

Reactivity

See below

Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

Possibility of hazardous reactions

Exothermic reaction with:

SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number

AX0612

Version 1.1

Product name

Alumina 80-200 Mesh Chromatographic Grade

Material must be

activated before use.

halogen-halogen compounds, Ethylene oxide, Fluorine, Hydrogen halides, vinyl acetate

Risk of explosion with:

nitrates, halogen oxides

Conditions to avoid

no information available

Incompatible materials

no information available

Hazardous decomposition products

no information available

SECTION 11. Toxicological information

Information on toxicological effects

Likely route of exposure

Inhalation, Eye contact, Skin contact, Ingestion

Target Organs

Eyes

Skin

Respiratory system

Acute oral toxicity

LD50 Rat: > 5,000 mg/kg

OECD Test Guideline 401

Skin irritation

Rabbit

Result: No irritation

OECD Test Guideline 404

Eye irritation

Rabbit

Result: No eye irritation

OECD Test Guideline 405

Genotoxicity in vitro

Ames test

Bacillus subtilis

Result: negative

(IUCLID)

Specific target organ systemic toxicity - single exposure

The substance or mixture is not classified as specific target organ toxicant, single exposure.

Specific target organ systemic toxicity - repeated exposure

The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Aspiration hazard

Regarding the available data the classification criteria are not fulfilled.

Carcinogenicity

IARC

No ingredient of this product present at levels greater than or

SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number	AX0612	Version 1.1
Product name	Alumina 80-200 Mesh Chromatographic Grade Material must be activated before use.	

	equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
ACGIH	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

Further information

On the basis of the morphology of the product, no hazardous properties are to be expected when it is handled and used with appropriate care.

Only very slightly absorbable via the gastrointestinal tract.

Inhalation of the dusts should be avoided as even inert dusts may impair respiratory organ functions.

Handle in accordance with good industrial hygiene and safety practice.

SECTION 12. Ecological information

Ecotoxicity

No information available.

Persistence and degradability

No information available.

Bioaccumulative potential

No information available.

Mobility in soil

No information available.

Additional ecological information

No ecological problems are to be expected when the product is handled and used with due care and attention.

SECTION 13. Disposal considerations

The information presented only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. Disposal should be in accordance with applicable regional, national and local laws and regulations.

SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number

AX0612

Version 1.1

Product name

Alumina 80-200 Mesh Chromatographic Grade
Material must be

activated before use.

SECTION 14. Transport information

Land transport (DOT)

Not classified as dangerous in the meaning of transport regulations.

Air transport (IATA)

Not classified as dangerous in the meaning of transport regulations.

Sea transport (IMDG)

Not classified as dangerous in the meaning of transport regulations.

SECTION 15. Regulatory information

United States of America

SARA 313

The following components are subject to reporting levels established by SARA Title III, Section 313:

Ingredients

Aluminium oxide

1344-28-1

100 %

SARA 302

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

DEA List I

Not listed

DEA List II

Not listed

US State Regulations

Massachusetts Right To Know

Ingredients

Aluminium oxide

Pennsylvania Right To Know

Ingredients

Aluminium oxide

New Jersey Right To Know

Ingredients

SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number	AX0612	Version 1.1
Product name	Alumina 80-200 Mesh Chromatographic Grade Material must be activated before use.	

Aluminium oxide

California Prop 65 Components

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

Notification status

TSCA: All components of the product are listed in the TSCA-inventory.

DSL: All components of this product are on the Canadian DSL

SECTION 16. Other information

Training advice

Provide adequate information, instruction and training for operators.

Key or legend to abbreviations and acronyms used in the safety data sheet

Used abbreviations and acronyms can be looked up at www.wikipedia.org.

Revision Date 06/05/2018

The information contained herein is based on the present state of our knowledge. It characterizes the product with regard to appropriate safety precautions. It does not represent a warranty of any product properties and we assume no liability for any loss or injury which may result from the use of this information. Users should conduct their own investigations to determine the suitability of the information.

All rights reserved. Millipore and the "M" Mark are registered trademarks of Merck KGaA, Darmstadt, Germany.