

PRODUCT

# 460-S0275 SOLN H-2 Total Hardness Buffer, Form Liquid

EMERGENCY TELEPHONE NUMBER(S) (800) 424-9300 (24 Hours) CHEMTREC

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME :

460-S0275 SOLN H-2 Total Hardness Buffer, Form Liquid

APPLICATION :

REAGENT

COMPANY IDENTIFICATION :

Nalco Company 1601 W. Diehl Road Naperville, Illinois 60563-1198

EMERGENCY TELEPHONE NUMBER(S): (800) 424-9300 (24 Hours) CHEMTREC

NFPA 704M/HMIS RATING

HEALTH: 2/2 FLAMMABILITY: 1/1 INSTABILITY: 0/0 OTHER: 0 =Insignificant 1 =Slight 2 =Moderate 3 =High 4 =Extreme

# 2. COMPOSITION/INFORMATION ON INGREDIENTS

Our hazard evaluation has identified the following chemical substance(s) as hazardous. Consult Section 15 for the nature of the hazard(s).

Hazardous Substance(s)	CAS NO	% (w/w)
9	141-43-5	20.0 - 40.0

# 3. HAZARDS IDENTIFICATION

## \*\*EMERGENCY OVERVIEW\*\*

## WARNING

Irritating to eyes and skin.

Monoethanolamine

Do not get in eyes, on skin, on clothing. Do not take internally. Keep container tightly closed. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water.

Wear suitable protective clothing, gloves and eye/face protection.

May evolve oxides of carbon (COx) under fire conditions. May evolve oxides of nitrogen (NOx) under fire conditions.

PRIMARY ROUTES OF EXPOSURE : Eye, Skin, Inhalation

HUMAN HEALTH HAZARDS - ACUTE :

EYE CONTACT : Can cause moderate to severe irritation.

SKIN CONTACT : Can cause moderate to severe irritation.



PRODUCT

# 460-S0275 SOLN H-2 Total Hardness **Buffer, Form Liquid**

**EMERGENCY TELEPHONE NUMBER(S)** (800) 424-9300 (24 Hours) CHEMTREC

**INGESTION:** 

Not a likely route of exposure. No adverse effects expected.

INHALATION : Can cause severe irritation.

SYMPTOMS OF EXPOSURE :

Acute :

A review of available data does not identify any symptoms from exposure not previously mentioned. Chronic:

A review of available data does not identify any symptoms from exposure not previously mentioned.

#### AGGRAVATION OF EXISTING CONDITIONS :

A review of available data does not identify any worsening of existing conditions.

#### FIRST AID MEASURES 4.

#### EYE CONTACT :

Immediately flush eye with water for at least 15 minutes while holding eyelids open. If irritation persists, repeat flushing. Get immediate medical attention.

**SKIN CONTACT :** 

Immediately flush with plenty of water for at least 15 minutes. If symptoms persist, call a physician.

**INGESTION:** 

Do not induce vomiting without medical advice. If conscious, washout mouth and give water to drink. Get medical attention.

INHALATION : Remove to fresh air, treat symptomatically. Get medical attention.

NOTE TO PHYSICIAN :

Based on the individual reactions of the patient, the physician's judgement should be used to control symptoms and clinical condition.

#### 5. FIRE FIGHTING MEASURES

FLASH POINT :

Minimum 200 °F / 93.3 °C ( PMCC )

**EXTINGUISHING MEDIA:** 

Use extinguishing media appropriate for surrounding fire.

FIRE AND EXPLOSION HAZARD :

May evolve oxides of carbon (COx) under fire conditions. May evolve oxides of nitrogen (NOx) under fire conditions.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE FIGHTING :

In case of fire, wear a full face positive-pressure self contained breathing apparatus and protective suit.



PRODUCT

# 460-S0275 SOLN H-2 Total Hardness Buffer, Form Liquid

EMERGENCY TELEPHONE NUMBER(S) (800) 424-9300 (24 Hours) CHEMTREC

## 6. ACCIDENTAL RELEASE MEASURES

#### **PERSONAL PRECAUTIONS:**

Restrict access to area as appropriate until clean-up operations are complete. Ensure clean-up is conducted by trained personnel only. Ventilate spill area if possible. Do not touch spilled material. Stop or reduce any leaks if it is safe to do so. Use personal protective equipment recommended in Section 8 (Exposure Controls/Personal Protection). Notify appropriate government, occupational health and safety and environmental authorities.

#### METHODS FOR CLEANING UP :

SMALL SPILLS: Soak up spill with absorbent material. Place residues in a suitable, covered, properly labeled container. Wash affected area. Dispose of material in compliance with regulations indicated in Section 13 (Disposal Considerations).

#### **ENVIRONMENTAL PRECAUTIONS :**

Do not contaminate surface water.

# 7. HANDLING AND STORAGE

#### HANDLING :

Avoid eye and skin contact. Do not take internally. Do not get in eyes, on skin, on clothing. Have emergency equipment (for fires, spills, leaks, etc.) readily available. Ensure all containers are labelled. Keep the containers closed when not in use. Use with adequate ventilation.

#### STORAGE CONDITIONS :

Store the containers tightly closed. Store in suitable labelled containers.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### OCCUPATIONAL EXPOSURE LIMITS :

Exposure guidelines have not been established for this product. Available exposure limits for the substance(s) are shown below.

ACGIH/TLV : Substance(s) Monoethanolamine

TWA: 3 ppm , 7.5 mg/m3 STEL: 6 ppm , 15 mg/m3

OSHA/PEL : Substance(s) Monoethanolamine

TWA: 3 ppm , 8 mg/m3 STEL: 6 ppm , 15 mg/m3

ENGINEERING MEASURES : General ventilation is recommended.



PRODUCT

# 460-S0275 SOLN H-2 Total Hardness Buffer, Form Liquid

EMERGENCY TELEPHONE NUMBER(S) (800) 424-9300 (24 Hours) CHEMTREC

RESPIRATORY PROTECTION : Respiratory protection is not normally needed.

HAND PROTECTION : Neoprene gloves, Nitrile gloves, Butyl gloves, PVC gloves

SKIN PROTECTION : Wear standard protective clothing.

EYE PROTECTION : Wear chemical splash goggles.

#### HYGIENE RECOMMENDATIONS :

If clothing is contaminated, remove clothing and thoroughly wash the affected area. Launder contaminated clothing before reuse. Keep an eye wash fountain available. Keep a safety shower available.

#### HUMAN EXPOSURE CHARACTERIZATION :

Based on our recommended product application and personal protective equipment, the potential human exposure is: Low

## 9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE Liquid

APPEARANCE Colorless

ODOR Slight, Amine

SPECIFIC GRAVITY	0.95
DENSITY	7.89 lb/gal
SOLUBILITY IN WATER	Complete
pH (100 %)	10
VAPOR PRESSURE	Same as water

Note: These physical properties are typical values for this product and are subject to change.

## 10. STABILITY AND REACTIVITY

STABILITY : Stable under normal conditions.

HAZARDOUS POLYMERIZATION : Hazardous polymerization will not occur.

CONDITIONS TO AVOID : Freezing temperatures.



PRODUCT

# 460-S0275 SOLN H-2 Total Hardness Buffer, Form Liquid

EMERGENCY TELEPHONE NUMBER(S) (800) 424-9300 (24 Hours) CHEMTREC

#### MATERIALS TO AVOID :

Certain amines in contact with nitrous acid, organic or inorganic nitrites or atmospheres with high nitrous oxide concentrations may produce N-nitrosamines, many of which are cancer-causing agents to laboratory animals. Contact with strong oxidizers (e.g. chlorine, peroxides, chromates, nitric acid, perchlorate, concentrated oxygen, permanganate) may generate heat, fires, explosions and/or toxic vapors.

HAZARDOUS DECOMPOSITION PRODUCTS :

Under fire conditions: Oxides of carbon, Oxides of nitrogen

## 11. TOXICOLOGICAL INFORMATION

The following results are for the hazardous components.

ACUTE ORAL TOXICITY : Species LD50 Rat 2,100 mg/kg Rating : Non-Hazardous

Test Descriptor Monoethanolamine

SENSITIZATION : This product is not expected to be a sensitizer.

#### CARCINOGENICITY :

None of the substances in this product are listed as carcinogens by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP) or the American Conference of Governmental Industrial Hygienists (ACGIH).

#### HUMAN HAZARD CHARACTERIZATION :

Based on our hazard characterization, the potential human hazard is: Moderate

## 12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL EFFECTS :

No toxicity studies have been conducted on this product.

ENVIRONMENTAL HAZARD AND EXPOSURE CHARACTERIZATION

Based on our hazard characterization, the potential environmental hazard is: Low Based on our recommended product application and the product's characteristics, the potential environmental exposure is: Low

If released into the environment, see CERCLA/SUPERFUND in Section 15.

#### 13. DISPOSAL CONSIDERATIONS

If this product becomes a waste, it is not a hazardous waste as defined by the Resource Conservation and Recovery Act (RCRA) 40 CFR 261, since it does not have the characteristics of Subpart C, nor is it listed under Subpart D.



PRODUCT

# 460-S0275 SOLN H-2 Total Hardness Buffer, Form Liquid EMERGENCY TELEPHONE NUMBER(S)

(800) 424-9300 (24 Hours) CHEMTREC

As a non-hazardous waste, it is not subject to federal regulation. Consult state or local regulation for any additional handling, treatment or disposal requirements. For disposal, contact a properly licensed waste treatment, storage, disposal or recycling facility.

## 14. TRANSPORT INFORMATION

The information in this section is for reference only and should not take the place of a shipping paper (bill of lading) specific to an order. Please note that the proper Shipping Name / Hazard Class may vary by packaging, properties, and mode of transportation. Typical Proper Shipping Names for this product are as follows.

LAND TRANSPORT :

	Proper Shipping Name : Technical Name(s) : UN/ID No : Hazard Class - Primary : Packing Group :	ETHANOLAMINE SOLUTION UN 2491 8 III		
	Flash Point :	Minimum 93.3 °C / 200 °F		
AIR TRANSPORT (ICAO/IATA) :				
	Proper Shipping Name : Technical Name(s) : UN/ID No : Hazard Class - Primary : Packing Group : IATA Cargo Packing Instructions : IATA Cargo Aircraft Limit :	ETHANOLAMINE SOLUTION UN 2491 8 III 820 60 L (Max net quantity per package)		
MARINE TRANSPORT (IMDG/IMO) :				
	Proper Shipping Name : Technical Name(s) : UN/ID No : Hazard Class - Primary : Packing Group :	ETHANOLAMINE SOLUTION UN 2491 8 III		

## 15. REGULATORY INFORMATION

NATIONAL REGULATIONS, USA :

OSHA HAZARD COMMUNICATION RULE, 29 CFR 1910.1200 : Based on our hazard evaluation, the following substance(s) in this product is/are hazardous and the reason(s) is/are shown below.

Monoethanolamine : Corrosive, Combustible.



PRODUCT

# 460-S0275 SOLN H-2 Total Hardness Buffer, Form Liquid

EMERGENCY TELEPHONE NUMBER(S) (800) 424-9300 (24 Hours) CHEMTREC

CERCLA/SUPERFUND, 40 CFR 117, 302 :

Notification of spills of this product is not required.

SARA/SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (TITLE III) - SECTIONS 302, 311, 312, AND 313 :

SECTION 302 - EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355) : This product does not contain substances listed in Appendix A and B as an Extremely Hazardous Substance.

SECTIONS 311 AND 312 - MATERIAL SAFETY DATA SHEET REQUIREMENTS (40 CFR 370) : Our hazard evaluation has found this product to be hazardous. The product should be reported under the following indicated EPA hazard categories:

- X Immediate (Acute) Health Hazard
- Delayed (Chronic) Health Hazard
- Fire Hazard
- Sudden Release of Pressure Hazard
- Reactive Hazard

Under SARA 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are: 500 pounds or the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

SECTION 313 - LIST OF TOXIC CHEMICALS (40 CFR 372) : This product does not contain substances on the List of Toxic Chemicals.

#### TOXIC SUBSTANCES CONTROL ACT (TSCA) :

The substances in this preparation are included on or exempted from the TSCA 8(b) Inventory (40 CFR 710)

FEDERAL WATER POLLUTION CONTROL ACT, CLEAN WATER ACT, 40 CFR 401.15 / formerly Sec. 307, 40 CFR 116.4 / formerly Sec. 311 :

None of the substances are specifically listed in the regulation.

CLEAN AIR ACT, Sec. 111 (40 CFR 60, Volatile Organic Compounds), Sec. 112 (40 CFR 61, Hazardous Air Pollutants), Sec. 602 (40 CFR 82, Class I and II Ozone Depleting Substances) : This product contains the following substances listed in the regulation:

Substance(s) Citations	
Monoethanolamine Sec. 111	

#### CALIFORNIA PROPOSITION 65 :

This product does not contain substances which require warning under California Proposition 65.

#### MICHIGAN CRITICAL MATERIALS :

None of the substances are specifically listed in the regulation.



PRODUCT

# 460-S0275 SOLN H-2 Total Hardness Buffer, Form Liquid

EMERGENCY TELEPHONE NUMBER(S) (800) 424-9300 (24 Hours) CHEMTREC

#### STATE RIGHT TO KNOW LAWS :

The following substances are disclosed for compliance with State Right to Know Laws:

Monoethanolamine 141-43-5

NATIONAL REGULATIONS, CANADA :

WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS) : This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS CLASSIFICATION :

E - Corrosive Material

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) : The substances in this preparation are listed on the Domestic Substances List (DSL), are exempt, or have been reported in accordance with the New Substances Notification Regulations.

## 16. OTHER INFORMATION

Due to our commitment to Product Stewardship, we have evaluated the human and environmental hazards and exposures of this product. Based on our recommended use of this product, we have characterized the product's general risk. This information should provide assistance for your own risk management practices. We have evaluated our product's risk as follows:

- \* The human risk is: Low
- \* The environmental risk is: Low

Any use inconsistent with our recommendations may affect the risk characterization. Our sales representative will assist you to determine if your product application is consistent with our recommendations. Together we can implement an appropriate risk management process.

This product material safety data sheet provides health and safety information. The product is to be used in applications consistent with our product literature. Individuals handling this product should be informed of the recommended safety precautions and should have access to this information. For any other uses, exposures should be evaluated so that appropriate handling practices and training programs can be established to insure safe workplace operations. Please consult your local sales representative for any further information.

#### REFERENCES

Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices, American Conference of Governmental Industrial Hygienists, OH., (Ariel Insight# CD-ROM Version), Ariel Research Corp., Bethesda, MD.

Hazardous Substances Data Bank, National Library of Medicine, Bethesda, Maryland (TOMES CPS# CD-ROM Version), Micromedex, Inc., Englewood, CO.



PRODUCT

## 460-S0275 SOLN H-2 Total Hardness Buffer, Form Liquid EMERGENCY TELEPHONE NUMBER(S) (800) 424-9300 (24 Hours) CHEMTREC

IARC Monographs on the Evaluation of the Carcinogenic Risk of Chemicals to Man, Geneva: World Health Organization, International Agency for Research on Cancer.

Integrated Risk Information System, U.S. Environmental Protection Agency, Washington, D.C. (TOMES CPS# CD-ROM Version), Micromedex, Inc., Englewood, CO.

Annual Report on Carcinogens, National Toxicology Program, U.S. Department of Health and Human Services, Public Health Service.

Title 29 Code of Federal Regulations, Part 1910, Subpart Z, Toxic and Hazardous Substances, Occupational Safety and Health Administration (OSHA), (Ariel Insight# CD-ROM Version), Ariel Research Corp., Bethesda, MD.

Registry of Toxic Effects of Chemical Substances, National Institute for Occupational Safety and Health, Cincinnati, OH, (TOMES CPS# CD-ROM Version), Micromedex, Inc., Englewood, CO.

Ariel Insight# (An integrated guide to industrial chemicals covered under major regulatory and advisory programs), North American Module, Western European Module, Chemical Inventories Module and the Generics Module (Ariel Insight# CD-ROM Version), Ariel Research Corp., Bethesda, MD.

The Teratogen Information System, University of Washington, Seattle, WA (TOMES CPS# CD-ROM Version), Micromedex, Inc., Englewood, CO.

Prepared By : Product Safety Department Date issued : 02/21/2004 Version Number : 1.5