

V207501 Bostik GlideCote Revision Date 17-May-2017 Supersedes Date: 18-Sep-2015

Version 1.03

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Product Name Bostik GlideCote

Product Code V207501

Product(s) Covered See section 16 for more information

1.2. Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Recommended useLubricants, greases, release products.

Uses Advised Against No information available

1.3. Details of the Supplier of the Safety Data Sheet

Responsible Party

Bostik Inc.

11320 W. Watertown Plank Road Wauwatosa, Wisconsin 53226 USA

Phone: +1 (800) 843-0844 (Domestic Toll Free) Phone: +1 (414) 774-2250 (International)

Fax: +1 (414) 774-8075

E-mail msds@bostik-us.com

1.4. Emergency Telephone Number

Telephone: 1-800-227-0332 (Outside U.S.) 1-703-527-3887

Section 2: HAZARD IDENTIFICATION

2.1. Classification of the Substance or Mixture

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable Aerosol	Category 1

2.2. Label Elements

EMERGENCY OVERVIEW

DANGER

Hazard statements

Causes skin irritation Causes serious eye irritation May cause drowsiness or dizziness May be fatal if swallowed and enters airways Extremely flammable aerosol

V207501 Bostik GlideCote Revision Date 17-May-2017 Supersedes Date: 18-Sep-2015

Version 1.03



Appearance Aerosol

Physical State Liquid

Odor Solvent

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

Specific treatment (see first aid measures on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards Not Otherwise Classified (HNOC)

Not applicable

Unknown acute toxicity

1.29% of the mixture consists of ingredient(s) of unknown toxicity

2.3. Other Information

May be harmful in contact with skin.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable

3.2 Mixtures

Chemical Name	CAS No.	Weight-%
Acetone	67-64-1	30 - 60

V207501Revision Date17-May-2017Bostik GlideCoteSupersedes Date:18-Sep-2015

Version 1.03

Naphtha, petroleum, light alkylate	64741-66-8	7 - 13
2,2,4-Trimethylpentane	540-84-1	5 - 10
Naphtha, petroleum, hydrotreated heavy, <0.1% Benzene	64742-48-9	1 - 5

The exact percentage (concentration) of composition has been withheld as a trade secret.

Section 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

General Advice Call 911 or emergency medical service. Remove and isolate contaminated clothing and

shoes.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms

persist, call a physician.

Skin Contact In case of contact with liquefied gas, thaw frosted parts with lukewarm water.

Inhalation Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration.

Administer oxygen if breathing is difficult.

Ingestion Do NOT induce vomiting. Rinse mouth. Drink plenty of water. If symptoms persist, call a

physician. Clean mouth with water and drink afterwards plenty of water. Never give

anything by mouth to an unconscious person. Call a physician.

Self-protection of the First Aider Ensure that medical personnel are aware of the material(s) involved and take precautions to

protect themselves.

4.2. Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms No information available.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

Note to physicians Keep victim warm and quiet.

4.4. Reference to Other Sections

Reference to Other Sections Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Section 11: TOXICOLOGY INFORMATION

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media

Use extinguishing agent suitable for type of surrounding fire. Dry chemical or CO2. Water spray, fog or regular foam. Move containers from fire area if you can do it without risk. Damaged cylinders should be handled only by specialists.

Unsuitable Extinguishing Media

CAUTION: Use of water spray when fighting fire may be inefficient.

5.2. Special Hazards Arising from the Substance or Mixture

Specific Hazards Arising from the Chemical

Some may burn but none ignite readily. Ruptured cylinders may rocket.

V207501Revision Date17-May-2017Bostik GlideCoteSupersedes Date:18-Sep-2015

Version 1.03

Explosion Data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

5.3. Advice for Firefighters

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions Remove all possible sources of ignition in the surrounding area. Ensure adequate

ventilation, especially in confined areas.

Other Information Ventilate the area.

6.2. Environmental Precautions

Environmental Precautions Prevent entry into waterways, sewers, basements or confined areas. Use water spray to

reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled

material. See Section 12 for additional Ecological Information.

6.3. Methods and Material for Containment and Cleaning up

Methods for Containment If possible, turn leaking containers so that gas escapes rather than liquid. Allow substance

to evaporate.

Methods for Cleaning upDo not direct water at spill or source of leak.

6.4. Reference to other sections

Reference to Other Sections Section 7: HANDLING AND STORAGE

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Section 13: DISPOSAL CONSIDERATIONS

Section 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Advice on Safe Handling Ensure adequate ventilation, especially in confined areas. Use only in well-ventilated areas.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Pressurized

container: Do not pierce or burn, even after use.

7.2. Conditions for Safe Storage, including any Incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight.

Do not expose to temperatures exceeding 50 °C/122 °F. Recommended storage

temperature. 10 - 35 °C. Observe local regulations / instructions for storage of pressurized

containers.

Incompatible MaterialsNone known based on information supplied.

7.3. Specific End Use(s)

Other Information No information available.

V207501 Revision Date 17-May-2017
Bostik GlideCote Supersedes Date: 18-Sep-2015

Version 1.03

7.4. References to Other Sections

Reference to Other Sections Section 13: DISPOSAL CONSIDERATIONS

Section 10: STABILITY AND REACTIVITY

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	NIOSH IDLH	OSHA PEL	Mexico
Acetone 67-64-1	STEL: 500 ppm TWA: 250 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m³	TWA: 1000 ppm TWA: 2400 mg/m ³	TWA: 1000 ppm TWA: 2400 mg/m³ STEL: 1260 ppm STEL: 3000 mg/m³
2,2,4-Trimethylpentane 540-84-1	TWA: 300 ppm	-	-	-

Chemical Name	Argentina	Brazil	Chile	Venezuela
Acetone	TWA: 500 ppm	TWA: 780 ppm	TWA: 438 ppm	STEL: 750 ppm
67-64-1	STEL: 750 ppm	TWA: 1870 mg/m ³	TWA: 1040 mg/m ³	TWA: 500 ppm
2,2,4-Trimethylpentane	TWA: 300 ppm	-	=	-
540-84-1				

8.2. Exposure Controls

Engineering Controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment [PPE]

Eye/Face Protection Tight sealing safety goggles. Face protection shield.

Skin and Body Protection Wear suitable chemical resistant gloves. The selection of suitable gloves does not only

depend on the material, but also on further marks of quality and various manufacturers.

Respiratory Protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive pressure supplied air respirators may be

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and

clothing is recommended. Wash contaminated clothing before reuse.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical StateLiquidAppearanceAerosolColorColorlessOdorSolvent

Odor Threshold No information available

Property Values Remarks • Method

pH No information available
Melting Point/Freezing Point No information available

Boiling Point No information available °C / °F

Flash Point -50 °C / -58 °F Evaporation Rate No information available

Flammability (solid, gas) No information available Not applicable for liquids

Page 5/10

V207501 Revision Date 17-May-2017
Bostik GlideCote Supersedes Date: 18-Sep-2015

Version 1.03

Flammability Limit in Air

Relative Density

Upper Flammability Limit Lower Flammability Limit Vapor Pressure Vapor Density No information available No information available No information available No information available No information available

Water Solubility Solubility in Other

Solvents

Partition Coefficient Autoignition Temperature

Decomposition Temperature

No information available No information available

No information available

No information available

Kinematic Viscosity No information available

Dynamic Viscosity No information available

Explosive PropertiesOxidizing Properties
No information available
No information available

9.2. Other Information

Softening PointNo information availableMolecular WeightNo information availableSolvent Content (%)No information available

 Solid Content (%)
 2.3

 Density
 .800 g/ml

 VOC
 < 20 %</td>

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

None under normal use conditions.

10.2. Chemical Stability

Stable under recommended storage conditions.

10.3. Possibility of Hazardous Reactions

None under normal processing.

10.4. Conditions to Avoid

Heating causes rise in pressure with risk of bursting.

10.5. Incompatible Materials

None known based on information supplied.

10.6. Hazardous Decomposition Products

None known based on information supplied.

Section 11: TOXICOLOGY INFORMATION

V207501 Revision Date 17-May-2017
Bostik GlideCote Supersedes Date: 18-Sep-2015

Version 1.03

11.1. Information on Toxicological Effects

Product InformationNo Data AvailableInhalationNo Data AvailableEye contactNo Data AvailableSkin ContactNo Data AvailableIngestionNo Data Available

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	>15800 mg/Kg (rat)	= 79 mg/l(Rat) 4 h
Naphtha, petroleum, light alkylate 64741-66-8	> 7000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 6.31 mg/L (Rat) 4 h
2,2,4-Trimethylpentane 540-84-1	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 14.38 mg/L (Rat)4 h
Naphtha, petroleum, hydrotreated heavy, <0.1% Benzene 64742-48-9	> 6000 mg/kg(Rat)	> 3160 mg/kg(Rabbit)	LC50 Vapour (4h) >5020 mg/m³ (Rat)

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

No information available. **Symptoms** Skin Corrosion/Irritation No information available. Serious Eye Damage/Eye Irritation No information available. No information available. Irritation No information available. Corrosivity Sensitization No information available. **Germ Cell Mutagenicity** No information available. No information available. **Reproductive Toxicity** No information available. **Developmental Toxicity Teratogenicity** No information available. **STOT - Single Exposure** No information available. No information available. **STOT - Repeated Exposure Chronic Toxicity** Avoid repeated exposure.

Target Organ Effects Central nervous system, Eyes, Respiratory system, Skin.

Aspiration Hazard No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to	Crustacea
			Microorganisms	
Acetone		LC50 96 h 4.74 - 6.33 mL/L	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704
67-64-1		(Oncorhynchus mykiss)		mg/L (Daphnia magna
				Static)
Naphtha, petroleum, light	EC50 72 h = 6.4 mg/L			LC50 48 h = 2 mg/L
alkylate	(Pseudokirchneriella			(Mysidopsis bahia)
64741-66-8	subcapitata)			
Naphtha, petroleum,	EL50 (72h) > 1000 mg/l	LC50 96 h = 2200 mg/L		LL50 (48h) > 1000 mg/l
hydrotreated heavy, <0.1%	(Pseudokirchneriella	(Pimephales promelas)		(Daphnia magna)

V207501 Revision Date 17-May-2017
Bostik GlideCote Supersedes Date: 18-Sep-2015

Version 1.03

Benzene	subcapitata)		OECD 202
64742-48-9	OECD 201		

12.2. Persistence and Degradability

No information available.

12.3. Bioaccumulative Potential

No information available.

12.4. Mobility in Soil

No information available.

12.5 Other adverse effects

No information available

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste Treatment Methods

Disposal of Wastes It is the responsibility of the waste generator to determine the toxicity and physical

properties of the material generated to determine the proper waste identification and

disposal methods in compliance with applicable regulations

Contaminated Packaging Dispose of in accordance with federal, state and local regulations

Section 14: TRANSPORTATION INFORMATION

Note: Per 49 CFR 173.306(a)(3), our aerosol product is considered a Limited Quantity for all

modes of transportation and ORM-D no longer applies to the product

DOT

UN/ID No UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1
Subsidiary Class 8

Reportable Quantity (RQ) (2,2,4-Trimethylpentane: RQ (kg)= 454.00, Acetone: RQ (kg)= 2270.00)

Special Provisions N82

Description UN1950, Aerosols, 2.1

Emergency Response Guide

Number

126

IATA

UN/ID No UN1950

Proper Shipping Name Aerosols, flammable

Hazard Class 2.1 ERG Code 10L

Special Provisions A145, A167, A802

Description UN1950, Aerosols, flammable, 2.1

IMDG

UN/ID No UN1950

Proper Shipping Name Aerosols (2,2,4-Trimethylpentane), Marine Pollutant

Hazard Class 2.1 **EmS-No** F-D, S-U

V207501 Bostik GlideCote Revision Date 17-May-2017 Supersedes Date: 18-Sep-2015

Version 1.03

Special Provisions 63,190, 277, 327, 344, 959

Description UN1950, Aerosols (2,2,4-Trimethylpentane), 2.1, (-50°C c.c.), Marine Pollutant

Section 15: REGULATORY INFORMATION

Global Inventories

TSCA	Listed
DSL	Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

Listed - The components of this product are either listed or exempt from listing on inventory.

Not Listed - One or more components of this product are not listed on inventory.

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

WHMIS Hazard Class

A - Compressed gases B5 - Flammable aerosol D2B - Toxic materials



CADA 212

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute Health Hazard yes
Chronic Health Hazard No
Fire Hazard yes
Sudden release of pressure hazard No
Reactive Hazard No

California Proposition 65

This product does not contain one or more substances listed on Proposition 65 at or above 0.01 wt. %.

Europe

Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU

This product does not contain Lead (7439-92-1), Cadmium (7440-43-9), Mercury (7439-97-6), Hexavalent chromium (7440-47-3), Polybrominated biphenyls (PBB), and Polybrominated diphenyl ethers (PBDE) above the regulated limit mentioned in this regulation.

EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No.

V207501 Bostik GlideCote Revision Date 17-May-2017 Supersedes Date: 18-Sep-2015

Version 1.03

1907/2006 (REACH), Article 59)

Section 16: OTHER INFORMATION

Product(s) Covered

HMIS Health Hazards 2 Flammability 4 Physical Hazards 0 Personal Protection X

Key or Legend to Abbreviations and Acronyms Used in the Safety Data Sheet

No information available

Key Literature References and Sources for Data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision Date 17-May-2017

Revision Note SDS sections updated, 9.

Training Advice No information available

Additional information No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet