

SAFETY DATA SHEET

1. Identification

Product identifier: Methyl Isobutyl Ketone

Other means of identification

Product No.: 9212, 4855, 6247, 5923, 5384, 9405, 9322

Recommended use and restriction on use

Recommended use: Not available.

Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Manufacturer

Company Name: Avantor Performance Materials, Inc.
Address: 3477 Corporate Parkway, Suite 200
Center Valley, PA 18034

Telephone: Customer Service: 855-282-6867

Fax:
Contact Person: Environmental Health & Safety
e-mail: info@avantormaterials.com

Emergency telephone number:

24 Hour Emergency: 908-859-2151

Chemtrec: 800-424-9300

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids Category 2

Health Hazards

Acute toxicity (Inhalation - vapor) Category 4
Serious Eye Damage/Eye Irritation Category 2A
Specific Target Organ Toxicity - Category 3
Single Exposure

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Highly flammable liquid and vapor.
Harmful if inhaled.
Causes serious eye irritation.
May cause respiratory irritation.

Precautionary Statement

Prevention:	Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Wash hands thoroughly after handling.
Response:	In case of fire: Use water spray, foam, dry powder or carbon dioxide for extinction. Call a POISON CENTER or doctor/physician if you feel unwell. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Storage:	Store in a well-ventilated place. Keep cool. Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Other hazards which do not result in GHS classification:

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Substances

Chemical Identity	Common name and synonyms	CAS number	Content in percent (%) [*]
METHYL ISOBUTYL KETONE		108-10-1	90 - 100%

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

General information:	Get medical advice/attention if you feel unwell. Show this safety data sheet to the doctor in attendance.
Ingestion:	Rinse mouth. Call a POISON CENTER or doctor/physician if you feel unwell.
Inhalation:	Move to fresh air. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin Contact:	Wash skin thoroughly with soap and water. If skin irritation occurs: Get medical advice/attention.
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Call a physician or poison control center immediately.

Most important symptoms/effects, acute and delayed

Symptoms: Irritating to eyes, respiratory system and skin.

Indication of immediate medical attention and special treatment needed

Treatment: Treat symptomatically. Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Flammable liquid and vapor.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Water spray, foam, dry powder or carbon dioxide.

Unsuitable extinguishing media: Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from the chemical: Vapors may cause a flash fire or ignite explosively. Vapors may travel considerable distance to a source of ignition and flash back. Prevent buildup of vapors or gases to explosive concentrations. Heat may cause the containers to explode.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep unauthorized personnel away. Keep upwind. Use personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. See Section 8 of the MSDS for Personal Protective Equipment.

Methods and material for containment and cleaning up: Eliminate all ignition sources if safe to do so. Take precautionary measures against static discharges. Stop leak if possible without any risk. Use only non-sparking tools. Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Clean surface thoroughly to remove residual contamination. Dike far ahead of larger spill for later recovery and disposal.

Notification Procedures: Prevent entry into waterways, sewer, basements or confined areas. Inform authorities if large amounts are involved.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling:	DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take precautionary measures against static discharges. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Wear protective gloves/protective clothing/eye protection/face protection. Avoid contact with eyes, skin, and clothing. Use only with adequate ventilation. Wash hands thoroughly after handling.
Conditions for safe storage, including any incompatibilities:	Keep away from food, drink and animal feeding stuffs. Keep container tightly closed in a cool, well-ventilated place. Ground container and transfer equipment to eliminate static electric sparks. Comply with all national, state, and local codes pertaining to the storage, handling, dispensing, and disposal of flammable liquids.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
METHYL ISOBUTYL KETONE	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	75 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	300 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	205 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	PEL	410 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	205 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	300 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
METHYL ISOBUTYL KETONE (methyl isobutyl ketone: Sampling time: End of shift.)	1 mg/l (Urine)	ACGIH BEL (03 2013)

Appropriate Engineering Controls

No data available.

Individual protection measures, such as personal protective equipment

General information: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. An eye wash and safety shower must be available in the immediate work area. Use explosion-proof ventilation equipment.

Eye/face protection: Wear safety glasses with side shields (or goggles). Wear safety glasses with side shields (or goggles) and a face shield.

Skin Protection

Hand Protection:	Wear protective gloves.
Other:	Wear suitable protective clothing.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
Hygiene measures:	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

9. Physical and chemical properties

Appearance

Physical state:	Liquid Liquid
Form:	Liquid
Color:	Colorless
Odor:	Characteristic
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	-84 °C
Initial boiling point and boiling range:	117 °C
Flash Point:	14 °C (Closed Cup)
Evaporation rate:	5.6 ether=1
Flammability (solid, gas):	No data available.
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	12 %(V)
Flammability limit - lower (%):	8 %(V)
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	2.65 kPa (20 °C)
Vapor density:	3.5 AIR=1
Relative density:	0.80 (20 °C)
Solubility(ies)	
Solubility in water:	19 g/l (25 °C) Slightly Soluble Slightly Soluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	1.31
Auto-ignition temperature:	840 °F
Decomposition temperature:	No data available.
Viscosity:	No data available.
Other information	
Molecular weight:	100.16 g/mol (C ₆ H ₁₂ O)

10. Stability and reactivity

Reactivity:	No dangerous reaction known under conditions of normal use.
Chemical Stability:	Material is stable under normal conditions.

Possibility of Hazardous Reactions:	Hazardous polymerization does not occur.
Conditions to Avoid:	Heat, sparks, flames. Contact with incompatible materials. Exposure to air.
Incompatible Materials:	Strong oxidizing agents. Strong acids.
Hazardous Decomposition Products:	Thermal decomposition may release oxides of carbon.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be harmful if swallowed.
Inhalation:	Harmful if inhaled.
Skin Contact:	Causes mild skin irritation.
Eye contact:	Causes serious eye irritation.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral Product:	LD 50 (Rat): 2,080 mg/kg
Dermal Product:	LD 50 (Rabbit): > 16,000 mg/kg
Inhalation Product:	LC 50 (Rat, 4 h): 12.4 mg/l Vapour
Repeated Dose Toxicity Product:	No data available.

Skin Corrosion/Irritation Product:	Causes mild skin irritation.
---	------------------------------

Serious Eye Damage/Eye Irritation Product:	Causes serious eye irritation.
---	--------------------------------

Respiratory or Skin Sensitization Product:	Not a skin sensitizer.
---	------------------------

Carcinogenicity Product:	No data available.
---------------------------------	--------------------

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

METHYL ISOBUTYL KETONE	Overall evaluation: 2B. Possibly carcinogenic to humans.
------------------------------	--

US. National Toxicology Program (NTP) Report on Carcinogens:
No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):
No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No mutagenic components identified

In vivo

Product: No mutagenic components identified

Reproductive Toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: Respiratory tract irritation.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: Not classified

Other Effects: None known.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

METHYL ISOBUTYL KETONE
LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 496 - 514 mg/l Mortality
LC 50 (Carp (*Leuciscus idus melanotus*), 48 h): 672 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

METHYL ISOBUTYL KETONE
LC 50 (Brine shrimp (*Artemia salina*), 24 h): 1,230 mg/l Mortality
LC 50 (Water flea (*Daphnia magna*), 24 h): 4,280 mg/l Mortality

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: There are no data on the degradability of this product.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential**Bioconcentration Factor (BCF)****Product:** No data available on bioaccumulation.**Partition Coefficient n-octanol / water (log Kow)****Product:** Log Kow: 1.31**Mobility in Soil:** The product is partly soluble in water. May spread in the aquatic environment.**Other Adverse Effects:** The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.**13. Disposal considerations****Disposal instructions:** Discharge, treatment, or disposal may be subject to national, state, or local laws.**Contaminated Packaging:** Since emptied containers retain product residue, follow label warnings even after container is emptied.**14. Transport information****DOT**

UN Number:	UN 1245
UN Proper Shipping Name:	Methyl isobutyl ketone
Transport Hazard Class(es)	
Class(es):	3
Label(s):	3
Packing Group:	II
Marine Pollutant:	No

IMDG

UN Number:	UN 1245
UN Proper Shipping Name:	METHYL ISOBUTYL KETONE
Transport Hazard Class(es)	
Class(es):	3
Label(s):	3
EmS No.:	F-E, S-D
Packing Group:	II
Marine Pollutant:	No

IATA

UN Number:	UN 1245
Proper Shipping Name:	Methyl isobutyl ketone
Transport Hazard Class(es):	
Class(es):	3
Label(s):	3
Marine Pollutant:	No
Packing Group:	II

15. Regulatory information**US Federal Regulations****TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

METHYL ISOBUTYL KETONE Reportable quantity: 5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)
Hazard categories
☒ Acute (Immediate) ☒ Chronic (Delayed) ☒ Fire ☐ Reactive ☐ Pressure Generating

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

Chemical Identity	RQ
METHYL ISOBUTYL KETONE	5000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
METHYL ISOBUTYL KETONE	500 lbs

SARA 313 (TRI Reporting)

Chemical Identity	Reporting threshold for other users	Reporting threshold for manufacturing and processing
METHYL ISOBUTYL KETONE	10000 lbs	25000 lbs.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations
US. California Proposition 65

METHYL ISOBUTYL KETONE	Carcinogenic.
METHYL ISOBUTYL KETONE	Developmental toxin.

US. New Jersey Worker and Community Right-to-Know Act

METHYL ISOBUTYL KETONE	Listed
------------------------	--------

US. Massachusetts RTK - Substance List

METHYL ISOBUTYL KETONE	Listed
------------------------	--------

US. Pennsylvania RTK - Hazardous Substances

METHYL ISOBUTYL KETONE	Listed
------------------------	--------

US. Rhode Island RTK

METHYL ISOBUTYL KETONE	Listed
------------------------	--------

Inventory Status:

Australia AICS:	On or in compliance with the inventory
Canada DSL Inventory List:	On or in compliance with the inventory
EU EINECS List:	On or in compliance with the inventory
EU ELINCS List:	Not in compliance with the inventory.
Japan (ENCS) List:	Not in compliance with the inventory.
EU No Longer Polymers List:	Not in compliance with the inventory.
China Inv. Existing Chemical Substances:	On or in compliance with the inventory
Korea Existing Chemicals Inv. (KECI):	On or in compliance with the inventory
Canada NDSL Inventory:	Not in compliance with the inventory.
Philippines PICCS:	On or in compliance with the inventory
US TSCA Inventory:	On or in compliance with the inventory
New Zealand Inventory of Chemicals:	On or in compliance with the inventory
Japan ISHL Listing:	On or in compliance with the inventory
Japan Pharmacopoeia Listing:	Not in compliance with the inventory.

16. Other information, including date of preparation or last revision

NFPA Hazard ID



Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe

Issue Date:	01-08-2015
Revision Date:	No data available.
Version #:	1.1
Further Information:	No data available.

Disclaimer:

THE INFORMATION PRESENTED IN THIS MATERIAL SAFETY DATA SHEET (MSDS/SDS) WAS PREPARED BY TECHNICAL PERSONNEL BASED ON DATA THAT THEY BELIEVE IN THEIR GOOD FAITH JUDGMENT IS ACCURATE. HOWEVER, THE INFORMATION PROVIDED HEREIN IS PROVIDED "AS IS," AND AVANTOR PERFORMANCE MATERIALS MAKES AND GIVES NO REPRESENTATIONS OR WARRANTIES WHATSOEVER, AND EXPRESSLY DISCLAIMS ALL WARRANTIES REGARDING SUCH INFORMATION AND THE PRODUCT TO WHICH IT RELATES, WHETHER EXPRESS, IMPLIED, OR STATUTORY, INCLUDING WITHOUT LIMITATION<(>,<)> WARRANTIES OF ACCURACY, COMPLETENESS, MERCHANTABILITY, NON-INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY, STABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, AND ANY WARRANTIES ARISING FROM COURSE OF DEALING, COURSE OF PERFORMANCE, OR USAGE OF TRADE. THIS MSDS/SDS IS INTENDED ONLY AS A GUIDE TO THE APPROPRIATE PRECAUTIONARY HANDLING OF THE MATERIAL BY A PROPERLY TRAINED PERSON USING THIS PRODUCT, AND IS NOT INTENDED TO BE COMPREHENSIVE AS TO THE MANNER AND CONDITIONS OF USE, HANDLING, STORAGE, OR DISPOSAL OF THE PRODUCT. INDIVIDUALS RECEIVING THIS MSDS/SDS MUST ALWAYS EXERCISE THEIR OWN INDEPENDENT JUDGMENT IN DETERMINING THE APPROPRIATENESS OF SUCH ISSUES. ACCORDINGLY, AVANTOR PERFORMANCE MATERIALS ASSUMES NO LIABILITY WHATSOEVER FOR THE USE OF OR RELIANCE UPON THIS INFORMATION. NO SUGGESTIONS FOR USE ARE INTENDED AS, AND NOTHING HEREIN SHALL BE CONSTRUED AS, A RECOMMENDATION TO INFRINGE ANY EXISTING PATENTS OR TO VIOLATE ANY FEDERAL, STATE, LOCAL, OR FOREIGN LAWS. AVANTOR PERFORMANCE MATERIALS REMINDS YOU THAT IT IS YOUR LEGAL DUTY TO MAKE ALL INFORMATION IN THIS MSDS/SDS AVAILABLE TO YOUR EMPLOYEES.