

SAFETY DATA SHEET

Version 8.6
Revision Date 01/24/2022
Print Date 06/07/2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifiers**

Product name : 1,2-Propylene oxide for synthesis

Product Number : 8.07027
Catalogue No. : 807027
Brand : Millipore
Index-No. : 603-055-00-4
CAS-No. : 75-56-9

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Chemical for synthesis

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-
527-3887 CHEMTREC (International) 24
Hours/day; 7 Days/week

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Flammable liquids (Category 1), H224
Acute toxicity, Oral (Category 4), H302
Acute toxicity, Inhalation (Category 3), H331
Acute toxicity, Dermal (Category 3), H311
Eye irritation (Category 2A), H319
Germ cell mutagenicity (Category 1B), H340
Carcinogenicity (Category 1B), H350
Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335
Short-term (acute) aquatic hazard (Category 3), H402

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Millipore - 8.07027

Page 1 of 11

Pictogram



Signal word

Danger

Hazard statement(s)

H224	Extremely flammable liquid and vapor.
H302	Harmful if swallowed.
H311 + H331	Toxic in contact with skin or if inhaled.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H340	May cause genetic defects.
H350	May cause cancer.
H402	Harmful to aquatic life.

Precautionary statement(s)

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P312 + P330	IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P311	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula : C₃H₆O
Molecular weight : 58.08 g/mol
CAS-No. : 75-56-9
EC-No. : 200-879-2
Index-No. : 603-055-00-4

Component	Classification	Concentration
propylene oxide		
	Flam. Liq. 1; Acute Tox. 4; Acute Tox. 3; Eye Irrit. 2A; Muta. 1B; Carc. 1B; STOT SE 3; Aquatic Acute 3; H224, H302, H331, H311, H319, H340, H350, H335, H402	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Millipore - 8.07027

Page 4 of 11

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.
For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons.

Recommended storage temperature see product label.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
propylene oxide	75-56-9	TWA	2 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Dermal Sensitization Confirmed animal carcinogen with unknown relevance to humans		
		Potential Occupational Carcinogen		
		TWA	100 ppm 240 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		PEL	2 ppm 4.75 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact
Material: butyl-rubber
Minimum layer thickness: 0.7 mm
Break through time: 30 min
Material tested: Butoject® (KCL 898)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance	Form: liquid Color: colorless
b) Odor	sweet, ether-like
c) Odor Threshold	No data available
d) pH	No data available
e) Melting point/freezing point	Melting point: ca.-112 °C (ca.-170 °F) at 1,013 hPa
f) Initial boiling point and boiling range	34.3 °C 93.7 °F at 1,013 hPa
g) Flash point	-38 °C (-36 °F) - Equilibrium method - closed cup
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	Upper explosion limit: 36 - 45 %(V) Lower explosion limit: 1.9 %(V)
k) Vapor pressure	2,028.5 hPa at 55 °C (131 °F)
l) Vapor density	2.01 - (Air = 1.0)
m) Density	0.83 g/cm ³ at 20 °C (68 °F) - OECD Test Guideline 109
Relative density	0.8320 °C - Regulation (EC) No. 440/2008, Annex, A.3
n) Water solubility	425 g/l at 20 °C (68 °F) - OECD Test Guideline 105
o) Partition coefficient: n-octanol/water	log Pow: 0.03 - Bioaccumulation is not expected.
p) Autoignition temperature	> 400 °C (> 752 °F) at 1,005 - 1,018 hPa - Tested according to Directive 92/69/EEC.

- | | |
|------------------------------|--|
| q) Decomposition temperature | No data available |
| r) Viscosity | 0.44 mm ² /s at 0 °C (32 °F) - OECD Test Guideline 114 - 0.37 mm ² /s at 20 °C (68 °F) - OECD Test Guideline 114 - |
| s) Explosive properties | No data available |
| t) Oxidizing properties | none |

9.2 Other safety information

- | | |
|------------------------|---|
| Surface tension | 71.5 mN/m at 1.06g/l at 21 °C (70 °F) - Surface tension |
| Relative vapor density | 2.01 - (Air = 1.0) |

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Risk of ignition or formation of inflammable gases or vapours with:

Hydrogen fluoride

Oxidizing agents

Nitric acid

Risk of explosion with:

polymerisation initiators

Oxygen

Exothermic reaction with:

Strong oxidizing agents

Ammonia

halogens

alkali hydroxides

polymerization

alkalines

Amines

metallic oxides

metallic chlorides

chlorosulfonic acid

Hydrogen chloride gas

fuming sulfuric acid

aluminium chloride

acids

10.4 Conditions to avoid

Heat.

Warming.

10.5 Incompatible materials

rubber, various plastics, Copper

10.6 Hazardous decomposition products

Peroxides

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male and female - 382 - 587 mg/kg
(OECD Test Guideline 401)

LC50 Inhalation - Rat - male and female - 4 h - 9.95 mg/l - vapor

(OECD Test Guideline 403)

LD50 Dermal - Rabbit - 950 mg/kg

Remarks: (ECHA)

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 4 h

(OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Severe irritations

(Draize Test)

Remarks: (RTECS)

Respiratory or skin sensitization

Split adjuvant test - Guinea pig

Result: negative

Remarks: (ECHA)

Germ cell mutagenicity

May cause genetic defects.

Test Type: Ames test

Test system: Escherichia coli/Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: positive

Test Type: In vitro mammalian cell gene mutation test

Test system: Mouse lymphoma test

Metabolic activation: without metabolic activation

Method: OECD Test Guideline 476

Result: positive

Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Metabolic activation: without metabolic activation

Method: OECD Test Guideline 473

Result: positive

Test Type: Mutagenicity (mammal cell test): micronucleus.

Species: Rat

Cell type: Red blood cells (erythrocytes)

Application Route: inhalation (vapor)

Method: OECD Test Guideline 474

Millipore - 8.07027

Page 8 of 11

Result: negative

Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Species: Rat

Application Route: inhalation (vapor)

Method: OECD Test Guideline 475

Result: negative

Carcinogenicity

Presumed to have carcinogenic potential for humans

IARC: 2B - Group 2B: Possibly carcinogenic to humans (propylene oxide)

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Inhalation - May cause respiratory irritation. - Respiratory system

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., Cough, Shortness of breath, Headache, Nausea
To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish	static test LC50 - Oncorhynchus mykiss (rainbow trout) - 52 mg/l - 96 h (US-EPA)
Toxicity to daphnia and other aquatic invertebrates	static test EC50 - Daphnia magna (Water flea) - 350 mg/l - 48 h (US-EPA)
Toxicity to algae	static test ErC50 - Pseudokirchneriella subcapitata (green algae) - 240 mg/l - 96 h (US-EPA)
Toxicity to bacteria	EC10 - Bacteria - 10 mg/l - 17 h

12.2 Persistence and degradability

Millipore - 8.07027

Page 9 of 11

Biodegradability aerobic - Exposure time 28 d
Result: 96 % - Readily biodegradable.
(OECD Test Guideline 301C)

12.3 Bioaccumulative potential

Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Biological effects:

Forms toxic mixtures in water, dilution measures notwithstanding.
Discharge into the environment must be avoided.

Stability in water - 15.7 yr
Remarks: reaction with hydroxyl radicals(calculated)
 - ca.11 d
Remarks: Hydrolysis

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

DOT (US)

UN number: 1280 Class: 3 Packing group: I
Proper shipping name: Propylene oxide
Reportable Quantity (RQ): 100 lbs
Poison Inhalation Hazard: No

IMDG

UN number: 1280 Class: 3 Packing group: I EMS-No: F-E, S-D
Proper shipping name: PROPYLENE OXIDE

IATA

UN number: 1280 Class: 3 Packing group: I
Proper shipping name: Propylene oxide

SECTION 15: Regulatory information

SARA 302 Components

propylene oxide

CAS-No.
75-56-9

Revision Date
2008-11-03

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

propylene oxide

CAS-No.
75-56-9

Revision Date
2008-11-03

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

SECTION 16: Other information

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 8.6

Revision Date: 01/24/2022

Print Date: 06/07/2022